

MFBL (Make First/Break Last) Connector System (Continued)

Type C Pin Assemblies

Number of Positions	Rows Loaded*	DIN Level	Part Numbers*
96	—	II	536437
			148123**
			536366 [†]
48	—	II	148330**
			148019
			536751 [†]
120	—	II	148002
			148032 [†]

*Refer to customer drawing for specific loading patterns and part numbers.

**Three levels of sequencing.

[†]With Boardlocks[‡]Reverse PolarizedType R Pin Assemblies,
4.57 [.180] Solder Post
Length

Number of Positions	Rows Loaded*	DIN Level	Part Numbers*
96	—	II	536744

*Refer to customer drawing for specific loading patterns and part numbers.

Type R Pin Assemblies,
6.35 [.250] ACTION PIN
(Press-Fit) Post Length,
Programmable

(for 2.36 [.093] Min. Thick PC Board)

Number of Positions	Rows Loaded	DIN Level	Part Numbers
96	A,B,C	II	536019-5
64	A,C	II	536098-5
48	A,B,C	II	536092-5
32	A,C	II	536100-5
120	A,B,C	II	536094-5
150	A,B,C	II	536096-5

Type R Pin Assemblies,
Eye of the Needle
Compliant Pin, 4.06 [.160]
Post Length, Programmable

Number of Positions	Rows Loaded	DIN Level	Part Numbers
48	A,B,C	II	148472-4
96	A,B,C	II	148304-4
120	A,B,C	II	148389-4
150	A,B,C	II	148306-4

Type R Pin Assemblies,
13.23 [.521] ACTION PIN
(Press-Fit) Post Length,
Programmable

(for 2.36 [.093] Min. Thick PC Board)

Number of Positions	Rows Loaded	DIN Level	Part Numbers
96	A,B,C	II	536067-5
64	A,C	II	536099-5
48	A,B,C	II	536093-5
32	A,C	II	536101-5
120	A,B,C	II	536095-5
150	A,B,C	II	536097-5