Distributed by:

JAMECO

ELECTRONICS

www.Jameco.com + 1-800-831-4242

The content and copyrights of the attached material are the property of its owner.

Jameco Part Number 833053



DS485

Low Power RS-485/RS-422 Multipoint Transceiver

General Description

The DS485 is a low-power transceiver for RS-485 and RS-422 communication. The device contains one driver and one receiver. The drivers slew rate allows for operation up to 2.5 Mbps (see Applications Information section).

The transceiver draws 200 μA of supply current when unloaded or fully loaded with the driver disabled and operates from a single +5V supply.

The driver is short-circuit current limited and is protected against excessive power dissipation by thermal shutdown circuitry that places the driver outputs into TRI-STATE® (High Impedance state) under fault conditions. The driver guarantees a minimum of 1.5V differential output voltage with maximum loading across the common mode range $(V_{\rm OD3})$.


The receiver has a failsafe feature that guarantees a logichigh output if the input is open circuit.

The DS485 is available in surface mount and DIP packages and is characterized for Industrial and Commercial temperature range operation.

Features

- Meets TIA/EIA RS-485 multipoint standard
- Guaranteed full load output voltage (V _{OD3})
- Low quiescent current: 200 µA typ
- -7V to +12V common-mode input voltage range
- TRI-STATE outputs on driver and receiver
- AC performance:
 - Driver transition time: 25 ns typ
 - Driver propagation delay: 40 ns typ
 - Driver skew: 1 ns typ
 - Receiver propagation delay: 200 ns typ
 - Receiver skew: 20 ns typ
- Half-duplex flow through pinout
- Operates from a single 5V supply
- Allows up to 32 transceivers on the bus
- Current-limiting and thermal shutdown for driver overload protection
- Industrial temperature range operation
- Pin and functional compatible with MAX485 and LTC485

Connection and Logic Diagram



Order Number	Temp. Range	Package/###		
DS485N	0°C to +70°C	DIP/N08E		
DS485M	0°C to +70°C	SOP/M08A		
DS485TN	-40°C to +85°C	DIP/N08E		
DS485TM	-40°C to +85°C	SOP/M08A		

Truth Table

DRIVER SECTION							
RE*	DE	DI	Α	В			
Х	Н	Н	Н	L			
X	Н	L	L	Н			
X	L	Х	Z	Z			
RECEIVER SECTION							
RE*	DE	A	-B	RO			
L	L	≥+0.2V		Н			
L	L	≤–0.2V		L			

Χ

OPEN*

*Note: Non Terminated, Open Input only

Χ

X = indeterminate

Н

Z = TRI-STATE

Ζ

Н

Absolute Maximum Ratings (Note 1)

If Military/Aerospace specified devices are required, please contact the National Semiconductor Sales Office/ Distributors for availability and specifications.

Supply Voltage (V_{CC}) +12V Enable Input Voltage (RE*, DE) -0.5V to (V_{CC} + 0.5V) Driver Input Voltage (DI) -0.5V to (V_{CC} + 0.5V) Driver Output Voltage (A, B) -14V to +14V Receiver Input Voltage (A, B) -0.5V to (V_{CC} + 0.5V) Maximum Package Power Dissipation @ +25°C

M Package 1.19W N Package 0.74W

Derate M Package 9.5 mW/°C above +25°C

Derate N Package 6.0 mW/°C above +25°C

Maximum Package Power Dissipation @ +70°C

M Package 0.76W

N Package 0.47W Storage Temperature Range -65°C to $+150^{\circ}\text{C}$ Lead Temperature Range (Soldering, 4 sec.) $+260^{\circ}\text{C}$ ESD (HBM) $\geq 2 \text{ kV}$

Recommended Operating Conditions

	Min	Тур	Max	Units
Supply Voltage (V _{CC})	+4.75	+5.0	+5.25	V
Operating Free Air				
Temperature (T _A)				
DS485	0	+25	+70	°C
DS485T	-40	+25	+85	°C
Bus Common Mode Voltage	-7		+12	V

Electrical Characteristics

Over Supply Voltage and Operating Temperature Ranges, unless otherwise specified (Notes 2, 3)

Symbol	Parameter	Conditions	Pin	Min	Тур	Max	Units
V _{OD1}	Differential Driver Output Voltage	(No Load)	A, B			5	V
V _{OD2}	Differential Driver Output Voltage	$R_L = 50\Omega$, (RS422), Figure 1	2		2.8		V
	with Load	$R_L = 27\Omega$, (RS485), Figure 1		1.5	2.3	5	V
ΔV_{OD}	Change in Magnitude of Output	$R_L = 27\Omega$ or 50Ω (Note 4)				0.2	IVI
	Differential Voltage						
V _{OD3}	Differential Driver Output Voltage—	R1 = 54Ω , R2 = 375Ω		1.5	2.0	5	V
	Full Load with Max V _{CM}	$V_{TEST} = -7V$ to +12V, Figure 5					
V _{oc}	Driver Common-Mode Output Voltage	$R_L = 27\Omega$ or 50Ω , Figure 1				3	V
ΔV_{OC}	Change in Magnitude of Common-Mode	$R_L = 27\Omega$ or 50Ω , Figure 1 (Note 4)				0.2	IVI
	Output Voltage						
V _{IH}	Input High Voltage		DI,	2.0			V
V _{IL}	Input Low Voltage		DE,			0.8	V
I _{IN1}	Input Current	$V_{IN} = 0V \text{ or } V_{CC}$	RE*			±2	μA
I _{IN2}	Input Current (Note 5)	$V_{IN} = +12V$	A, B			1.0	mA
	$DE = 0V, V_{CC} = 0V \text{ or } 5.25V$	$V_{IN} = -7V$				-0.8	mA
V_{TH}	Receiver Differential Threshold Voltage	$-7V \le V_{CM} \le +12V$		-0.2		0.2	V
ΔV_{TH}	Receiver Input Hysteresis	$V_{CM} = 0V$			70		mV
V _{OH}	Receiver Output High Voltage	$I_O = -4$ mA, $V_{ID} = 0.2V$	RO	3.5			V
V_{OL}	Receiver Output Low Voltage	$I_{O} = 4 \text{ mA}, V_{ID} = -0.2 \text{V}$				0.4	V
I _{OZR}	TRI-STATE Output Current at Receiver	$0.4V \le V_O \le 2.4V$				±1	μΑ
R _{IN}	Receiver Input Resistance	$-7V \le V_{IN} \le +12V$	A, B	12			kΩ
I _{CC}	No-Load Supply Current (Note 6)	$DE = V_{CC}$, $RE^* = 0V$ or V_{CC}	V _{CC}		200	900	μA
		DE = 0V, RE* = 0V or V_{CC}			200	500	μA
I _{OSD1}	Driver Short Circuit Current, V _O = HIGH	$-7V \le V_O \le +12V$	A, B	35		250	mA
I _{OSD2}	Driver Short Circuit Current, V _O = LOW	$-7V \le V_O \le +12V$		35		250	mA
I _{OSR}	Receiver Short Circuit Current	$0V \le V_O \le V_{CC}$	RO	7		85	mA

Switching Characteristics

Over Supply Voltage and Operating Temperature Ranges, unless otherwise specified (Notes 3, 7, 8)

Symbol	Parameter	Conditions	Min	Тур	Max	Units
t _{PLHD}	Driver Differential Propagation Delay—Low to High	$R_L = 54\Omega, C_L = 100 pF$	10	40	65	ns
t _{PHLD}	Driver Differential Propagation Delay—High to Low		10	39	65	ns
t _{SKEW}	Differential Skew t _{PHLD} - t _{PLHD}			1	10	ns
t _r	Driver Rise Time		3	25	40	ns
t _f	Driver Fall Time		3	25	40	ns
t _{zH}	Driver Enable to Output High	C _L = 100 pF			170	ns
t _{ZL}	Driver Enable to Output Low	C _L = 100 pF			170	ns
t _{LZ}	Driver Disable from Output Low	C _L = 15 pF			170	ns
t _{HZ}	Driver Disable from Output High	C _L = 15 pF			170	ns
t _{PLHD}	Receiver Differential Propagation Delay—Low to High	C _L = 15 pF (RO)	70	190	320	ns
t _{PHLD}	Receiver Differential Propagation Delay—High to Low		70	210	320	ns
t _{SKEW}	Differential Skew t _{PHLD} - t _{PLHD}			20	50	ns
t _{ZH}	Receiver Enable to Output High	C _L = 15 pF			110	ns
t _{ZL}	Receiver Enable to Output Low				110	ns
t _{LZ}	Receiver Disable from Output Low				110	ns
t _{HZ}	Receiver Disable from Output High				110	ns
f _{max}	Maximum Data Rate	(Note 9)	2.5			Mbps

Note 1: "Absolute Maximum Ratings" are those values beyond which the safety of the device cannot be guaranteed. They are not meant to imply that the devices should be operated at these limits. The table of "Electrical Characteristics" specifies conditions of device operation.

Note 2: Current into device pins is defined as positive. Current out of device pins is defined as negative. All voltages are referenced to ground except V_{OD1/2/3} and V_{ID}.

Note 3: All typicals are given for: $V_{CC} = +5.0V$, $T_A = +25$ °C.

Note 4: $\Delta IV_{OD}I$ and $\Delta IV_{OC}I$ are changes in magnitude of V_{OD} and V_{OC} respectively, that occur when the input changes state.

Note 5: I_{IN2} includes the receiver input current and driver TRI-STATE leakage current.

Note 6: Supply current specification is valid for loaded transmitters when DE = 0V or enabled (DE = H) with no load.

Note 7: f = 1 MHz, t_r and $t_f \le 6$ ns, $Z_O = 50\Omega$.

Note 8: C_L includes jig and probe capacitance.

Note 9: f_{max} is the guaranteed data rate for 50 ft of twisted pair cable. f_{max} may be conservatively determined from the ratio of driver transition time (t_r) to the data rate unit interval $(1/f_{max})$. Using a 10% ratio yields $f_{max} = (0.1)/40$ ns = 2.5 Mb/s. Higher data rates may be supported by allowing larger ratios.

Parameter Measurement Information




FIGURE 1. $V_{\rm OD}$




FIGURE 5. V_{OD3}




FIGURE 2.




FIGURE 6.




FIGURE 3.




FIGURE 7.




FIGURE 4.




FIGURE 8.

Parameter Measurement Information (Continued)




FIGURE 9.




FIGURE 10.




FIGURE 11.




FIGURE 12.

Parameter Measurement Information (Continued)




FIGURE 13.

Pin Descriptions

Pin #	I/O	Name	Function
1	0	RO	Receiver Output: If A > B by 200 mV, RO will be high; If A < B by 200 mV, RO will be low. RO will
			be high also if the inputs (A and B) are open (non-terminated).
2	I	RE*	Receiver Output Enable: RO is enabled when RE* is low; RO is in TRI-STATE when RE* is high.
3	I	DE	Driver Output Enable: The driver outputs (A and B) are enabled when DE is high; they are in TRI-STATE when DE is low. Pins A and B also function as the receiver input pins (see below).
4	I	DI	Driver Input: A low on DI forces A low and B high while a high on DI forces A high and B low when the driver is enabled.
5	NA	GND	Ground
6	I/O	Α	Non-inverting Driver Output and Receiver Input pin. Driver output levels conform to RS-485 signaling levels.
7	I/O	В	Inverting Driver Output and Receiver Input pin. Driver output levels conform to RS-485 signaling levels.
8	NA	V_{CC}	Power Supply: $4.75V \le V_{CC} \le 5.25V$

Related National Low Power RS-485 Transceivers

Part Number	Temperature	Number of	Comments		
	Range	XCVRs on Bus			
DS36C278	0°C to +70°C	128	Ultra Low Power Transceiver		
DS36C278T	-40°C to +85°C	64	Ultra Low Power Transceiver		
DS36C279	0°C to +70°C	128	Auto-Sleep Mode		
DS36C279T	-40°C to +85°C	64	Auto-Sleep Mode		
DS36C280	0°C to +70°C	128	Adjustable Slew Rate Control		
DS36C280T	-40°C to +85°C	64	Adjustable Slew Rate Control		


Applications Information

The DS485 is a low power transceiver designed for use in RS-485 multipoint applications. The DS485 can transmit data up to 2.5 Mbps based on a ratio of driver transition time to the unit interval (bit time) of 10%. This maximum data rate may be further limited by the interconnecting media. The DS485 provides a standard unit load to the RS-485 bus across the common mode range of -7V to +12V. This allows up to 32 transceivers (standard unit load) to be connected to the bus. More transceivers may be connected to the bus if they support a reduced unit load (see DS36C278). The DS485 also guarantees the driver's output differential voltage into a worst case load that models standard termination loads and 32 unit loads referenced to the maximum common mode voltage extremes. With a minimum of 1.5V swing into this load, a 1.3V differential noise margin is supported along with the standard common mode rejection range of the receivers.

Due to the multipoint nature of the bus, contention between drivers may occur. This will not cause damage to the drivers since they feature short-circuit protection and also thermal shutdown protection. Thermal shutdown senses die temperature and puts the driver outputs into TRI-STATE if a fault condition occurs that causes excessive power dissipation which can elevate the junction temperature to +150°C.


A typical multipoint application is shown in the following figure. Note that termination is typically required but is only located at the two ends of the cable (not on every node). Commonly pull up and pull down resistors may be required at one end of the bus to provide a failsafe bias. These resistors provide a bias to the line when all drivers are in TRI-STATE. See National Application Note 847 for a complete discussion of failsafe biasing of differention buses.


Multipoint RS-485 Application




Physical Dimensions inches (millimeters)


unless otherwise noted







Order Number DS485M or DS485TM NS Package Number M08A



Order Number DS485N or DS485TN NS Package Number N08E

Notes

National does not assume any responsibility for use of any circuitry described, no circuit patent licenses are implied and National reserves the right at any time without notice to change said circuitry and specifications.

For the most current product information visit us at www.national.com.

LIFE SUPPORT POLICY

NATIONAL'S PRODUCTS ARE NOT AUTHORIZED FOR USE AS CRITICAL COMPONENTS IN LIFE SUPPORT DEVICES OR SYSTEMS WITHOUT THE EXPRESS WRITTEN APPROVAL OF THE PRESIDENT AND GENERAL COUNSEL OF NATIONAL SEMICONDUCTOR CORPORATION. As used herein:

- 1. Life support devices or systems are devices or systems which, (a) are intended for surgical implant into the body, or (b) support or sustain life, and whose failure to perform when properly used in accordance with instructions for use provided in the labeling, can be reasonably expected to result in a significant injury to the user.
- A critical component is any component of a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.

BANNED SUBSTANCE COMPLIANCE

National Semiconductor certifies that the products and packing materials meet the provisions of the Customer Products Stewardship Specification (CSP-9-111C2) and the Banned Substances and Materials of Interest Specification (CSP-9-111S2) and contain no "Banned Substances" as defined in CSP-9-111S2.



National Semiconductor Americas Customer Support Center

Email: new.feedback@nsc.com Tel: 1-800-272-9959

www.national.com

National Semiconductor
Europe Customer Support Center
Fax: +49 (0) 180-530 85 86
Email: europe.support@nsc.con
Deutsch Tel: +49 (0) 69 9508 6208

Email: europe.support@nsc.com
Deutsch Tel: +49 (0) 69 9508 6208
English Tel: +44 (0) 870 24 0 2171
Français Tel: +33 (0) 1 41 91 8790

National Semiconductor
Asia Pacific Customer
Support Center
Email: ap.support@nsc.com

National Semiconductor Japan Customer Support Center Fax: 81-3-5639-7507 Email: jpn.feedback@nsc.com Tel: 81-3-5639-7560