
MAX3222 3-V TO 5.5-V MULTICHANNEL RS-232 LINE DRIVER/RECEIVER WITH \pm 15-kV ESD PROTECTION

SLLS408G - JANUARY 2000 - REVISED MARCH 2004

- RS-232 Bus-Pin ESD Protection Exceeds ±15 kV Using Human-Body Model (HBM)
- Meets or Exceeds the Requirements of TIA/EIA-232-F and ITU v.28 Standards
- Operates With 3-V to 5.5-V V_{CC} Supply
- Operates Up To 250 kbit/s
- Two Drivers and Two Receivers
- Low Standby Current . . . 1 μA Typical
- External Capacitors . . . 4 × 0.1 μF
- Accepts 5-V Logic Input With 3.3-V Supply
- Alternative High-Speed Pin-Compatible Device (1 Mbit/s)
 - SNx5C3222
- Applications
 - Battery-Powered Systems, PDAs, Notebooks, Laptops, Palmtop PCs, and Hand-Held Equipment

DB, DW, OR PW PACKAGE (TOP VIEW)



NC - No internal connection

description/ordering information

The MAX3222 consists of two line drivers, two line receivers, and a dual charge-pump circuit with ± 15 -kV ESD protection pin to pin (serial-port connection pins, including GND). The device meets the requirements of TIA/EIA-232-F and provides the electrical interface between an asynchronous communication controller and the serial-port connector. The charge pump and four small external capacitors allow operation from a single 3-V to 5.5-V supply. The device operates at data signaling rates up to 250 kbit/s and a maximum of 30-V/ μ s driver output slew rate.

ORDERING INFORMATION

TA	PACKAGE [†]		ORDERABLE PART NUMBER	TOP-SIDE MARKING
	COIC (DW)	Tube of 25	MAX3222CDW	MAYAAAA
	SOIC (DW)	Reel of 2000	MAX3222CDWR	MAX3222C
000 1- 7000	0000 (DD)	Tube of 70	MAX3222CDB	14400000
−0°C to 70°C	SSOP (DB)	Reel of 2000	MAX3222CDBR	MA3222C
	TSSOP (PW)	Tube of 70	MAX3222CPW	14400000
		Reel of 2000	MAX3222CPWR	MA3222C
	SOIC (DW)	Tube of 25	MAX3222IDW	MANAGOOD
		Reel of 2000	MAX3222IDWR	MAX3222I
-40°C to 85°C	0000 (DD)	Tube of 70	MAX3222IDB	MPaggal
	SSOP (DB)	Reel of 2000	MAX3222IDBR	MB3222I
	TCCOD (DWA)	Tube of 70	MAX3222IPW	MB3222I
	TSSOP (PW)	Reel of 2000	MAX3222IPWR	IVID3ZZZI

[†] Package drawings, standard packing quantities, thermal data, symbolization, and PCB design guidelines are available at www.ti.com/sc/package.



Please be aware that an important notice concerning availability, standard warranty, and use in critical applications of Texas Instruments semiconductor products and disclaimers thereto appears at the end of this data sheet.



3-V TO 5.5-V MULTICHANNEL RS-232 LINE DRIVER/RECEIVER WITH \pm 15-kV ESD PROTECTION

SLLS408G - JANUARY 2000 - REVISED MARCH 2004

description/ordering information (continued)

The MAX3222 can be placed in the power-down mode by setting $\overline{PWRDOWN}$ low, which draws only 1 μA from the power supply. When the device is powered down, the receivers remain active while the drivers are placed in the high-impedance state. Also, during power down, the onboard charge pump is disabled; V+ is lowered to V_{CC} , and V- is raised toward GND. Receiver outputs also can be placed in the high-impedance state by setting \overline{EN} high.

Function Tables

EACH DRIVER

IN	PUTS	OUTPUT
DIN	PWRDOWN	DOUT
Х	L	Z
L	Н	Н
Н	Н	L


H = high level, L = low level, X = irrelevant, Z = high impedance

EACH RECEIVER

INPL	OUTPUT	
RIN	EN	ROUT
L	L	Н
Н	L	L
X	Н	Z
Open	L	Н

H = high level, L = low level, X = irrelevant, Z = high impedance (off), Open = input disconnected or connected driver off

logic diagram (positive logic)





3-V TO 5.5-V MULTICHANNEL RS-232 LINE DRIVER/RECEIVER WITH +15-kV ESD PROTECTION

SLLS408G - JANUARY 2000 - REVISED MARCH 2004

absolute maximum ratings over operating free-air temperature range (unless otherwise noted)

Supply voltage range, V _{CC} (see Note 1)	-0.3 V to 6 V
Positive output supply voltage range, V+ (see Note 1)	
Negative output supply voltage range, V- (see Note 1)	
Supply voltage difference, V+ - V- (see Note 1)	
Input voltage range, V _I : Drivers, EN, PWRDOWN	
Receivers	
Output voltage range, V _O : Drivers	13.2 V to 13.2 V
Receivers	0.3 V to V _{CC} + 0.3 V
Package thermal impedance, θ _{JA} (see Notes 2 and 3):	: DB package
	DW package 58°C/W
	PW package 83°C/W
Operating virtual junction temperature, T _J	150°C
Storage temperature range, T _{stg}	–65°C to 150°C

[†] Stresses beyond those listed under "absolute maximum ratings" may cause permanent damage to the device. These are stress ratings only, and functional operation of the device at these or any other conditions beyond those indicated under "recommended operating conditions" is not implied. Exposure to absolute-maximum-rated conditions for extended periods may affect device reliability.

NOTES: 1. All voltages are with respect to network GND.

- 2. Maximum power dissipation is a function of T_J(max), θ_{JA}, and T_A. The maximum allowable power dissipation at any allowable ambient temperature is P_D = (T_J(max) T_A)/θ_{JA}. Operating at the absolute maximum T_J of 150°C can affect reliability.
- 3. The package thermal impedance is calculated in accordance with JESD 51-7.

recommended operating conditions (see Note 4 and Figure 5)

				MIN	NOM	MAX	UNIT
	Outside contract	V _{CC} = 3.3 V		3	3.3	3.6	.,
	Supply voltage	V _{CC} = 5 V		4.5	5	5.5	V
	Driver and control black level in a strockers	DIN EN DWDDOWN	V _{CC} = 3.3 V	2			.,
VIH	Driver and control high-level input voltage	DIN, EN, PWRDOWN	V _{CC} = 5 V	2.4			٧
VIL	Driver and control low-level input voltage	DIN, EN, PWRDOWN				0.8	V
٧ _I	Driver and control input voltage	DIN, EN, PWRDOWN		0		5.5	V
٧ _I	Receiver input voltage			-25		25	V
_		MAX3222C MAX3222I		0		70	00
TA	Operating free-air temperature			-40		85	°C

NOTE 4: Test conditions are C1–C4 = 0.1 μ F at V $_{CC}$ = 3.3 V \pm 0.3 V; C1 = 0.047 μ F, C2–C4 = 0.33 μ F at V $_{CC}$ = 5 V \pm 0.5 V.

electrical characteristics over recommended ranges of supply voltage and operating free-air temperature (unless otherwise noted) (see Note 4 and Figure 5)

_						
	PARAMETER	TEST CONDITIONS	MIN	TYP [‡]	MAX	UNIT
lį	Input leakage current (EN, PWRDOWN)			±0.01	±1	μΑ
loo	Supply current	No load, PWRDOWN at VCC		0.3	1	mA
ICC	Supply current (powered off)	No load, PWRDOWN at GND		1	10	μΑ

[‡] All typical values are at $V_{CC} = 3.3 \text{ V}$ or $V_{CC} = 5 \text{ V}$, and $T_A = 25^{\circ}\text{C}$.

NOTE 4: Test conditions are C1–C4 = 0.1 μ F at V_{CC} = 3.3 V ± 0.3 V; C1 = 0.047 μ F, C2–C4 = 0.33 μ F at V_{CC} = 5 V ± 0.5 V.



DRIVER SECTION

electrical characteristics over recommended ranges of supply voltage and operating free-air temperature (unless otherwise noted) (see Note 4 and Figure 5)

	PARAMETER	TEST CONDITIONS		MIN	TYP†	MAX	UNIT
Vон	High-level output voltage	DOUT at R _L = $3 \text{ k}\Omega$ to GND,	DIN = GND	5	5.4		V
VOL	Low-level output voltage	DOUT at R _L = $3 \text{ k}\Omega$ to GND,	DIN = VCC	-5	-5.4		V
lιΗ	High-level input current	VI = VCC			±0.01	±1	μΑ
IJĽ	Low-level input current	V _I at GND			±0.01	±1	μΑ
IOS Short-circuit output current‡	$V_{CC} = 3.6 \text{ V},$	V _O = 0 V		105	±60	Λ	
	Snort-circuit output current+	V _{CC} = 5.5 V,	VO = 0 V	±35		mA	
r _O	Output resistance	V_{CC} , V+, and V- = 0 V,	V _O = ±2 V	300	10M		Ω
I _{off} Output leakage current	Output leakers surrest	PWRDOWN = GND, V _{CC} = 3 V to 3.6 V	$V_0 = \pm 12 \text{ V},$			±25	A
	Output leakage current	PWRDOWN = GND, V _{CC} = 4.5 V to 5.5 V	$V_0 = \pm 10 \text{ V},$			±25	μΑ

[†] All typical values are at $V_{CC} = 3.3 \text{ V}$ or $V_{CC} = 5 \text{ V}$, and $T_A = 25^{\circ}C$.

switching characteristics over recommended ranges of supply voltage and operating free-air temperature (unless otherwise noted) (see Note 4 and Figure 5)

	PARAMETER	TEST CONDITIONS		MIN	TYP [†]	MAX	UNIT
	Maximum data rate	C _L = 1000 pF, One DOUT switching,	$R_L = 3 kΩ$, See Figure 1	150	250		kbit/s
tsk(p)	Pulse skew§	C _L = 150 pF to 2500 pF, See Figure 2	$R_L = 3 \text{ k}\Omega \text{ to } 7 \text{ k}\Omega,$		300		ns
CD/tr\	Slew rate, transition region	$R_L = 3 k\Omega$ to $7 k\Omega$,	C _L = 150 pF to 1000 pF	6		30	\//uo
SR(tr)	(See Figure 1)	V _{CC} = 3.3 V	C _L = 150 pF to 2500 pF	4		30	V/μs

[†] All typical values are at $V_{CC} = 3.3 \text{ V}$ or $V_{CC} = 5 \text{ V}$, and $T_A = 25^{\circ}\text{C}$.

§ Pulse skew is defined as $|t_{PLH} - t_{PHL}|$ of each channel of the same device. NOTE 4: Test conditions are C1–C4 = 0.1 μ F at V_{CC} = 3.3 V ± 0.3 V; C1 = 0.047 μ F, C2–C4 = 0.33 μ F at V_{CC} = 5 V ± 0.5 V.



^{\$} Short-circuit durations should be controlled to prevent exceeding the device absolute power-dissipation ratings, and not more than one output should be shorted at a time.

NOTE 4: Test conditions are C1–C4 = 0.1 μ F at V_{CC} = 3.3 V ± 0.3 V; C1 = 0.047 μ F, C2–C4 = 0.33 μ F at V_{CC} = 5 V ± 0.5 V.

SLLS408G - JANUARY 2000 - REVISED MARCH 2004

RECEIVER SECTION

electrical characteristics over recommended ranges of supply voltage and operating free-air temperature (unless otherwise noted) (see Note 4 and Figure 5)

	PARAMETER	TEST CONDITIONS	MIN	TYP†	MAX	UNIT
VOH	High-level output voltage	I _{OH} = -1 mA	V _{CC} – 0.6 V	V _{CC} – 0.1 V		V
VOL	Low-level output voltage	I _{OL} = 1.6 mA			0.4	V
\/-	Positive-going input threshold voltage	V _{CC} = 3.3 V		1.5	2.4	V
V _{IT+}		V _{CC} = 5 V		1.8	2.4	V
\/	Negative-going input threshold voltage	V _{CC} = 3.3 V	0.6	1.2		V
V _{IT} –		V _{CC} = 5 V	0.8	1.5		V
V _{hys}	Input hysteresis (V _{IT+} - V _{IT-})			0.3		V
I _{off}	Output leakage current	EN = V _{CC}		±0.05	±10	μΑ
rį	Input resistance	$V_{I} = \pm 3 \text{ V to } \pm 25 \text{ V}$	3	5	7	kΩ

[†] All typical values are at $V_{CC} = 3.3 \text{ V}$ or $V_{CC} = 5 \text{ V}$, and $T_A = 25^{\circ}\text{C}$.

NOTE 4: Test conditions are C1–C4 = 0.1 μ F at V_{CC} = 3.3 V ± 0.3 V; C1 = 0.047 μ F, C2–C4 = 0.33 μ F at V_{CC} = 5 V ± 0.5 V.

switching characteristics over recommended ranges of supply voltage and operating free-air temperature (unless otherwise noted) (see Note 4)

	PARAMETER	TEST CONDITIONS	MIN TYPT MAX	UNIT
tPLH	Propagation delay time, low- to high-level output	$C_{L} = 150$ pF, See Figure 3	300	ns
tPHL	Propagation delay time, high- to low-level output	C _L = 150 pF, See Figure 3	300	ns
t _{en}	Output enable time	C_L = 150 pF, R_L = 3 kΩ, See Figure 4	200	ns
t _{dis}	Output disable time	C_L = 150 pF, R_L = 3 kΩ, See Figure 4	200	ns
t _{sk(p)}	Pulse skew [‡]	See Figure 3	300	ns


[†] All typical values are at $V_{CC} = 3.3 \text{ V}$ or $V_{CC} = 5 \text{ V}$, and $T_A = 25^{\circ}\text{C}$.

NOTE 4: Test conditions are C1–C4 = 0.1 μ F at V_{CC} = 3.3 $V \pm 0.3 V$; C1 = 0.047 μ F, C2–C4 = 0.33 μ F at V_{CC} = 5 $V \pm 0.5 V$.



[‡] Pulse skew is defined as |tpLH - tpHL| of each channel of the same device.


PARAMETER MEASUREMENT INFORMATION



NOTES: A. C_L includes probe and jig capacitance.

B. The pulse generator has the following characteristics: PRR = 250 kbit/s, $Z_O = 50~\Omega$, 50% duty cycle, $t_\Gamma \le 10$ ns. $t_f \le 10$ ns.


Figure 1. Driver Slew Rate



NOTES: A. C_L includes probe and jig capacitance.

B. The pulse generator has the following characteristics: PRR = 250 kbit/s, $Z_O = 50 \Omega$, 50% duty cycle, $t_\Gamma \le 10$ ns. $t_f \le 10$ ns.

Figure 2. Driver Pulse Skew



NOTES: A. C_L includes probe and jig capacitance.


B. The pulse generator has the following characteristics: $Z_O = 50 \Omega$, 50% duty cycle, $t_r \le 10$ ns, $t_f \le 10$ ns.

Figure 3. Receiver Propagation Delay Times



SLLS408G - JANUARY 2000 - REVISED MARCH 2004

PARAMETER MEASUREMENT INFORMATION




NOTES: A. C_L includes probe and jig capacitance.

B. The pulse generator has the following characteristics: $Z_0 = 50 \Omega$, 50% duty cycle, $t_r \le 10$ ns, $t_f \le 10$ ns.

Figure 4. Receiver Enable and Disable Times

APPLICATION INFORMATION



†C3 can be connected to VCC or GND.

NOTES: A. Resistor values shown are nominal.

- B. NC No internal connection
- C. Nonpolarized ceramic capacitors are acceptable. If polarized tantalum or electrolytic capacitors are used, they should be connected as shown.

V_{CC} vs CAPACITOR VALUES

VCC	C1	C2, C3, and C4
3.3 V \pm 0.3 V	0.1 μ F	0.1 μ F
5 V ± 0.5 V	0.047 μ F	0.33 μ F
3 V to 5.5 V	0.1 μF	0.47 μ F

Figure 5. Typical Operating Circuit and Capacitor Values



DW (R-PDSO-G20)

PLASTIC SMALL-OUTLINE PACKAGE



NOTES:

- A. All linear dimensions are in inches (millimeters).
- B. This drawing is subject to change without notice.
- C. Body dimensions do not include mold flash or protrusion not to exceed 0.006 (0,15).
- D. Falls within JEDEC MS-013 variation AC.



DB (R-PDSO-G**)

PLASTIC SMALL-OUTLINE

28 PINS SHOWN



NOTES: A. All linear dimensions are in millimeters.

B. This drawing is subject to change without notice.

C. Body dimensions do not include mold flash or protrusion not to exceed 0,15.

D. Falls within JEDEC MO-150

PW (R-PDSO-G**)

14 PINS SHOWN

PLASTIC SMALL-OUTLINE PACKAGE



NOTES: A. All linear dimensions are in millimeters.

B. This drawing is subject to change without notice.

C. Body dimensions do not include mold flash or protrusion not to exceed 0,15.

D. Falls within JEDEC MO-153

IMPORTANT NOTICE

Texas Instruments Incorporated and its subsidiaries (TI) reserve the right to make corrections, modifications, enhancements, improvements, and other changes to its products and services at any time and to discontinue any product or service without notice. Customers should obtain the latest relevant information before placing orders and should verify that such information is current and complete. All products are sold subject to TI's terms and conditions of sale supplied at the time of order acknowledgment.

TI warrants performance of its hardware products to the specifications applicable at the time of sale in accordance with TI's standard warranty. Testing and other quality control techniques are used to the extent TI deems necessary to support this warranty. Except where mandated by government requirements, testing of all parameters of each product is not necessarily performed.

TI assumes no liability for applications assistance or customer product design. Customers are responsible for their products and applications using TI components. To minimize the risks associated with customer products and applications, customers should provide adequate design and operating safeguards.

TI does not warrant or represent that any license, either express or implied, is granted under any TI patent right, copyright, mask work right, or other TI intellectual property right relating to any combination, machine, or process in which TI products or services are used. Information published by TI regarding third-party products or services does not constitute a license from TI to use such products or services or a warranty or endorsement thereof. Use of such information may require a license from a third party under the patents or other intellectual property of the third party, or a license from TI under the patents or other intellectual property of TI.

Reproduction of information in TI data books or data sheets is permissible only if reproduction is without alteration and is accompanied by all associated warranties, conditions, limitations, and notices. Reproduction of this information with alteration is an unfair and deceptive business practice. TI is not responsible or liable for such altered documentation.

Resale of TI products or services with statements different from or beyond the parameters stated by TI for that product or service voids all express and any implied warranties for the associated TI product or service and is an unfair and deceptive business practice. TI is not responsible or liable for any such statements.

Following are URLs where you can obtain information on other Texas Instruments products and application solutions:

Products		Applications	
Amplifiers	amplifier.ti.com	Audio	www.ti.com/audio
Data Converters	dataconverter.ti.com	Automotive	www.ti.com/automotive
DSP	dsp.ti.com	Broadband	www.ti.com/broadband
Interface	interface.ti.com	Digital Control	www.ti.com/digitalcontrol
Logic	logic.ti.com	Military	www.ti.com/military
Power Mgmt	power.ti.com	Optical Networking	www.ti.com/opticalnetwork
Microcontrollers	microcontroller.ti.com	Security	www.ti.com/security
		Telephony	www.ti.com/telephony
		Video & Imaging	www.ti.com/video
		Wireless	www.ti.com/wireless
Data Converters DSP Interface Logic Power Mgmt	dataconverter.ti.com dsp.ti.com interface.ti.com logic.ti.com power.ti.com	Broadband Digital Control Military Optical Networking Security Telephony Video & Imaging	www.ti.com/broadband www.ti.com/digitalcontrol www.ti.com/military www.ti.com/opticalnetwor www.ti.com/security www.ti.com/telephony www.ti.com/video

Mailing Address: Texas Instruments

Post Office Box 655303 Dallas, Texas 75265

Copyright © 2004, Texas Instruments Incorporated