


PT6320 Series

3 AMP ADJUSTABLE LOW VOLTAGE INPUT INTEGRATED SWITCHING REGULATORS

SLTS065
(Revised 6/4/98)




- Low Voltage Input (7V)
- 90% Efficiency
- Adjustable Output Voltage
- Internal Short Circuit Protection
- Over-Temperature Protection
- On/Off Control (Ground Off)

The PT6320 series is a low voltage input (typically 7V) version of Power Trends' high-performance 3A, 12 pin SIP Integrated Switching

Regulators (ISRs). These ISRs are designed with premium low threshold FETs for those applications requiring very low input/output voltage differentials such as battery powered equipment. This high-performance ISR family offers a unique combination of features combining 90% typical efficiency with open-collector on/off control and adjustable output voltage. Quiescent current in the shutdown mode is less than 100µA.

Standard Application



Pin-Out Information


| Pin | Function |
|-----|----------------------|
| 1 | Inhibit (30V max) |
| 2 | V _{in} |
| 3 | V _{in} |
| 4 | V _{in} |
| 5 | GND |
| 6 | GND |
| 7 | GND |
| 8 | GND |
| 9 | V _{out} |
| 10 | V _{out} |
| 11 | V _{out} |
| 12 | V _{out} Adj |

Ordering Information

PT6322□ = +5 Volts
PT6323□ = +3.3 Volts

PT Series Suffix (PT1234X)

| Case/Pin Configuration | |
|--------------------------|---|
| Vertical Through-Hole | N |
| Horizontal Through-Hole | A |
| Horizontal Surface Mount | C |



Specifications

| Characteristics (T _a =25°C unless noted) | Symbols | Conditions | PT6320 SERIES | | | |
|--|------------------------------------|--|------------------------|------------|--------|-------------------------|
| | | | Min | Typ | Max | Units |
| Output Current | I _o | Over V _{in} range | 0.1* | — | 3.0 | A |
| Short Circuit Current | I _{sc} | V _{in} = V _o + 5V | — | 5.0 | — | Apk |
| Input Voltage Range (Note: inhibit function cannot be used above 30V) | V _{in} | 0.1 ≤ I _o ≤ 3.0 A V _o = 3.3V V _o = 5V | 7 | — | 26 | V |
| Output Voltage Tolerance | ΔV _o | Over V _{in} Range, I _o = 3.0 A T _a = 0°C to +60°C | — | ±1.0 | ±2.0 | %V _o |
| Line Regulation | Reg _{line} | Over V _{in} range | — | ±0.25 | ±0.5 | %V _o |
| Load Regulation | Reg _{load} | 0.1 ≤ I _o ≤ 3.0 A | — | ±0.25 | ±0.5 | %V _o |
| V _o Ripple/Noise | V _n | V _{in} = V _{in} min, I _o = 3.0A | — | ±2 | — | %V _o |
| Transient Response with C _o = 100µF | t _{tr} V _{os} | 50% load change V _o over/undershoot | — | 100 5.0 | 200 | µSec %V _o |
| Efficiency | η | V _{in} = 9V, I _o = 0.5 A, V _o = 3.3V V _{in} = 9V, I _o = 0.5 A, V _o = 5V | — | 84 89 | — | % |
| Switching Frequency | f _o | Over V _{in} and I _o ranges | 400 | 500 | 600 | kHz |
| Shutdown Current | I _{sc} | V _{in} = 15V | — | 100 | — | µA |
| Quiescent Current | I _{nl} | I _o = 0A, V _{in} = 10V | — | 10 | — | mA |
| Output Voltage Adjustment Range | V _o | Below V _o Above V _o | See Application Notes. | | | |
| Absolute Maximum Operating Temperature Range | T _a | | -40 | — | +85 | °C |
| Recommended Operating Temperature Range | T _a | Free Air Convection, (40-60LFM) At V _{in} = 24V, I _o = 2.5A | -40 | — | +80*** | °C |
| Thermal Resistance | θ _{ja} | Free Air Convection (40-60LFM) | — | 30 | — | °C/W |
| Storage Temperature | T _s | | -40 | — | +125 | °C |
| Mechanical Shock | | Per Mil-STD-883D, Method 2002.3, 1 msec, Half Sine, mounted to a fixture | — | 500 | — | G's |
| Mechanical Vibration | | Per Mil-STD-883D, Method 2007.2, 20-2000 Hz, Soldered in a PC board | — | 10 | — | G's |
| Weight | — | | — | 6.5 | — | grams |


* ISR will operate to no load with reduced specifications.
** Input voltage cannot exceed 30V when the inhibit function is used. *** See Thermal Derating chart.
Note: The PT6320 Series requires a 100µF electrolytic or tantalum output capacitor for proper operation in all applications.

PT6320 Series


CHARACTERISTIC DATA

PT6323, 3.3 VDC (See Note 1)


Efficiency vs Output Current




Ripple vs Output Current



Thermal Derating (Ta) (See Note 2)




Power Dissipation vs Output Current




PT6322, 5.0 VDC (See Note 1)


Efficiency vs Output Current




Ripple vs Output Current



Thermal Derating (Ta) (See Note 2)



Power Dissipation vs Output Current



Note 1: All data listed in the above graphs except for derating data has been developed from actual products tested at 25°C. This data is considered typical data for the ISR
 Note 2: Thermal derating graphs are developed in free air convection cooling of 40-60 LFM. (See Thermal Application note.)

Application Notes **PT6100/6120/6210/6220/6300/6320 Series**

[More Application Notes](#)

Adjusting the Output Voltage of Power Trends' Wide Input Range Bus ISRs

The output voltage of the Power Trends' Wide Input Range Series ISRs may be adjusted higher or lower than the factory trimmed pre-set voltage with the addition of a single external resistor. Table 1 accordingly gives the allowable adjustment range for each model for either series as V_a (min) and V_a (max).

Adjust Up: An increase in the output voltage is obtained by adding a resistor R2, between pin 12 (V_o adjust) and pins 5-8 (GND).

Adjust Down: Add a resistor (R1), between pin 12 (V_o adjust) and pins 9-11 (V_{out}).

Refer to Figure 1 and Table 2 for both the placement and value of the required resistor; either (R1) or R2 as appropriate.

Notes:

1. Use only a single 1% resistor in either the (R1) or R2 location. Place the resistor as close to the ISR as possible.
2. Never connect capacitors from V_o adjust to either GND or V_{out} . Any capacitance added to the V_o adjust pin will affect the stability of the ISR.
4. Adjustments to the output voltage may place additional limits on the maximum and minimum input voltage for the part. The revised maximum and minimum input voltage limits must comply with the following requirements. Note that the minimum input voltage limits are also model dependant.

$$V_{in}(\max) = (8 \times V_a)V \text{ or } *30/38V, \text{ whichever is less.}$$

**Limit is 30V when inhibit function is active.*

PT6x0x/PT6x1x series:


$$V_{in}(\min) = (V_a + 4)V \text{ or } 9V, \text{ whichever is greater.}$$

PT6x2x series:

$$V_o < 10V; \quad V_{in}(\min) = (V_a + 2.0)V \text{ or } 7.0V, \text{ whichever is greater.}$$

$$V_o \geq 10V; \quad V_{in}(\min) = (V_a + 2.5)V$$

Figure 1



The values of (R1) [adjust down], and R2 [adjust up], can also be calculated using the following formulae.

$$(R1) = \frac{R_o (V_a - 1.25)}{V_o - V_a} \quad k\Omega$$

$$R2 = \frac{1.25 R_o}{V_a - V_o} \quad k\Omega$$

Where: V_o = Original output voltage
 V_a = Adjusted output voltage
 R_o = The resistance value from Table 1

Table 1

| ISR ADJUSTMENT RANGE AND FORMULA PARAMETERS | | | | |
|---|-------------|--------|--------|--------|
| | PT6102 | PT6101 | | PT6103 |
| 1Adc Rated | PT6122 | PT6121 | | |
| | PT6213 | | PT6212 | PT6214 |
| 2Adc Rated | PT6223 | | PT6222 | |
| | PT6303 | | PT6302 | PT6304 |
| 3Adc Rated | PT6323 | | PT6322 | |
| | V_o (nom) | 3.3 | 5.0 | 5.0 |
| V_a (min) | 1.89 | 1.88 | 2.18 | 2.43 |
| V_a (max) | 6.07 | 11.25 | 8.5 | 22.12 |
| R_o (k Ω) | 66.5 | 150.0 | 90.9 | 243.0 |

Table 2

ISR ADJUSTMENT RESISTOR VALUES

| 1Adc Rated | PT6102 | PT6101 | | PT6103 |
|---------------|--------------------|--------------------|--------------------|-------------------|
| 2Adc Rated | PT6213 | PT6211 | PT6212 | PT6214 |
| 3Adc Rated | PT6303 | | PT6302 | PT6304 |
| V_o (nom) | 3.3 | 5.0 | 5.0 | 12.0 |
| V_a (req.d) | | | | |
| 1.9 | (30.9)k Ω | (31.5)k Ω | | |
| 2.0 | (38.4)k Ω | (37.5)k Ω | | |
| 2.1 | (47.1)k Ω | (44.0)k Ω | | |
| 2.2 | (57.4)k Ω | (50.9)k Ω | (30.8)k Ω | |
| 2.3 | (69.8)k Ω | (58.3)k Ω | (35.4)k Ω | |
| 2.4 | (85.0)k Ω | (66.3)k Ω | (40.2)k Ω | |
| 2.5 | (104.0)k Ω | (75.0)k Ω | (45.5)k Ω | (32.0)k Ω |
| 2.6 | (128.0)k Ω | (84.4)k Ω | (51.1)k Ω | (34.9)k Ω |
| 2.7 | (161.0)k Ω | (94.6)k Ω | (57.3)k Ω | (37.9)k Ω |
| 2.8 | (206.0)k Ω | (106.0)k Ω | (64.0)k Ω | (40.9)k Ω |
| 2.9 | (274.0)k Ω | (118.0)k Ω | (71.4)k Ω | (44.1)k Ω |
| 3.0 | (388.0)k Ω | (131.0)k Ω | (79.5)k Ω | (47.3)k Ω |
| 3.1 | (615.0)k Ω | (146.0)k Ω | (88.5)k Ω | (50.5)k Ω |
| 3.2 | (1300.0)k Ω | (163.0)k Ω | (98.5)k Ω | (53.8)k Ω |
| 3.3 | | (181.0)k Ω | (110.0)k Ω | (57.3)k Ω |
| 3.4 | 831.0k Ω | (202.0)k Ω | (122.0)k Ω | (60.8)k Ω |
| 3.5 | 416.0k Ω | (225.0)k Ω | (136.0)k Ω | (64.3)k Ω |
| 3.6 | 227.0k Ω | (252.0)k Ω | (153.0)k Ω | (68.0)k Ω |
| 3.7 | 208.0k Ω | (283.0)k Ω | (171.0)k Ω | (71.7)k Ω |
| 3.8 | 166.0k Ω | (319.0)k Ω | (193.0)k Ω | (75.6)k Ω |
| 3.9 | 139.0k Ω | (361.0)k Ω | (219.0)k Ω | (79.5)k Ω |
| 4.0 | 119.0k Ω | (413.0)k Ω | (250.0)k Ω | (83.5)k Ω |
| 4.1 | 104.0k Ω | (475.0)k Ω | (288.0)k Ω | (87.7)k Ω |
| 4.2 | 92.4k Ω | (533.0)k Ω | (335.0)k Ω | (91.9)k Ω |
| 4.3 | 83.1k Ω | (654.0)k Ω | (396.0)k Ω | (96.3)k Ω |
| 4.4 | 75.6k Ω | (788.0)k Ω | (477.0)k Ω | (101.0)k Ω |
| 4.5 | 69.3k Ω | (975.0)k Ω | (591.0)k Ω | (105.0)k Ω |
| 4.6 | 63.9k Ω | (1260.0)k Ω | (761.0)k Ω | (110.0)k Ω |
| 4.7 | 59.4k Ω | (1730.0)k Ω | (1050.0)k Ω | (115.0)k Ω |
| 4.8 | 55.4k Ω | | (1610.0)k Ω | (120.0)k Ω |
| 4.9 | 52.0k Ω | | | (125.0)k Ω |
| 5.0 | 48.9k Ω | | | (130.0)k Ω |
| 5.1 | 46.2k Ω | 1880.0k Ω | 1140.0k Ω | (136.0)k Ω |
| 5.2 | 43.8k Ω | 937.0k Ω | 568.0k Ω | (141.0)k Ω |
| 5.3 | 41.6k Ω | 625.0k Ω | 379.0k Ω | (147.0)k Ω |
| 5.4 | 39.6k Ω | 469.0k Ω | 284.0k Ω | (153.0)k Ω |
| 5.5 | 37.8k Ω | 375.0k Ω | 227.0k Ω | (159.0)k Ω |
| 5.6 | 36.1k Ω | 313.0k Ω | 189.0k Ω | (165.0)k Ω |
| 5.7 | 34.6k Ω | 268.0k Ω | 162.0k Ω | (172.0)k Ω |
| 5.8 | 33.3k Ω | 234.0k Ω | 142.0k Ω | (178.0)k Ω |
| 5.9 | 32.0k Ω | 208.0k Ω | 126.0k Ω | (185.0)k Ω |
| 6.0 | 30.8k Ω | 188.0k Ω | 114.0k Ω | (192.0)k Ω |

R1 = (Red) R2 = Black

ISR ADJUSTMENT RESISTOR VALUES (Cont)

| 1Adc Rated | PT6101 | | PT6103 |
|---------------|-----------------|----------------|--------------------|
| 2Adc Rated | PT6211 | PT6212 | PT6214 |
| 3Adc Rated | | PT6302 | PT6304 |
| V_o (nom) | 5.0 | 5.0 | 12.0 |
| V_a (req.d) | | | |
| 6.2 | 156.0k Ω | 94.7k Ω | (207.0)k Ω |
| 6.4 | 134.0k Ω | 81.2k Ω | (223.0)k Ω |
| 6.6 | 117.0k Ω | 71.0k Ω | (241.0)k Ω |
| 6.8 | 104.0k Ω | 63.1k Ω | (259.0)k Ω |
| 7.0 | 93.8k Ω | 56.8k Ω | (279.0)k Ω |
| 7.2 | 85.2k Ω | 51.6k Ω | (301.0)k Ω |
| 7.4 | 78.1k Ω | 47.3k Ω | (325.0)k Ω |
| 7.6 | 72.1k Ω | 43.7k Ω | (351.0)k Ω |
| 7.8 | 67.0k Ω | 40.6k Ω | (379.0)k Ω |
| 8.0 | 62.5k Ω | 37.9k Ω | (410.0)k Ω |
| 8.2 | 58.6k Ω | 35.5k Ω | (444.0)k Ω |
| 8.4 | 55.1k Ω | 33.4k Ω | (483.0)k Ω |
| 8.6 | 52.1k Ω | | (525.0)k Ω |
| 8.8 | 49.3k Ω | | (573.0)k Ω |
| 9.0 | 46.9k Ω | | (628.0)k Ω |
| 9.5 | 41.7k Ω | | (802.0)k Ω |
| 10.0 | 37.5k Ω | | (1060.0)k Ω |
| 10.5 | 34.1k Ω | | (1500.0)k Ω |
| 11.0 | 31.3k Ω | | |
| 11.5 | | | |
| 12.0 | | | |
| 12.5 | | | 608.0k Ω |
| 13.0 | | | 304.0k Ω |
| 13.5 | | | 203.0k Ω |
| 14.0 | | | 152.0k Ω |
| 14.5 | | | 122.0k Ω |
| 15.0 | | | 101.0k Ω |
| 15.5 | | | 86.8k Ω |
| 16.0 | | | 75.9k Ω |
| 16.5 | | | 67.5k Ω |
| 17.0 | | | 60.8k Ω |
| 17.5 | | | 55.2k Ω |
| 18.0 | | | 50.6k Ω |
| 18.5 | | | 46.7k Ω |
| 19.0 | | | 43.4k Ω |
| 19.5 | | | 40.5k Ω |
| 20.0 | | | 38.0k Ω |
| 20.5 | | | 35.7k Ω |
| 21.5 | | | 33.8k Ω |
| 21.5 | | | 32.0k Ω |
| 22.0 | | | 30.4k Ω |

[More Application Notes](#)

Using the Inhibit Function on Power Trends' Wide Input Range Bus ISRs

For applications requiring output voltage On/Off control, the 12pin ISR products incorporate an inhibit function. The function has uses in areas such as battery conservation, power-up sequencing, or any other application where the regulated output from the module is required to be switched off. The On/Off function is provided by the *Inhibit* control, pin 1.

The ISR functions normally with pin 1 open-circuit, providing a regulated output whenever a valid source voltage is applied to V_{in} , (pins 2, 3, & 4). When a low-level² ground signal is applied to pin 1 the regulator output is disabled, and the input current to the ISR is reduced to about 100 μ A³.

Figure 1 shows an application schematic, which details the typical use of the inhibit function. Note the discrete transistor, Q1. The inhibit control has its own internal pull-up with a maximum open-circuit voltage of 8.3VDC. Only devices with a true open-collector or open-drain output can be used to control this pin. A discrete bipolar transistor or MOSFET is recommended.


Notes:

1. The inhibit control logic is similar for all Power Trends' modules, but the flexibility and threshold tolerances will be different. For specific information on the inhibit function of other ISR models, consult the applicable application note.
2. Use only a true open-collector device (preferably a discrete transistor) for the inhibit input. **Do Not** use a pull-up resistor, or drive the input directly from the output of a TTL or other logic gate. To disable the output voltage, the control pin should be pulled low to less than +1.5VDC.
3. The following equation may be used to determine the approximate current drawn from the input supply at V_{in} , and through Q1 when the inhibit is active.

$$I_{stby} = V_{in} \div 155k\Omega \pm 20\%$$


4. When the inhibit control pin is active, i.e. pulled low, the maximum input voltage is limited to +30Vdc.
5. Do not control the inhibit input with an external DC voltage. This will lead to erratic operation of the ISR and may over-stress the regulator.
6. Avoid capacitance greater than 500pF at the Inhibit control pin. Excessive capacitance at this pin will cause the ISR to produce a pulse on the output voltage bus at turn-on.
7. Keep the On/Off transition to less than 10 μ s. This prevents erratic operation of the ISR, which can cause a momentary high output voltage.

Figure 1



Turn-On Time: The output of the ISR is enabled automatically when external power is applied to the input. The *Inhibit* control pin is pulled high by its internal pull-up resistor. The ISR produces a fully regulated output voltage within 1-msec of either the release of the Inhibit control pin, or the application of power. The actual turn-on time will vary with the input voltage, output load, and the total amount of capacitance connected to the output. Using the circuit of Figure 1, Figure 2 shows the typical rise in output voltage for the PT6101 following the turn-off of Q1 at time $t=0$. The waveform was measured with a 9Vdc input voltage, and 5-Ohm resistive load.

Figure 2



PACKAGING INFORMATION

| Orderable Device | Status ⁽¹⁾ | Package Type | Package Drawing | Pins | Package Qty | Eco Plan ⁽²⁾ | Lead/Ball Finish | MSL Peak Temp ⁽³⁾ |
|------------------|-----------------------|--------------|-----------------|------|-------------|-------------------------|------------------|------------------------------|
| PT6322C | NRND | SIP MOD ULE | EBC | 12 | 12 | Pb-Free (RoHS) | Call TI | Level-1-215C-UNLIM |
| PT6322G | NRND | SIP MOD ULE | EBG | 12 | 12 | Pb-Free (RoHS) | Call TI | N / A for Pkg Type |
| PT6322N | NRND | SIP MOD ULE | EBD | 12 | 12 | Pb-Free (RoHS) | Call TI | N / A for Pkg Type |
| PT6322R | NRND | SIP MOD ULE | EBE | 12 | 12 | Pb-Free (RoHS) | Call TI | N / A for Pkg Type |
| PT6323C | NRND | SIP MOD ULE | EBC | 12 | 12 | Pb-Free (RoHS) | Call TI | Level-1-215C-UNLIM |
| PT6323G | NRND | SIP MOD ULE | EBG | 12 | 12 | Pb-Free (RoHS) | Call TI | N / A for Pkg Type |
| PT6323N | NRND | SIP MOD ULE | EBD | 12 | 12 | Pb-Free (RoHS) | Call TI | N / A for Pkg Type |
| PT6323R | NRND | SIP MOD ULE | EBE | 12 | 12 | Pb-Free (RoHS) | Call TI | N / A for Pkg Type |

⁽¹⁾ The marketing status values are defined as follows:

ACTIVE: Product device recommended for new designs.

LIFEBUY: TI has announced that the device will be discontinued, and a lifetime-buy period is in effect.

NRND: Not recommended for new designs. Device is in production to support existing customers, but TI does not recommend using this part in a new design.

PREVIEW: Device has been announced but is not in production. Samples may or may not be available.

OBSOLETE: TI has discontinued the production of the device.

⁽²⁾ Eco Plan - The planned eco-friendly classification: Pb-Free (RoHS), Pb-Free (RoHS Exempt), or Green (RoHS & no Sb/Br) - please check <http://www.ti.com/productcontent> for the latest availability information and additional product content details.

TBD: The Pb-Free/Green conversion plan has not been defined.

Pb-Free (RoHS): TI's terms "Lead-Free" or "Pb-Free" mean semiconductor products that are compatible with the current RoHS requirements for all 6 substances, including the requirement that lead not exceed 0.1% by weight in homogeneous materials. Where designed to be soldered at high temperatures, TI Pb-Free products are suitable for use in specified lead-free processes.

Pb-Free (RoHS Exempt): This component has a RoHS exemption for either 1) lead-based flip-chip solder bumps used between the die and package, or 2) lead-based die adhesive used between the die and leadframe. The component is otherwise considered Pb-Free (RoHS compatible) as defined above.

Green (RoHS & no Sb/Br): TI defines "Green" to mean Pb-Free (RoHS compatible), and free of Bromine (Br) and Antimony (Sb) based flame retardants (Br or Sb do not exceed 0.1% by weight in homogeneous material)

⁽³⁾ MSL, Peak Temp. -- The Moisture Sensitivity Level rating according to the JEDEC industry standard classifications, and peak solder temperature.

Important Information and Disclaimer:The information provided on this page represents TI's knowledge and belief as of the date that it is provided. TI bases its knowledge and belief on information provided by third parties, and makes no representation or warranty as to the accuracy of such information. Efforts are underway to better integrate information from third parties. TI has taken and continues to take reasonable steps to provide representative and accurate information but may not have conducted destructive testing or chemical analysis on incoming materials and chemicals. TI and TI suppliers consider certain information to be proprietary, and thus CAS numbers and other limited information may not be available for release.

In no event shall TI's liability arising out of such information exceed the total purchase price of the TI part(s) at issue in this document sold by TI to Customer on an annual basis.

IMPORTANT NOTICE

Texas Instruments Incorporated and its subsidiaries (TI) reserve the right to make corrections, modifications, enhancements, improvements, and other changes to its products and services at any time and to discontinue any product or service without notice. Customers should obtain the latest relevant information before placing orders and should verify that such information is current and complete. All products are sold subject to TI's terms and conditions of sale supplied at the time of order acknowledgment.

TI warrants performance of its hardware products to the specifications applicable at the time of sale in accordance with TI's standard warranty. Testing and other quality control techniques are used to the extent TI deems necessary to support this warranty. Except where mandated by government requirements, testing of all parameters of each product is not necessarily performed.

TI assumes no liability for applications assistance or customer product design. Customers are responsible for their products and applications using TI components. To minimize the risks associated with customer products and applications, customers should provide adequate design and operating safeguards.

TI does not warrant or represent that any license, either express or implied, is granted under any TI patent right, copyright, mask work right, or other TI intellectual property right relating to any combination, machine, or process in which TI products or services are used. Information published by TI regarding third-party products or services does not constitute a license from TI to use such products or services or a warranty or endorsement thereof. Use of such information may require a license from a third party under the patents or other intellectual property of the third party, or a license from TI under the patents or other intellectual property of TI.

Reproduction of information in TI data books or data sheets is permissible only if reproduction is without alteration and is accompanied by all associated warranties, conditions, limitations, and notices. Reproduction of this information with alteration is an unfair and deceptive business practice. TI is not responsible or liable for such altered documentation.

Resale of TI products or services with statements different from or beyond the parameters stated by TI for that product or service voids all express and any implied warranties for the associated TI product or service and is an unfair and deceptive business practice. TI is not responsible or liable for any such statements.

Following are URLs where you can obtain information on other Texas Instruments products and application solutions:

| Products | | Applications | |
|--------------------|--|---------------------|--|
| Amplifiers | amplifier.ti.com | Audio | www.ti.com/audio |
| Data Converters | dataconverter.ti.com | Automotive | www.ti.com/automotive |
| DSP | dsp.ti.com | Broadband | www.ti.com/broadband |
| Interface | interface.ti.com | Digital Control | www.ti.com/digitalcontrol |
| Logic | logic.ti.com | Military | www.ti.com/military |
| Power Mgmt | power.ti.com | Optical Networking | www.ti.com/opticalnetwork |
| Microcontrollers | microcontroller.ti.com | Security | www.ti.com/security |
| Low Power Wireless | www.ti.com/lpw | Telephony | www.ti.com/telephony |
| | | Video & Imaging | www.ti.com/video |
| | | Wireless | www.ti.com/wireless |

Mailing Address: Texas Instruments
Post Office Box 655303 Dallas, Texas 75265