- **Outstanding Combination of dc Precision and AC Performance:**
  - **Unity-Gain Bandwidth . . . 15 MHz Typ**
  - **V_n ..... 3.3 nV/$\sqrt{Hz}$ at f = 10 Hz Typ,**
    2.5 nV/$\sqrt{Hz}$ at f = 1 kHz Typ
  - **V_{IO} .... 25 μV Max**
  - **A_{VD} .... 45 V/μV Typ With R_L = 2 kΩ,**
    19 V/μV Typ With R_L = 600 Ω
- **Available in Standard-Pinout Small-Outline Package**
- **Output Features Saturation Recovery Circuitry**
- **Macromodels and Statistical information**

D, JG, OR P PACKAGE
(TOP VIEW)



FK PACKAGE
(TOP VIEW)



description

The TLE20x7 and TLE20x7A contain innovative circuit design expertise and high-quality process control techniques to produce a level of ac performance and dc precision previously unavailable in single operational amplifiers. Manufactured using Texas Instruments state-of-the-art Excalibur process, these devices allow upgrades to systems that use lower-precision devices.

In the area of dc precision, the TLE20x7 and TLE20x7A offer maximum offset voltages of 100 μV and 25 μV, respectively, common-mode rejection ratio of 131 dB (typ), supply voltage rejection ratio of 144 dB (typ), and dc gain of 45 V/μV (typ).

AVAILABLE OPTIONS

T_A	V_{IO}max AT 25°C	PACKAGED DEVICES				CHIP FORM‡ (Y)
		SMALL OUTLINE† (D)	CHIP CARRIER (FK)	CERAMIC DIP (JG)	PLASTIC DIP (P)	
0°C to 70°C	25 μV	TLE2027ACD TLE2037ACD	— —	— —	TLE2027ACP TLE2037ACP	TLE2027Y TLE2037Y
	100 μV	TLE2027CD TLE2037CD	— —	— —	TLE2027CP TLE2037CP	TLE2027Y TLE2037Y
–40°C to 105°C	25 μV	TLE2027AID TLE2037AID	— —	— —	TLE2027AIP TLE2037AIP	—
	100 μV	TLE2027ID TLE2037ID	— —	— —	TLE2027IP TLE2037IP	—
–55°C to 125°C	25 μV	TLE2027AMD TLE2037AMD	TLE2027AMFK TLE2037AMFK	TLE2027AMJG TLE2037AMJG	TLE2027AMP TLE2037AMP	—
	100 μV	TLE2027MD TLE2037MD	TLE2027MFK TLE2037MFK	TLE2027MJG TLE2037MJG	TLE2027MP TLE2037MP	—

† The D packages are available taped and reeled. Add R suffix to device type (e.g., TLE2027ACDR).
‡ Chip forms are tested at 25°C only.

Please be aware that an important notice concerning availability, standard warranty, and use in critical applications of Texas Instruments semiconductor products and disclaimers thereto appears at the end of this data sheet.

All trademarks are the property of their respective owners.

PRODUCTION DATA information is current as of publication date. Products conform to specifications per the terms of Texas Instruments standard warranty. Production processing does not necessarily include testing of all parameters.

Copyright © 2002–2006, Texas Instruments Incorporated

description (continued)

The ac performance of the TLE2027 and TLE2037 is highlighted by a typical unity-gain bandwidth specification of 15 MHz, 55° of phase margin, and noise voltage specifications of 3.3 nV/$\sqrt{\text{Hz}}$ and 2.5 nV/$\sqrt{\text{Hz}}$ at frequencies of 10 Hz and 1 kHz respectively. The TLE2037 and TLE2037A have been decompensated for faster slew rate (–7.5 V/μs, typical) and wider bandwidth (50 MHz). To ensure stability, the TLE2037 and TLE2037A should be operated with a closed-loop gain of 5 or greater.

Both the TLE20x7 and TLE20x7A are available in a wide variety of packages, including the industry-standard 8-pin small-outline version for high-density system applications. The C-suffix devices are characterized for operation from 0°C to 70°C. The I-suffix devices are characterized for operation from –40°C to 105°C. The M-suffix devices are characterized for operation over the full military temperature range of –55°C to 125°C.

symbol



TLE202xY chip information

This chip, when properly assembled, displays characteristics similar to the TLE202xC. Thermal compression or ultrasonic bonding may be used on the doped-aluminum bonding pads. The chip may be mounted with conductive epoxy or a gold-silicon preform.

BONDING PAD ASSIGNMENTS





CHIP THICKNESS: 15 MILS TYPICAL

BONDING PADS: 4 × 4 MILS MINIMUM

$T_J$max = 150°C

TOLERANCES ARE ±10%.

ALL DIMENSIONS ARE IN MILS.

PIN (4) IS INTERNALLY CONNECTED TO BACKSIDE OF CHIP.

equivalent schematic



ACTUAL DEVICE COMPONENT COUNT		
COMPONENT	TLE2027	TLE2037
Transistors	61	61
Resistors	26	26
epiFET	1	1
Capacitors	4	4

absolute maximum ratings over operating free-air temperature range (unless otherwise noted)†

Supply voltage, V_{CC+} (see Note 1) . . . . . 19 V
Supply voltage, V_{CC-} . . . . . – 19 V
Differential input voltage, V_{ID} (see Note 2) . . . . . ±1.2 V
Input voltage range, V_I (any input) . . . . . $V_{CC±}$
Input current, I_I (each Input) . . . . . ±1 mA
Output current, I_O . . . . . ± 50 mA
Total current into V_{CC+} . . . . . 50 mA
Total current out of V_{CC-} . . . . . 50 mA
Duration of short-circuit current at (or below) 25°C (see Note 3) . . . . . unlimited
Continuous total power dissipation . . . . . See Dissipation Rating Table
Operating free-air temperature range, T_A: C suffix . . . . . 0°C to 70°C
I suffix . . . . . – 40°C to 105°C
M suffix . . . . . – 55°C to 125°C
Storage temperature range, T_{stg} . . . . . – 65°C to 150°C
Case temperature for 60 seconds, T_C: FK package . . . . . 260°C
Lead temperature 1,6 mm (1/16 inch) from case for 10 seconds: D or P package . . . . . 260°C
Lead temperature 1,6 mm (1/16 inch) from case for 60 seconds: JG package . . . . . 300°C

† Stresses beyond those listed under “absolute maximum ratings” may cause permanent damage to the device. These are stress ratings only, and functional operation of the device at these or any other conditions beyond those indicated under “recommended operating conditions” is not implied. Exposure to absolute-maximum-rated conditions for extended periods may affect device reliability.

NOTES: 1. All voltage values, except differential voltages, are with respect to the midpoint between V_{CC+} and V_{CC-}.
2. Differential voltages are at IN+ with respect to IN–. Excessive current flows if a differential input voltage in excess of approximately ±1.2 V is applied between the inputs unless some limiting resistance is used.
3. The output may be shorted to either supply. Temperature and/or supply voltages must be limited to ensure that the maximum dissipation rating is not exceeded.

DISSIPATION RATING TABLE

PACKAGE	$T_A \le 25°C$ POWER RATING	DERATING FACTOR ABOVE $T_A = 25°C$	$T_A = 70°C$ POWER RATING	$T_A = 105°C$ POWER RATING	$T_A = 125°C$ POWER RATING
D	725 mW	5.8 mW/°C	464 mW	261 mW	145 mW
FK	1375 mW	11.0 mW/°C	880 mW	495 mW	275 mW
JG	1050 mW	8.4 mW/°C	672 mW	378 mW	210 mW
P	1000 mW	8.0 mW/°C	640 mW	360 mW	200 mW

recommended operating conditions

		C SUFFIX		I SUFFIX		M SUFFIX		UNIT
		MIN	MAX	MIN	MAX	MIN	MAX	
Supply voltage, $V_{CC±}$		±4	±19	±4	±19	±4	±19	V
Common-mode input voltage, V_{IC}	T_A = 25°C	–11	11	–11	11	–11	11	V
	T_A = Full range‡	–10.5	10.5	–10.4	10.4	–10.2	10.2	
Operating free-air temperature, T_A		0	70	–40	105	–55	125	°C

‡ Full range is 0°C to 70°C for C-suffix devices, – 40°C to 105°C for I-suffix devices, and – 55°C to 125°C for M-suffix devices.

TLE20x7C electrical characteristics at specified free-air temperature, $V_{CC\pm}$ = ±15 V (unless otherwise noted)

PARAMETER		TEST CONDITIONS	T_A†	TLE20x7C			TLE20x7AC			UNIT
				MIN	TYP	MAX	MIN	TYP	MAX	
V_{IO}	Input offset voltage	V_{IC} = 0, R_S = 50 Ω	25°C		20	100		10	25	μV
			Full range			145			70	
α_{VIO}	Temperature coefficient of input offset voltage		Full range		0.4	1		0.2	1	μV/°C
	Input offset voltage long-term drift (see Note 4)		25°C		0.006	1		0.006	1	μV/mo
I_{IO}	Input offset current		25°C		6	90		6	90	nA
			Full range			150			150	
I_{IB}	Input bias current		25°C		15	90		15	90	nA
			Full range			150			150	
V_{ICR}	Common-mode input voltage range	R_S = 50 Ω	25°C	−11 to 11	−13 to 13		−11 to 11	−13 to 13		V
			Full range	−10.5 to 10.5			−10.5 to 10.5			
V_{OM+}	Maximum positive peak output voltage swing	R_L = 600 Ω	25°C	10.5	12.9		10.5	12.9		V
			Full range	10			10			
		R_L = 2 kΩ	25°C	12	13.2		12	13.2		
			Full range	11			11			
V_{OM-}	Maximum negative peak output voltage swing	R_L = 600 Ω	25°C	−10.5	−13		−10.5	−13		V
			Full range	−10			−10			
		R_L = 2 kΩ	25°C	−12	−13.5		−12	−13.5		
			Full range	−11			−11			
A_{VD}	Large-signal differential voltage amplification	V_O = ±11 V, R_L = 2 kΩ	25°C	5	45		10	45		V/μV
		V_O = ±10 V, R_L = 2 kΩ	Full range	2			4			
		V_O = ±10 V, R_L = 1 kΩ	25°C	3.5	38		8	38		
			Full range	1			2.5			
		V_O = ±10 V, R_L = 600 Ω	25°C	2	19		5	19		
			Full range	0.5			2			
C_i	Input capacitance		25°C		8			8		pF
z_o	Open-loop output impedance	I_O = 0	25°C		50			50		Ω
CMRR	Common-mode rejection ratio	V_{IC} = V_{ICR}min, R_S = 50 Ω	25°C	100	131		117	131		dB
			Full range	98			114			
k_{SVR}	Supply-voltage rejection ratio ($\Delta V_{CC\pm}$ / ΔV_{IO})	$V_{CC\pm}$ = ±4 V to ±18 V, R_S = 50 Ω	25°C	94	144		110	144		dB
		$V_{CC\pm}$ = ±4 V to ±18 V, R_S = 50 Ω	Full range	92			106			
I_{CC}	Supply current	V_O = 0, No load	25°C		3.8	5.3		3.8	5.3	mA
			Full range			5.6			5.6	

† Full range is 0°C to 70°C.

NOTE 4: Typical values are based on the input offset voltage shift observed through 168 hours of operating life test at T_A = 150°C extrapolated to T_A = 25°C using the Arrhenius equation and assuming an activation energy of 0.96 eV.

TLE20x7C operating characteristics at specified free-air temperature, $V_{CC\pm}$ = ±15 V, T_A = 25°C (unless otherwise specified)

PARAMETER		TEST CONDITIONS		TLE20x7C			TLE20x7AC			UNIT
				MIN	TYP	MAX	MIN	TYP	MAX	
SR	Slew rate at unity gain	R_L = 2 kΩ, C_L = 100 pF, See Figure 1	TLE2027	1.7	2.8		1.7	2.8		V/μs
			TLE2037	6	7.5		6	7.5		
		R_L = 2 kΩ, C_L = 100 pF, T_A = 0°C to 70°C, See Figure 1	TLE2027	1.2			1.2			
			TLE2037	5			5			
V_n	Equivalent input noise voltage (see Figure 2)	R_S = 20 Ω,	f = 10 Hz		3.3	8		3.3	4.5	nV/√Hz
		R_S = 20 Ω,	f = 1 kHz		2.5	4.5		2.5	3.8	
$V_{N(PP)}$	Peak-to-peak equivalent input noise voltage	f = 0.1 Hz to 10 Hz			50	250		50	130	nV
I_n	Equivalent input noise current	f = 10 Hz			10	25		10	25	pA/√Hz
		f = 1 kHz			0.8	1.8		0.8	1.8	
THD	Total harmonic distortion	V_O = +10 V, A_{VD} = 1, See Note 5	TLE2027		<0.002%			<0.002%		
		V_O = +10 V, A_{VD} = 5, See Note 5	TLE2037		<0.002%			<0.002%		
B_1	Unity-gain bandwidth (see Figure 3)	R_L = 2 kΩ, C_L = 100 pF	TLE2027	9[6]	13		9[6]	13		MHz
GBW	Gain bandwidth product	R_L = 2 kΩ, C_L = 100 pF	TLE2037	35	50		35	50		
B_{OM}	Maximum output-swing bandwidth	R_L = 2 kΩ	TLE2027		30			30		kHz
			TLE2037		80			80		
ϕ_m	Phase margin at unity gain (see Figure 3)	R_L = 2 kΩ, C_L = 100 pF	TLE2027		55°			55°		
			TLE2037		50°			50°		

NOTE 5: Measured distortion of the source used in the analysis was 0.002%.
NOTE 6: This parameter is not production tested

TLE20x7I electrical characteristics at specified free-air temperature, $V_{CC\pm}$ = ±15 V (unless otherwise noted)

PARAMETER		TEST CONDITIONS	T_A†	TLE20x7I			TLE20x7AI			UNIT
				MIN	TYP	MAX	MIN	TYP	MAX	
V_{IO}	Input offset voltage	V_{IC} = 0, R_S = 50 Ω	25°C		20	100		10	25	μV
			Full range			180			105	
α_{VIO}	Temperature coefficient of input offset voltage		Full range		0.4	1		0.2	1	μV/°C
	Input offset voltage long-term drift (see Note 4)		25°C		0.006	1		0.006	1	μV/mo
I_{IO}	Input offset current		25°C		6	90		6	90	nA
			Full range			150			150	
I_{IB}	Input bias current		25°C		15	90		15	90	nA
			Full range			150			150	
V_{ICR}	Common-mode input voltage range	R_S = 50 Ω	25°C	−11 to 11	−13 to 13		−11 to 11	−13 to 13		V
			Full range	−10.4 to 10.4			−10.4 to 10.4			
V_{OM+}	Maximum positive peak output voltage swing	R_L = 600 Ω	25°C	10.5	12.9		10.5	12.9		V
			Full range	10			10			
		R_L = 2 kΩ	25°C	12	13.2		12	13.2		
			Full range	11			11			
V_{OM-}	Maximum negative peak output voltage swing	R_L = 600 Ω	25°C	−10.5	−13		−10.5	−13		V
			Full range	−10			−10			
		R_L = 2 kΩ	25°C	−12	−13.5		−12	−13.5		
			Full range	−11			−11			
A_{VD}	Large-signal differential voltage amplification	V_O = ±11 V, R_L = 2 kΩ	25°C	5	45		10	45		V/μV
		V_O = ±10 V, R_L = 2 kΩ	Full range	2			3.5			
		V_O = ±10 V, R_L = 1 kΩ	25°C	3.5	38		8	38		
			Full range	1			2.2			
		V_O = ±10 V, R_L = 600 Ω	25°C	2	19		5	19		
			Full range	0.5			1.1			
C_i	Input capacitance		25°C		8			8		pF
z_o	Open-loop output impedance	I_O = 0	25°C		50			50		Ω
CMRR	Common-mode rejection ratio	V_{IC} = V_{ICR}min, R_S = 50 Ω	25°C	100	131		117	131		dB
			Full range	96			113			
k_{SVR}	Supply-voltage rejection ratio ($\Delta V_{CC\pm}$ / ΔV_{IO})	$V_{CC\pm}$ = ±4 V to ±18 V, R_S = 50 Ω	25°C	94	144		110	144		dB
		$V_{CC\pm}$ = ±4 V to ±18 V, R_S = 50 Ω	Full range	90			105			
I_{CC}	Supply current	V_O = 0, No load	25°C		3.8	5.3		3.8	5.3	mA
			Full range			5.6			5.6	

† Full range is – 40°C to 105°C.

NOTE 4: Typical values are based on the input offset voltage shift observed through 168 hours of operating life test at T_A = 150°C extrapolated to T_A = 25°C using the Arrhenius equation and assuming an activation energy of 0.96 eV.

TLE20x7I operating characteristics at specified free-air temperature, $V_{CC\pm}$ = ±15 V, T_A = 25°C (unless otherwise specified)

PARAMETER		TEST CONDITIONS		TLE20x7I			TLE20x7AI			UNIT
				MIN	TYP	MAX	MIN	TYP	MAX	
SR	Slew rate at unity gain	R_L = 2 kΩ, C_L = 100 pF, See Figure 1	TLE2027	1.7	2.8		1.7	2.8		V/μs
			TLE2037	6	7.5		6	7.5		
		R_L = 2 kΩ, C_L = 100 pF, T_A = –40°C to 85°C, See Figure 1	TLE2027	1.1			1.1			
			TLE2037	4.7			4.7			
V_n	Equivalent input noise voltage (see Figure 2)	R_S = 20 Ω,	f = 10 Hz		3.3	8		3.3	4.5	nV/√Hz
		R_S = 20 Ω,	f = 1 kHz		2.5	4.5		2.5	3.8	
$V_{N(PP)}$	Peak-to-peak equivalent input noise voltage	f = 0.1 Hz to 10 Hz			50	250		50	130	nV
I_n	Equivalent input noise current	f = 10 Hz			10	25		10	25	pA/√Hz
		f = 1 kHz			0.8	1,8		0.8	1.8	
THD	Total harmonic distortion	V_O = +10 V, A_{VD} = 1, See Note 5	TLE2027		< 0.002%			< 0.002%		
		V_O = +10 V, A_{VD} = 5, See Note 5	TLE2037		< 0.002%			< 0.002%		
B_1	Unity-gain bandwidth (see Figure 3)	R_L = 2 kΩ, C_L = 100 pF	TLE2027	9(6)	13		9(6)	13		MHz
GBW	Gain bandwidth product	R_L = 2 kΩ, C_L = 100 pF	TLE2037	35	50		35	50		
B_{OM}	Maximum output-swing bandwidth	R_L = 2 kΩ	TLE2027		30			30		kHz
			TLE2037		80			80		
ϕ_m	Phase margin at unity gain (see Figure 3)	R_L = 2 kΩ, C_L = 100 pF	TLE2027		55°			55°		
			TLE2037		50°			50°		

NOTE 5: Measured distortion of the source used in the analysis was 0.002%.
NOTE 6: This parameter is not production tested.

TLE20x7M electrical characteristics at specified free-air temperature, $V_{CC\pm}$ = ±15 V (unless otherwise noted)

PARAMETER		TEST CONDITIONS	T_A†	TLE20x7M			TLE20x7AM			UNIT
				MIN	TYP	MAX	MIN	TYP	MAX	
V_{IO}	Input offset voltage	V_{IC} = 0, R_S = 50 Ω	25°C		20	100		10	25	μV
			Full range			200			105	
α_{VIO}	Temperature coefficient of input offset voltage		Full range		0.4	1*		0.2	1*	μV/°C
	Input offset voltage long-term drift (see Note 4)		25°C		0.006	1*		0.006	1*	μV/mo
I_{IO}	Input offset current		25°C		6	90		6	90	nA
			Full range			150			150	
I_{IB}	Input bias current		25°C		15	90		15	90	nA
			Full range			150			150	
V_{ICR}	Common-mode input voltage range	R_S = 50 Ω	25°C	−11 to 11	−13 to 13		−11 to 11	−13 to 13		V
			Full range	−10.3 to 10.3			−10.4 to 10.4			
V_{OM+}	Maximum positive peak output voltage swing	R_L = 600 Ω	25°C	10.5	12.9		10.5	12.9		V
			Full range	10			10			
		R_L = 2 kΩ	25°C	12	13.2		12	13.2		
			Full range	11			11			
V_{OM-}	Maximum negative peak output voltage swing	R_L = 600 Ω	25°C	−10.5	−13		−10.5	−13		V
			Full range	−10			−10			
		R_L = 2 kΩ	25°C	−12	−13.5		−12	−13.5		
			Full range	−11			−11			
A_{VD}	Large-signal differential voltage amplification	V_O = ±11 V, R_L = 2 kΩ	25°C	5	45		10	45		V/μV
		V_O = ±10 V, R_L = 2 kΩ	Full range	2.5			3.5			
		V_O = ±10 V, R_L = 1 kΩ	25°C	3.5	38		8	38		
			Full range	1.8			2.2			
		V_O = ±10 V, R_L = 600 Ω	25°C	2	19		5	19		
C_i	Input capacitance		25°C		8			8		pF
z_o	Open-loop output impedance	I_O = 0	25°C		50			50		Ω
CMRR	Common-mode rejection ratio	V_{IC} = V_{ICR}min, R_S = 50 Ω	25°C	100	131		117	131		dB
			Full range	96			113			
k_{SVR}	Supply-voltage rejection ratio ($\Delta V_{CC\pm}$ /ΔV_{IO})	$V_{CC\pm}$ = ±4 V to ±18 V, R_S = 50 Ω	25°C	94	144		110	144		dB
		$V_{CC\pm}$ = ±4 V to ±18 V, R_S = 50 Ω	Full range	90			105			
I_{CC}	Supply current	V_O = 0, No load	25°C		3.8	5.3		3.8	5.3	mA
			Full range			5.6			5.6	

* On products compliant to MIL-PRF-38535, this parameter is not production tested.

† Full range is – 55°C to 125°C.

NOTE 4: Typical values are based on the input offset voltage shift observed through 168 hours of operating life test at T_A = 150°C extrapolated to T_A = 25°C using the Arrhenius equation and assuming an activation energy of 0.96 eV.

TLE20x7M operating characteristics at specified free-air temperature, $V_{CC\pm}$ = ±15 V, T_A = 25°C (unless otherwise specified)

PARAMETER		TEST CONDITIONS		TLE20x7M			TLE20x7AM			UNIT
				MIN	TYP	MAX	MIN	TYP	MAX	
SR	Slew rate at unity gain	R_L = 2 kΩ, C_L = 100 pF, See Figure 1	TLE2027	1.7	2.8		1.7	2.8		V/μs
			TLE2037	6*	7.5		6*	7.5		
		R_L = 2 kΩ, C_L = 100 pF, T_A = –55°C to 125°C, See Figure 1	TLE2027	1			1			
			TLE2037	4.4*			4.4*			
V_n	Equivalent input noise voltage (see Figure 2)	R_S = 20 Ω,	f = 10 Hz		3.3	8*		3.3	8*	nV/√Hz
		R_S = 20 Ω,	f = 1 kHz		2.5	4*		2.5	4*	
$V_{N(PP)}$	Peak-to-peak equivalent input noise voltage	f = 0.1 Hz to 10 Hz			225	375*		225	375*	nV
I_n	Equivalent input noise current	f = 10 Hz			25			25		pA/√Hz
		f = 1 kHz			2.5			2.5		
THD	Total harmonic distortion	V_O = +10 V, A_{VD} = 1, See Note 5	TLE2027		< 0.002%			< 0.002%		
		V_O = +10 V, A_{VD} = 5, See Note 5	TLE2037		< 0.002%			< 0.002%		
B_1	Unity-gain bandwidth (see Figure 3)	R_L = 2 kΩ, C_L = 100 pF	TLE2027	7*	13		9*	13		MHz
			TLE2037	35	50		35	50		
B_{OM}	Maximum output-swing bandwidth	R_L = 2 kΩ	TLE2027		30			30		kHz
			TLE2037		80			80		
ϕ_m	Phase margin at unity gain (see Figure 3)	R_L = 2 kΩ, C_L = 100 pF	TLE2027		55°			55°		
			TLE2037		50°			50°		

* On products compliant to MIL-PRF-38535, this parameter is not production tested.

NOTE 5: Measured distortion of the source used in the analysis was 0.002%.

TLE20x7Y electrical characteristics, $V_{CC\pm}$ = ±15 V, T_A = 25°C (unless otherwise noted)

PARAMETER		TEST CONDITIONS	TLE20x7Y			UNIT
			MIN	TYP	MAX	
V_{IO}	Input offset voltage	V_{IC} = 0, R_S = 50 Ω		20		μV
	Input offset voltage long-term drift (see Note 4)	V_{IC} = 0, R_S = 50 Ω		0.006		μV/mo
I_{IO}	Input offset current	V_{IC} = 0, R_S = 50 Ω		6		nA
I_{IB}	Input bias current	V_{IC} = 0, R_S = 50 Ω		15		nA
V_{ICR}	Common-mode input voltage range	R_S = 50 Ω		−13 to 13		V
V_{OM+}	Maximum positive peak output voltage swing	R_L = 600 Ω		12.9		V
		R_L = 2 kΩ		13.2		
V_{OM-}	Maximum negative peak output voltage swing	R_L = 600 Ω		−13		V
		R_L = 2 kΩ		−13.5		
A_{VD}	Large-signal differential voltage amplification	V_O = ±11 V, R_L = 2 kΩ		45		V/μV
		V_O = ±10 V, R_L = 1 kΩ		38		
		V_O = ±10 V, R_L = 600 Ω		19		
C_i	Input capacitance			8		pF
z_o	Open-loop output impedance	I_O = 0		50		Ω
CMRR	Common-mode rejection ratio	V_{IC} = V_{ICR}min, R_S = 50 Ω		131		dB
k_{SVR}	Supply-voltage rejection ratio ($\Delta V_{CC\pm}$ / ΔV_{IO})	$V_{CC\pm}$ = ±4 V to ±18 V, R_S = 50 Ω		144		dB
I_{CC}	Supply current	V_O = 0, No load		3.8		mA

NOTE 4: Typical values are based on the input offset voltage shift observed through 168 hours of operating life test at T_A = 150°C extrapolated to T_A = 25°C using the Arrhenius equation and assuming an activation energy of 0.96 eV.

TLE20x7Y operating characteristics at specified free-air temperature, $V_{CC\pm}$ = ±15 V

PARAMETER		TEST CONDITIONS		TLE20x7Y MIN	TLE20x7Y TYP	TLE20x7Y MAX	UNIT
SR	Slew rate at unity gain	R_L = 2 kΩ, C_L = 100 pF, See Figure 1	TLE2027		2.8		V/μs
			TLE2037		7.5		
V_n	Equivalent input noise voltage (see Figure 2)	R_S = 20 Ω, f = 10 Hz			3.3		nV/√Hz
		R_S = 20 Ω, f = 1 kHz			2.5		
$V_{N(PP)}$	Peak-to-peak equivalent input noise voltage	f = 0.1 Hz to 10 Hz			50		nV
I_n	Equivalent input noise current	f = 10 Hz			10		pA/√Hz
		f = 1 kHz			0.8		
THD	Total harmonic distortion	V_O = +10 V, A_{VD} = 1, See Note 5	TLE2027		<0.002%		
		V_O = +10 V, A_{VD} = 5, See Note 5	TLE2037		<0.002%		
B_1	Unity-gain bandwidth (see Figure 3)	R_L = 2 kΩ, C_L = 100 pF	TLE2027		13		MHz
			TLE2037		50		
B_{OM}	Maximum output-swing bandwidth	R_L = 2 kΩ	TLE2027		30		kHz
			TLE2037		80		
ϕ_m	Phase margin at unity gain (see Figure 3)	R_L = 2 kΩ, C_L = 100 pF	TLE2027		55°		
			TLE2037		50°		

NOTE 5: Measured distortion of the source used in the analysis was 0.002%.

PARAMETER MEASUREMENT INFORMATION



NOTE A: C_L includes fixture capacitance.

Figure 1. Slew-Rate Test Circuit



Figure 2. Noise-Voltage Test Circuit



NOTE A: C_L includes fixture capacitance.

Figure 3. Unity-Gain Bandwidth and Phase-Margin Test Circuit (TLE2027 Only)



NOTES: A. C_L includes fixture capacitance.
B. For the TLE2037 and TLE2037A, A_{VD} must be ≥ 5.

Figure 4. Small-Signal Pulse-Response Test Circuit

typical values

Typical values presented in this data sheet represent the median (50% point) of device parametric performance.

initial estimates of parameter distributions

In the ongoing program of improving data sheets and supplying more information to our customers, Texas Instruments has added an estimate of not only the typical values but also the spread around these values. These are in the form of distribution bars that show the 95% (upper) points and the 5% (lower) points from the characterization of the initial wafer lots of this new device type (see Figure 5). The distribution bars are shown at the points where data was actually collected. The 95% and 5% points are used instead of ± 3 sigma since some of the distributions are not true Gaussian distributions.

The number of units tested and the number of different wafer lots used are on all of the graphs where distribution bars are shown. As noted in Figure 5, there were a total of 835 units from two wafer lots. In this case, there is a good estimate for the within-lot variability and a possibly poor estimate of the lot-to-lot variability. This is always the case on newly released products since there can only be data available from a few wafer lots.

The distribution bars are not intended to replace the minimum and maximum limits in the electrical tables. Each distribution bar represents 90% of the total units tested at a specific temperature. While 10% of the units tested fell outside any given distribution bar, this should not be interpreted to mean that the same individual devices fell outside every distribution bar.



Figure 5. Sample Graph With Distribution Bars

TYPICAL CHARACTERISTICS

Table of Graphs

			FIGURE
V_{IO}	Input offset voltage	Distribution	6, 7
ΔV_{IO}	Input offset voltage change	vs Time after power on	8, 9
I_{IO}	Input offset current	vs Free-air temperature	10
I_{IB}	Input bias current	vs Free-air temperature vs Common-mode input voltage	11 12
I_I	Input current	vs Differential input voltage	13
$V_{O(PP)}$	Maximum peak-to-peak output voltage	vs Frequency	14, 15
V_{OM}	Maximum (positive/negative) peak output voltage	vs Load resistance vs Free-air temperature	16, 17 18, 19
A_{VD}	Large-signal differential voltage amplification	vs Supply voltage vs Load resistance vs Frequency vs Free-air temperature	20 21 22 – 25 26
z_o	Output impedance	vs Frequency	27
CMRR	Common-mode rejection ratio	vs Frequency	28
k_{SVR}	Supply-voltage rejection ratio	vs Frequency	29
I_{OS}	Short-circut output current	vs Supply voltage vs Elapsed time vs Free-air temperature	30, 31 32, 33 34, 35
I_{CC}	Supply current	vs Supply voltage vs Free-air temperature	36 37
	Voltage-follower pulse response	Small signal Large signal	38, 40 39, 41
V_n	Equivalent input noise voltage	vs Frequency	42
	Noise voltage (referred to input)	Over 10-second interval	43
B_1	Unity-gain bandwidth	vs Supply voltage vs Load capacitance	44 45
	Gain bandwidth product	vs Supply voltage vs Load capacitance	46 47
SR	Slew rate	vs Free-air temperature	48, 49
ϕ_m	Phase margin	vs Supply voltage vs Load capacitance vs Free-air temperature	50, 51 52, 53 54, 55
	Phase shift	vs Frequency	22 – 25

TYPICAL CHARACTERISTICS

**DISTRIBUTION
INPUT OFFSET VOLTAGE**



Figure 6

**INPUT OFFSET VOLTAGE CHANGE
vs
TIME AFTER POWER ON**



Figure 7

**INPUT OFFSET VOLTAGE CHANGE
vs
TIME AFTER POWER ON**



Figure 8

INPUT OFFSET CURRENT† vs FREE-AIR TEMPERATURE



Figure 9

† Data at high and low temperatures are applicable only within the rated operating free-air temperature ranges of the various devices.

TYPICAL CHARACTERISTICS

INPUT BIAS CURRENT † vs FREE-AIR TEMPERATURE



Figure 10

INPUT BIAS CURRENT vs COMMON-MODE INPUT VOLTAGE



Figure 11

INPUT CURRENT vs DIFFERENTIAL INPUT VOLTAGE



Figure 12

TLE2027 MAXIMUM PEAK-TO-PEAK OUTPUT VOLTAGE† vs FREQUENCY



Figure 13

† Data at high and low temperatures are applicable only within the rated operating free-air temperature ranges of the various devices.

TYPICAL CHARACTERISTICS

TLE2037
MAXIMUM PEAK-TO-PEAK OUTPUT VOLTAGE† vs FREQUENCY



Figure 14

MAXIMUM POSITIVE PEAK OUTPUT VOLTAGE vs LOAD RESISTANCE



Figure 15

MAXIMUM NEGATIVE PEAK OUTPUT VOLTAGE vs LOAD RESISTANCE



Figure 16

MAXIMUM POSITIVE PEAK OUTPUT VOLTAGE† vs FREE-AIR TEMPERATURE



Figure 17

† Data at high and low temperatures are applicable only within the rated operating free-air temperature ranges of the various devices.

TYPICAL CHARACTERISTICS

MAXIMUM NEGATIVE PEAK OUTPUT VOLTAGE† vs FREE-AIR TEMPERATURE



Figure 18

LARGE-SIGNAL DIFFERENTIAL VOLTAGE AMPLIFICATION vs SUPPLY VOLTAGE



Figure 19

LARGE-SIGNAL DIFFERENTIAL VOLTAGE AMPLIFICATION vs LOAD RESISTANCE



Figure 20

† Data at high and low temperatures are applicable only within the rated operating free-air temperature ranges of the various devices.

TYPICAL CHARACTERISTICS

TLE2027
LARGE-SIGNAL DIFFERENTIAL VOLTAGE AMPLIFICATION AND PHASE SHIFT vs FREQUENCY



Figure 21

TLE2037
LARGE-SIGNAL DIFFERENTIAL VOLTAGE AMPLIFICATION AND PHASE SHIFT vs FREQUENCY



Figure 22

TYPICAL CHARACTERISTICS

TLE2027
LARGE-SIGNAL DIFFERENTIAL VOLTAGE AMPLIFICATION AND PHASE SHIFT vs FREQUENCY



Figure 23

TLE2037
LARGE-SIGNAL DIFFERENTIAL VOLTAGE AMPLIFICATION AND PHASE SHIFT vs FREQUENCY



Figure 24

TYPICAL CHARACTERISTICS

LARGE-SIGNAL DIFFERENTIAL VOLTAGE AMPLIFICATION† vs FREE-AIR TEMPERATURE



Figure 25

OUTPUT IMPEDANCE vs FREQUENCY



NOTE A: For this curve, the TLE2027 is A_{VD} = 1 and the TLE2037 is A_{VD} = 5.

Figure 26

COMMON-MODE REJECTION RATIO vs FREQUENCY



Figure 27

SUPPLY-VOLTAGE REJECTION RATIO vs FREQUENCY



Figure 28

† Data at high and low temperatures are applicable only within the rated operating free-air temperature ranges of the various devices.

TYPICAL CHARACTERISTICS

SHORT-CIRCUIT OUTPUT CURRENT vs SUPPLY VOLTAGE



Figure 29

SHORT-CIRCUIT OUTPUT CURRENT vs SUPPLY VOLTAGE



Figure 30

SHORT-CIRCUIT OUTPUT CURRENT vs ELAPSED TIME



Figure 31

SHORT-CIRCUIT OUTPUT CURRENT vs ELAPSED TIME



Figure 32

TYPICAL CHARACTERISTICS

SHORT-CIRCUIT OUTPUT CURRENT † vs FREE-AIR TEMPERATURE



Figure 33

SHORT-CIRCUIT OUTPUT CURRENT † vs FREE-AIR TEMPERATURE



Figure 34

SUPPLY CURRENT † vs SUPPLY VOLTAGE



Figure 35

SUPPLY CURRENT † vs FREE-AIR TEMPERATURE



Figure 36

† Data at high and low temperatures are applicable only within the rated operating free-air temperature ranges of the various devices.

TYPICAL CHARACTERISTICS

**TLE2027
VOLTAGE-FOLLOWER
SMALL-SIGNAL
PULSE RESPONSE**



Figure 37

**TLE2027
VOLTAGE-FOLLOWER
LARGE-SIGNAL
PULSE RESPONSE**



Figure 38

**TLE2037
VOLTAGE-FOLLOWER
SMALL-SIGNAL
PULSE RESPONSE**



Figure 39

**TLE2037
VOLTAGE-FOLLOWER
LARGE-SIGNAL
PULSE RESPONSE**



Figure 40

TYPICAL CHARACTERISTICS

EQUIVALENT INPUT NOISE VOLTAGE vs FREQUENCY



Figure 41

NOISE VOLTAGE (REFERRED TO INPUT) OVER A 10-SECOND INTERVAL



Figure 42

TLE2027 UNITY-GAIN BANDWIDTH vs SUPPLY VOLTAGE



Figure 43

TLE2037 GAIN-BANDWIDTH PRODUCT vs SUPPLY VOLTAGE



Figure 44

TYPICAL CHARACTERISTICS

TLE2027
UNITY-GAIN BANDWIDTH
vs
LOAD CAPACITANCE



Figure 45

TLE2037
GAIN-BANDWIDTH PRODUCT
vs
LOAD CAPACITANCE



Figure 46

TLE2027
SLEW RATE†
vs
FREE-AIR TEMPERATURE



Figure 47

TLE2037
SLEW RATE†
vs
FREE-AIR TEMPERATURE



Figure 48

† Data at high and low temperatures are applicable only within the rated operating free-air temperature ranges of the various devices.

TYPICAL CHARACTERISTICS

**TLE2027
PHASE MARGIN
vs
SUPPLY VOLTAGE**



Figure 49

**TLE2037
PHASE MARGIN
vs
SUPPLY VOLTAGE**



Figure 50

**TLE2027
PHASE MARGIN
vs
LOAD CAPACITANCE**



Figure 51

**TLE2037
PHASE MARGIN
vs
LOAD CAPACITANCE**



Figure 52

TYPICAL CHARACTERISTICS

TLE2027
PHASE MARGIN† vs FREE-AIR TEMPERATURE



Figure 53

TLE2037
PHASE MARGIN† vs FREE-AIR TEMPERATURE



Figure 54

† Data at high and low temperatures are applicable only within the rated operating free-air temperature ranges of the various devices.

APPLICATION INFORMATION

input offset voltage nulling

The TLE2027 and TLE2037 series offers external null pins that can be used to further reduce the input offset voltage. The circuits of Figure 55 can be connected as shown if the feature is desired. If external nulling is not needed, the null pins may be left disconnected.



Figure 55. Input Offset Voltage Nulling Circuits

voltage-follower applications

The TLE2027 circuitry includes input-protection diodes to limit the voltage across the input transistors; however, no provision is made in the circuit to limit the current if these diodes are forward biased. This condition can occur when the device is operated in the voltage-follower configuration and driven with a fast, large-signal pulse. It is recommended that a feedback resistor be used to limit the current to a maximum of 1 mA to prevent degradation of the device. Also, this feedback resistor forms a pole with the input capacitance of the device. For feedback resistor values greater than 10 kΩ, this pole degrades the amplifier phase margin. This problem can be alleviated by adding a capacitor (20 pF to 50 pF) in parallel with the feedback resistor (see Figure 56).



Figure 56. Voltage Follower

APPLICATION INFORMATION

macromodel information

Macromodel information provided was derived using Microsim *Parts*™, the model generation software used with Microsim *PSpice*™. The Boyle macromodel (see Note 6) and subcircuit in Figure 57, Figure 58, and Figure 59 were generated using the TLE20x7 typical electrical and operating characteristics at 25°C. Using this information, output simulations of the following key parameters can be generated to a tolerance of 20% (in most cases):

- Maximum positive output voltage swing
- Maximum negative output voltage swing
- Slew rate
- Quiescent power dissipation
- Input bias current
- Open-loop voltage amplification
- Gain-bandwidth product
- Common-mode rejection ratio
- Phase margin
- DC output resistance
- AC output resistance
- Short-circuit output current limit

NOTE 6: G. R. Boyle, B. M. Cohn, D. O. Pederson, and J. E. Solomon, “Macromodeling of Integrated Circuit Operational Amplifiers”, IEEE Journal of Solid-State Circuits, SC-9, 353 (1974).



Figure 57. Boyle Macromodel

PSpice and *Parts* are trademarks of MicroSim Corporation.

APPLICATION INFORMATION

macromodel information (continued)

```
.subckt TLE2027 1 2 3 4 5
*
  c1      11   12   4.003E-12
  c2       6    7   20.00E-12
  dc       5   53   dz
  de      54    5   dz
  dlp     90   91   dz
  dln     92   90   dx
  dp       4    3   dz
  egnd    99    0   poly(2) (3,0)
(4,0) 0 5 .5
  fb       7   99   poly(5) vb vc
ve vlp vln 0 954.8E6 -1E9 1E9 1E9
-1E9
  ga       6    0   11  12
2.062E-3
  gcm      0    6   10  99
531.3E-12
  iee     10    4   dc  56.01E-6
  hlim    90    0   vlim 1K
  q1      11    2   13 qx
  q2      12    1   14 qx
  r2       6    9   100.0E3
  rc1      3   11   530.5
  rc2      3   12   530.5
  re1     13   10   -393.2
  re2     14   10   -393.2
  ree     10   99   3.571E6
  ro1      8    5   25
  ro2      7   99   25
  rp       3    4   8.013E3
  vb       9    0   dc  0
  vc       3   53   dc  2.400
  ve      54    4   dc  2.100
  vlim     7    8   dc  0
  vlp     91    0   dc  40
  vln      0   92   dc  40
.modeldx D(Is=800.0E-18)
.modelqx NPN(Is=800.0E-18
Bf=7.000E3)
.ends
```

Figure 58. TLE2027 Macromodel Subcircuit

```
.subckt TLE2037 1 2 3 4 5
*
  c1      11   12   4.003E-12
  c2       6    7   7.500E-12
  dc       5   53   dz
  de      54    5   dz
  dlp     90   91   dz
  dln     92   90   dx
  dp       4    3   dz
  egnd    99    0   poly(2)  (3,0)
     (4,0)  0  .5  .5
  fb       7   99   poly(5)  vb vc
     ve vip vln 0 923.4E6 A800E6
     800E6 800E6 A800E6
  ga       6    0   11 12 2.121E-3
  gcm      0    6   10 99 597.7E-12
  iee     10    4   dc 56.26E-6
  hlim    90    0   vlim 1K
  q1      11    2   13 qx
  q2      12    1   14 qz
  r2       6    9   100.0E3
  rc1      3   11   471.5
  rc2      3   12   471.5
  re1     13   10   A448
  re2     14   10   A448
  ree     10   99   3.555E6
  ro1      8    5   25
  ro2      7   99   25
  rp       3    4   8.013E3
  vb       9    0   dc 0
  vc       3   53   dc  2.400
  ve      54    4   dc  2.100
  vlim     7    8   dc  0
  vlp     91    0   dc  40
  vln      0   92   dc  40
.model    dxD(Is=800.0E-18)
.model    qxNPN(Is=800.0E-18
    Bf=7.031E3)
.ends
```

Figure 59. TLE2037 Macromodel Subcircuit

REVISION HISTORY

Changes from Revision B (October 2006) to Revision C

- Changed values of V_n, $V_{N(PP)}$, and I_n 11

PACKAGING INFORMATION

Orderable Device	Status (1)	Package Type	Package Drawing	Pins	Package Qty	Eco Plan (2)	Lead/ Ball Finish	MSL Peak Temp (3)	Samples (Requires Login)
5962-9089601M2A	ACTIVE	LCCC	FK	20	1	TBD	Call TI	Call TI	
5962-9089601MPA	ACTIVE	CDIP	JG	8	1	TBD	Call TI	Call TI	
5962-9089602MPA	OBSOLETE	CDIP	JG	8		TBD	Call TI	Call TI	
5962-9089603Q2A	ACTIVE	LCCC	FK	20	1	TBD	Call TI	Call TI	
5962-9089603QPA	ACTIVE	CDIP	JG	8	1	TBD	Call TI	Call TI	
TLE2027ACD	OBSOLETE	SOIC	D	8		TBD	Call TI	Call TI	
TLE2027ACP	OBSOLETE	PDIP	P	8		TBD	Call TI	Call TI	
TLE2027AID	OBSOLETE	SOIC	D	8		TBD	Call TI	Call TI	
TLE2027AIP	OBSOLETE	PDIP	P	8		TBD	Call TI	Call TI	
TLE2027AMD	ACTIVE	SOIC	D	8	75	Green (RoHS & no Sb/Br)	CU NIPDAU	Level-1-260C-UNLIM	
TLE2027AMDG4	ACTIVE	SOIC	D	8	75	Green (RoHS & no Sb/Br)	CU NIPDAU	Level-1-260C-UNLIM	
TLE2027AMFKB	ACTIVE	LCCC	FK	20	1	TBD	POST-PLATE	N / A for Pkg Type	
TLE2027AMJG	ACTIVE	CDIP	JG	8	1	TBD	A42	N / A for Pkg Type	
TLE2027AMJGB	ACTIVE	CDIP	JG	8	1	TBD	A42	N / A for Pkg Type	
TLE2027CD	ACTIVE	SOIC	D	8	75	Green (RoHS & no Sb/Br)	CU NIPDAU	Level-1-260C-UNLIM	
TLE2027CDG4	ACTIVE	SOIC	D	8	75	Green (RoHS & no Sb/Br)	CU NIPDAU	Level-1-260C-UNLIM	
TLE2027CDR	ACTIVE	SOIC	D	8	2500	Green (RoHS & no Sb/Br)	CU NIPDAU	Level-1-260C-UNLIM	
TLE2027CDRG4	ACTIVE	SOIC	D	8	2500	Green (RoHS & no Sb/Br)	CU NIPDAU	Level-1-260C-UNLIM	
TLE2027CP	OBSOLETE	PDIP	P	8		TBD	Call TI	Call TI	
TLE2027ID	ACTIVE	SOIC	D	8	75	Green (RoHS & no Sb/Br)	CU NIPDAU	Level-1-260C-UNLIM	
TLE2027IDG4	ACTIVE	SOIC	D	8	75	Green (RoHS & no Sb/Br)	CU NIPDAU	Level-1-260C-UNLIM	
TLE2027IDR	ACTIVE	SOIC	D	8	2500	Green (RoHS & no Sb/Br)	CU NIPDAU	Level-1-260C-UNLIM	

Orderable Device	Status (1)	Package Type	Package Drawing	Pins	Package Qty	Eco Plan (2)	Lead/ Ball Finish	MSL Peak Temp (3)	Samples (Requires Login)
TLE2027IDRG4	ACTIVE	SOIC	D	8	2500	Green (RoHS & no Sb/Br)	CU NIPDAU	Level-1-260C-UNLIM	
TLE2027IP	OBSOLETE	PDIP	P	8		TBD	Call TI	Call TI	
TLE2027MD	ACTIVE	SOIC	D	8	75	Green (RoHS & no Sb/Br)	CU NIPDAU	Level-1-260C-UNLIM	
TLE2027MDG4	ACTIVE	SOIC	D	8	75	Green (RoHS & no Sb/Br)	CU NIPDAU	Level-1-260C-UNLIM	
TLE2027MFKB	ACTIVE	LCCC	FK	20	1	TBD	POST-PLATE	N / A for Pkg Type	
TLE2027MJG	ACTIVE	CDIP	JG	8	1	TBD	A42	N / A for Pkg Type	
TLE2027MJGB	ACTIVE	CDIP	JG	8	1	TBD	A42	N / A for Pkg Type	
TLE2037ACD	OBSOLETE	SOIC	D	8		TBD	Call TI	Call TI	
TLE2037ACP	OBSOLETE	PDIP	P	8		TBD	Call TI	Call TI	
TLE2037AID	OBSOLETE	SOIC	D	8		TBD	Call TI	Call TI	
TLE2037AIP	OBSOLETE	PDIP	P	8		TBD	Call TI	Call TI	
TLE2037AMD	ACTIVE	SOIC	D	8	75	Green (RoHS & no Sb/Br)	CU NIPDAU	Level-1-260C-UNLIM	
TLE2037AMDG4	ACTIVE	SOIC	D	8	75	Green (RoHS & no Sb/Br)	CU NIPDAU	Level-1-260C-UNLIM	
TLE2037AMJGB	OBSOLETE	CDIP	JG	8		TBD	Call TI	Call TI	
TLE2037CD	ACTIVE	SOIC	D	8	75	Green (RoHS & no Sb/Br)	CU NIPDAU	Level-1-260C-UNLIM	
TLE2037CDG4	ACTIVE	SOIC	D	8	75	Green (RoHS & no Sb/Br)	CU NIPDAU	Level-1-260C-UNLIM	
TLE2037CDR	ACTIVE	SOIC	D	8	2500	Green (RoHS & no Sb/Br)	CU NIPDAU	Level-1-260C-UNLIM	
TLE2037CDRG4	ACTIVE	SOIC	D	8	2500	Green (RoHS & no Sb/Br)	CU NIPDAU	Level-1-260C-UNLIM	
TLE2037CP	OBSOLETE	PDIP	P	8		TBD	Call TI	Call TI	
TLE2037ID	ACTIVE	SOIC	D	8	75	Green (RoHS & no Sb/Br)	CU NIPDAU	Level-1-260C-UNLIM	
TLE2037IDG4	ACTIVE	SOIC	D	8	75	Green (RoHS & no Sb/Br)	CU NIPDAU	Level-1-260C-UNLIM	
TLE2037IDR	ACTIVE	SOIC	D	8	2500	Green (RoHS & no Sb/Br)	CU NIPDAU	Level-1-260C-UNLIM	

Orderable Device	Status (1)	Package Type	Package Drawing	Pins	Package Qty	Eco Plan (2)	Lead/ Ball Finish	MSL Peak Temp (3)	Samples (Requires Login)
TLE2037IDRG4	ACTIVE	SOIC	D	8	2500	Green (RoHS & no Sb/Br)	CU NIPDAU	Level-1-260C-UNLIM	
TLE2037IP	OBSOLETE	PDIP	P	8		TBD	Call TI	Call TI	
TLE2037MD	ACTIVE	SOIC	D	8	75	Green (RoHS & no Sb/Br)	CU NIPDAU	Level-1-260C-UNLIM	
TLE2037MDG4	ACTIVE	SOIC	D	8	75	Green (RoHS & no Sb/Br)	CU NIPDAU	Level-1-260C-UNLIM	
TLE2037MFKB	OBSOLETE	LCCC	FK	20		TBD	Call TI	Call TI	
TLE2037MJGB	OBSOLETE	CDIP	JG	8		TBD	Call TI	Call TI	

(1) The marketing status values are defined as follows:
ACTIVE: Product device recommended for new designs.
LIFEBUY: TI has announced that the device will be discontinued, and a lifetime-buy period is in effect.
NRND: Not recommended for new designs. Device is in production to support existing customers, but TI does not recommend using this part in a new design.
PREVIEW: Device has been announced but is not in production. Samples may or may not be available.
OBSOLETE: TI has discontinued the production of the device.

(2) Eco Plan - The planned eco-friendly classification: Pb-Free (RoHS), Pb-Free (RoHS Exempt), or Green (RoHS & no Sb/Br) - please check http://www.ti.com/productcontent for the latest availability information and additional product content details.
TBD: The Pb-Free/Green conversion plan has not been defined.
Pb-Free (RoHS): TI's terms "Lead-Free" or "Pb-Free" mean semiconductor products that are compatible with the current RoHS requirements for all 6 substances, including the requirement that lead not exceed 0.1% by weight in homogeneous materials. Where designed to be soldered at high temperatures, TI Pb-Free products are suitable for use in specified lead-free processes.
Pb-Free (RoHS Exempt): This component has a RoHS exemption for either 1) lead-based flip-chip solder bumps used between the die and package, or 2) lead-based die adhesive used between the die and leadframe. The component is otherwise considered Pb-Free (RoHS compatible) as defined above.
Green (RoHS & no Sb/Br): TI defines "Green" to mean Pb-Free (RoHS compatible), and free of Bromine (Br) and Antimony (Sb) based flame retardants (Br or Sb do not exceed 0.1% by weight in homogeneous material)

(3) MSL, Peak Temp. -- The Moisture Sensitivity Level rating according to the JEDEC industry standard classifications, and peak solder temperature.

Important Information and Disclaimer: The information provided on this page represents TI's knowledge and belief as of the date that it is provided. TI bases its knowledge and belief on information provided by third parties, and makes no representation or warranty as to the accuracy of such information. Efforts are underway to better integrate information from third parties. TI has taken and continues to take reasonable steps to provide representative and accurate information but may not have conducted destructive testing or chemical analysis on incoming materials and chemicals. TI and TI suppliers consider certain information to be proprietary, and thus CAS numbers and other limited information may not be available for release.

In no event shall TI's liability arising out of such information exceed the total purchase price of the TI part(s) at issue in this document sold by TI to Customer on an annual basis.

OTHER QUALIFIED VERSIONS OF TLE2027, TLE2027A, TLE2027AM, TLE2027M, TLE2037, TLE2037A :

- Catalog: TLE2027A, TLE2027
- Automotive: TLE2037-Q1, TLE2037A-Q1
- Enhanced Product: TLE2027-EP, TLE2027-EP
- Military: TLE2027M, TLE2027AM

NOTE: Qualified Version Definitions:

- Catalog - TI's standard catalog product
- Automotive - Q100 devices qualified for high-reliability automotive applications targeting zero defects
- Enhanced Product - Supports Defense, Aerospace and Medical Applications
- Military - QML certified for Military and Defense Applications

TAPE AND REEL INFORMATION

REEL DIMENSIONS



TAPE DIMENSIONS



A0	Dimension designed to accommodate the component width
B0	Dimension designed to accommodate the component length
K0	Dimension designed to accommodate the component thickness
W	Overall width of the carrier tape
P1	Pitch between successive cavity centers

QUADRANT ASSIGNMENTS FOR PIN 1 ORIENTATION IN TAPE



*All dimensions are nominal

Device	Package Type	Package Drawing	Pins	SPQ	Reel Diameter (mm)	Reel Width W1 (mm)	A0 (mm)	B0 (mm)	K0 (mm)	P1 (mm)	W (mm)	Pin1 Quadrant
TLE2027CDR	SOIC	D	8	2500	330.0	12.4	6.4	5.2	2.1	8.0	12.0	Q1
TLE2027IDR	SOIC	D	8	2500	330.0	12.4	6.4	5.2	2.1	8.0	12.0	Q1
TLE2037CDR	SOIC	D	8	2500	330.0	12.4	6.4	5.2	2.1	8.0	12.0	Q1
TLE2037IDR	SOIC	D	8	2500	330.0	12.4	6.4	5.2	2.1	8.0	12.0	Q1

TAPE AND REEL BOX DIMENSIONS



*All dimensions are nominal

Device	Package Type	Package Drawing	Pins	SPQ	Length (mm)	Width (mm)	Height (mm)
TLE2027CDR	SOIC	D	8	2500	340.5	338.1	20.6
TLE2027IDR	SOIC	D	8	2500	340.5	338.1	20.6
TLE2037CDR	SOIC	D	8	2500	340.5	338.1	20.6
TLE2037IDR	SOIC	D	8	2500	340.5	338.1	20.6

MCER001A – JANUARY 1995 – REVISED JANUARY 1997

JG (R-GDIP-T8) **CERAMIC DUAL-IN-LINE**



NOTES: A. All linear dimensions are in inches (millimeters).
B. This drawing is subject to change without notice.
C. This package can be hermetically sealed with a ceramic lid using glass frit.
D. Index point is provided on cap for terminal identification.
E. Falls within MIL STD 1835 GDIP1-T8

FK (S–CQCC–N**) LEADLESS CERAMIC CHIP CARRIER

28 TERMINAL SHOWN



NO. OF TERMINALS **	A		B	
	MIN	MAX	MIN	MAX
20	0.342 (8,69)	0.358 (9,09)	0.307 (7,80)	0.358 (9,09)
28	0.442 (11,23)	0.458 (11,63)	0.406 (10,31)	0.458 (11,63)
44	0.640 (16,26)	0.660 (16,76)	0.495 (12,58)	0.560 (14,22)
52	0.740 (18,78)	0.761 (19,32)	0.495 (12,58)	0.560 (14,22)
68	0.938 (23,83)	0.962 (24,43)	0.850 (21,6)	0.858 (21,8)
84	1.141 (28,99)	1.165 (29,59)	1.047 (26,6)	1.063 (27,0)



4040140/D 01/11

NOTES:
A. All linear dimensions are in inches (millimeters).
B. This drawing is subject to change without notice.
C. This package can be hermetically sealed with a metal lid.
D. Falls within JEDEC MS–004

P (R–PDIP–T8) PLASTIC DUAL–IN–LINE PACKAGE



NOTES:
A. All linear dimensions are in inches (millimeters).
B. This drawing is subject to change without notice.
C. Falls within JEDEC MS–001 variation BA.

D (R–PDSO–G8) PLASTIC SMALL OUTLINE



NOTES:
A. All linear dimensions are in inches (millimeters).
B. This drawing is subject to change without notice.
C. Body length does not include mold flash, protrusions, or gate burrs. Mold flash, protrusions, or gate burrs shall not exceed 0.006 (0,15) each side.
D. Body width does not include interlead flash. Interlead flash shall not exceed 0.017 (0,43) each side.
E. Reference JEDEC MS–012 variation AA.

D (R–PDSO–G8) PLASTIC SMALL OUTLINE



NOTES:
A. All linear dimensions are in millimeters.
B. This drawing is subject to change without notice.
C. Publication IPC–7351 is recommended for alternate designs.
D. Laser cutting apertures with trapezoidal walls and also rounding corners will offer better paste release. Customers should contact their board assembly site for stencil design recommendations. Refer to IPC–7525 for other stencil recommendations.
E. Customers should contact their board fabrication site for solder mask tolerances between and around signal pads.

IMPORTANT NOTICE

Texas Instruments Incorporated and its subsidiaries (TI) reserve the right to make corrections, enhancements, improvements and other changes to its semiconductor products and services per JESD46, latest issue, and to discontinue any product or service per JESD48, latest issue. Buyers should obtain the latest relevant information before placing orders and should verify that such information is current and complete. All semiconductor products (also referred to herein as “components”) are sold subject to TI’s terms and conditions of sale supplied at the time of order acknowledgment.

TI warrants performance of its components to the specifications applicable at the time of sale, in accordance with the warranty in TI’s terms and conditions of sale of semiconductor products. Testing and other quality control techniques are used to the extent TI deems necessary to support this warranty. Except where mandated by applicable law, testing of all parameters of each component is not necessarily performed.

TI assumes no liability for applications assistance or the design of Buyers’ products. Buyers are responsible for their products and applications using TI components. To minimize the risks associated with Buyers’ products and applications, Buyers should provide adequate design and operating safeguards.

TI does not warrant or represent that any license, either express or implied, is granted under any patent right, copyright, mask work right, or other intellectual property right relating to any combination, machine, or process in which TI components or services are used. Information published by TI regarding third-party products or services does not constitute a license to use such products or services or a warranty or endorsement thereof. Use of such information may require a license from a third party under the patents or other intellectual property of the third party, or a license from TI under the patents or other intellectual property of TI.

Reproduction of significant portions of TI information in TI data books or data sheets is permissible only if reproduction is without alteration and is accompanied by all associated warranties, conditions, limitations, and notices. TI is not responsible or liable for such altered documentation. Information of third parties may be subject to additional restrictions.

Resale of TI components or services with statements different from or beyond the parameters stated by TI for that component or service voids all express and any implied warranties for the associated TI component or service and is an unfair and deceptive business practice. TI is not responsible or liable for any such statements.

Buyer acknowledges and agrees that it is solely responsible for compliance with all legal, regulatory and safety-related requirements concerning its products, and any use of TI components in its applications, notwithstanding any applications-related information or support that may be provided by TI. Buyer represents and agrees that it has all the necessary expertise to create and implement safeguards which anticipate dangerous consequences of failures, monitor failures and their consequences, lessen the likelihood of failures that might cause harm and take appropriate remedial actions. Buyer will fully indemnify TI and its representatives against any damages arising out of the use of any TI components in safety-critical applications.

In some cases, TI components may be promoted specifically to facilitate safety-related applications. With such components, TI’s goal is to help enable customers to design and create their own end-product solutions that meet applicable functional safety standards and requirements. Nonetheless, such components are subject to these terms.

No TI components are authorized for use in FDA Class III (or similar life-critical medical equipment) unless authorized officers of the parties have executed a special agreement specifically governing such use.

Only those TI components which TI has specifically designated as military grade or “enhanced plastic” are designed and intended for use in military/aerospace applications or environments. Buyer acknowledges and agrees that any military or aerospace use of TI components which have ***not*** been so designated is solely at the Buyer's risk, and that Buyer is solely responsible for compliance with all legal and regulatory requirements in connection with such use.

TI has specifically designated certain components which meet ISO/TS16949 requirements, mainly for automotive use. Components which have not been so designated are neither designed nor intended for automotive use; and TI will not be responsible for any failure of such components to meet such requirements.

Products		**Applications**	
Audio	www.ti.com/audio	Automotive and Transportation	www.ti.com/automotive
Amplifiers	amplifier.ti.com	Communications and Telecom	www.ti.com/communications
Data Converters	dataconverter.ti.com	Computers and Peripherals	www.ti.com/computers
DLP® Products	www.dlp.com	Consumer Electronics	www.ti.com/consumer-apps
DSP	dsp.ti.com	Energy and Lighting	www.ti.com/energy
Clocks and Timers	www.ti.com/clocks	Industrial	www.ti.com/industrial
Interface	interface.ti.com	Medical	www.ti.com/medical
Logic	logic.ti.com	Security	www.ti.com/security
Power Mgmt	power.ti.com	Space, Avionics and Defense	www.ti.com/space-avionics-defense
Microcontrollers	microcontroller.ti.com	Video and Imaging	www.ti.com/video
RFID	www.ti-rfid.com		
OMAP Applications Processors	www.ti.com/omap	**TI E2E Community**	e2e.ti.com
Wireless Connectivity	www.ti.com/wirelessconnectivity		

Mailing Address: Texas Instruments, Post Office Box 655303, Dallas, Texas 75265
Copyright © 2012, Texas Instruments Incorporated