

## FEATURES

- ESD Protection for RS-232 I/O Pins
  - $\pm 15$  kV Human-Body Model (HBM)
  - $\pm 8$  kV IEC 61000-4-2, Contact Discharge
  - $\pm 8$  kV IEC 61000-4-2, Air-Gap Discharge
- 300- $\mu$ A Operating Supply Current
- 1- $\mu$ A Low-Power Standby (With Receivers Active) Mode
- Designed to Transmit at a Data Rate of 460 kbps
- Auto-Powerdown Plus Option Features Flexible Power-Saving Mode
- Operates From a Single 2.25-V to 3-V  $V_{CC}$  Supply

## APPLICATIONS

- Battery-Powered Systems
- PDAs
- Cellular Phones
- Notebooks
- Hand-Held Equipment
- Pagers

## DESCRIPTION/ORDERING INFORMATION

The TRS3318 is a dual-driver, dual-receiver, RS-232 compatible transceiver. The device features auto-powerdown plus and enhanced electrostatic discharge (ESD) protection integrated into the chip. Driver output and receiver input are protected to  $\pm 8$  kV using the IEC 61000-4-2 Air-Gap Discharge method,  $\pm 8$  kV using the IEC 61000-4-2 Contact Discharge method, and  $\pm 15$  kV using the Human-Body Model (HBM).


The device operates at a data rate of 460 kbps. The transceiver has a proprietary low-dropout driver output stage enabling RS-232-compatible operation from a 2.25-V to 3-V supply with a dual charge pump. The charge pump requires only four 0.1- $\mu$ F capacitors and features a logic-level output (READY) that asserts when the charge pump is regulating and the device is ready to begin transmitting.

The TRS3318 achieves a 1- $\mu$ A supply current using the auto-powerdown feature. This device automatically enters a low-power power-down mode when the RS-232 cable is disconnected or the drivers of the connected peripherals are inactive for more than 30 s. The device turns on again when it senses a valid transition at any driver or receiver input. Auto-powerdown saves power without changes to the existing BIOS or operating system.

This device is available in two space-saving packages: 20-pin SSOP and 20-pin TSSOP.

Flexible control options for power management are featured when the serial port and driver inputs are inactive. The auto-powerdown plus feature functions when FORCEON is low and FORCEOFF is high. During this mode of operation, if the device does not sense valid signal transitions on all receiver and driver inputs for approximately 30 s, the built-in charge pump and drivers are powered down, reducing the supply current to 1  $\mu$ A. By disconnecting the serial port or placing the peripheral drivers off, auto-powerdown plus can be disabled when FORCEON and FORCEOFF are high. With auto-powerdown plus enabled, the device activates automatically when a valid signal is applied to any receiver or driver input. INVALID is high (valid data) if any receiver input voltage is greater than 2.7 V or less than  $-2.7$  V, or has been between  $-0.3$  V and 0.3 V for less than 30  $\mu$ s (typical number). INVALID is low (invalid data) if all receiver input voltage are between  $-0.3$  V and 0.3 V for more than 30  $\mu$ s (typical number).

DB OR PW PACKAGE  
(TOP VIEW)



Please be aware that an important notice concerning availability, standard warranty, and use in critical applications of Texas Instruments semiconductor products and disclaimers thereto appears at the end of this data sheet.

**TRS3318**  
**2.5-V 460-kbps RS-232 TRANSCEIVER**  
**WITH ±15-kV ESD PROTECTION**

SLLS820–AUGUST 2007

**ORDERING INFORMATION**

| T <sub>A</sub> | PACKAGE <sup>(1)(2)</sup> |              | ORDERABLE PART NUMBER | TOP-SIDE MARKING |
|----------------|---------------------------|--------------|-----------------------|------------------|
| 0°C to 70°C    | SSOP – DB                 | Tube of 70   | TRS3318CDB            | RV18C            |
|                |                           | Reel of 2000 | TRS3318CDBR           |                  |
|                | TSSOP – PW                | Tube of 70   | TRS3318CPW            | RV18C            |
|                |                           | Reel of 2000 | TRS3318CPWR           |                  |
| –40°C to 85°C  | SSOP – DB                 | Tube of 70   | TRS3318IDB            | RV18I            |
|                |                           | Reel of 2000 | TRS3318IDBR           |                  |
|                | TSSOP – PW                | Tube of 70   | TRS3318IPW            | RV18I            |
|                |                           | Reel of 2000 | TRS3318IPWR           |                  |

(1) Package drawings, thermal data, and symbolization are available at [www.ti.com/packaging](http://www.ti.com/packaging).


(2) For the most current package and ordering information, see the Package Option Addendum at the end of this document, or see the TI website at [www.ti.com](http://www.ti.com).

**FUNCTION TABLE<sup>(1)</sup>**

| INPUT CONDITIONS               |          |                                     |                                        | OUTPUT STATES |          |         |       | OPERATING MODE                                |
|--------------------------------|----------|-------------------------------------|----------------------------------------|---------------|----------|---------|-------|-----------------------------------------------|
| FORCEON                        | FORCEOFF | RECEIVER OR DRIVER EDGE WITHIN 30 s | VALID RS-232 LEVEL PRESENT AT RECEIVER | DRIVER        | RECEIVER | INVALID | READY |                                               |
| Auto-Powerdown Plus Conditions |          |                                     |                                        |               |          |         |       |                                               |
| H                              | H        | No                                  | No                                     | Active        | Active   | L       | H     | Normal operation auto-powerdown plus disabled |
| H                              | H        | No                                  | Yes                                    | Active        | Active   | H       | H     | Normal operation auto-powerdown plus disabled |
| L                              | H        | Yes                                 | No                                     | Active        | Active   | L       | H     | Normal operation auto-powerdown plus enabled  |
| L                              | H        | Yes                                 | Yes                                    | Active        | Active   | H       | H     | Normal operation auto-powerdown plus enabled  |
| L                              | H        | No                                  | No                                     | Z             | Active   | L       | L     | Power down, auto-powerdown plus enabled       |
| L                              | H        | No                                  | Yes                                    | Z             | Active   | H       | L     | Power down, auto-powerdown plus enabled       |
| X                              | L        | X                                   | No                                     | Z             | Active   | L       | L     | Manual power down                             |
| X                              | L        | X                                   | Yes                                    | Z             | Active   | H       | L     | Manual power down                             |
| Auto-Powerdown Conditions      |          |                                     |                                        |               |          |         |       |                                               |
| INVALID                        | INVALID  | X                                   | No                                     | Z             | Active   | L       | L     | Power down, auto-powerdown enabled            |
| INVALID                        | INVALID  | X                                   | Yes                                    | Active        | Active   | H       | H     | Normal operation auto-powerdown enabled       |

(1) H = high level, L = low level, X = irrelevant, Z = high impedance

### LOGIC DIAGRAM (POSITIVE LOGIC)



### TERMINAL FUNCTIONS

| TERMINAL                     |        | DESCRIPTION                                                                                                                                                    |
|------------------------------|--------|----------------------------------------------------------------------------------------------------------------------------------------------------------------|
| NAME                         | NO.    |                                                                                                                                                                |
| C1+                          | 2      | Positive voltage-doubler charge-pump capacitor                                                                                                                 |
| C1–                          | 4      | Negative voltage-doubler charge-pump capacitor                                                                                                                 |
| C2+                          | 5      | Positive inverting charge-pump capacitor                                                                                                                       |
| C2–                          | 6      | Negative inverting charge-pump capacitor                                                                                                                       |
| DIN                          | 12, 13 | CMOS driver inputs                                                                                                                                             |
| DOUT                         | 8, 17  | RS-232 driver outputs                                                                                                                                          |
| $\overline{\text{FORCEOFF}}$ | 20     | Force-off input, active low. Drive low to power down transmitters, receivers, and charge pump. This overrides auto-powerdown and FORCEON (see Function Table). |
| FORCEON                      | 14     | Force-on input, active high. Drive high to override auto-powerdown, keeping transmitters and receivers on (FORCEOFF must be high) (see Function Table).        |
| GND                          | 18     | Ground                                                                                                                                                         |
| $\overline{\text{INVALID}}$  | 11     | Valid signal detector output, active low. A logic high indicates that a valid RS-232 level is present on a receiver input.                                     |
| READY                        | 1      | Ready to transmit output, active high. READY is enabled high when V– goes below –3.5 V and the device is ready to transmit.                                    |
| RIN                          | 9, 16  | RS-232 receiver inputs                                                                                                                                         |
| ROUT                         | 10, 15 | CMOS receiver outputs                                                                                                                                          |
| V+                           | 3      | $2 \times V_{CC}$ generated by the charge pump                                                                                                                 |
| V–                           | 7      | $-2 \times V_{CC}$ generated by the charge pump                                                                                                                |
| V <sub>CC</sub>              | 19     | 2.25-V to 3-V single-supply voltage                                                                                                                            |

# TRS3318

## 2.5-V 460-kbps RS-232 TRANSCEIVER

### WITH $\pm 15$ -kV ESD PROTECTION

SLLS820–AUGUST 2007

## Absolute Maximum Ratings<sup>(1)</sup>

over operating free-air temperature range (unless otherwise noted)

|                  |                                                         |                                            | MIN  | MAX                   | UNIT |
|------------------|---------------------------------------------------------|--------------------------------------------|------|-----------------------|------|
| V <sub>CC</sub>  | Supply voltage range                                    |                                            | −0.3 | 6                     | V    |
| V+               | Positive supply voltage range <sup>(2)</sup>            |                                            | −0.3 | 7                     | V    |
| V−               | Negative supply voltage range <sup>(2)</sup>            |                                            | −7   | 0.3                   | V    |
| V+ + IV−I        | Supply voltage differential <sup>(2)</sup>              |                                            |      | 13                    | V    |
| V <sub>I</sub>   | Input voltage                                           | DIN, FORCEON, FORCEOFF to GND              | −0.3 | 6                     | V    |
|                  |                                                         | RIN to GND                                 |      | ±25                   |      |
| V <sub>O</sub>   | Output voltage                                          | DOUT to GND                                |      | ±13.2                 | V    |
|                  |                                                         | ROUT, INVALID, READY to GND                | −0.3 | V <sub>CC</sub> + 0.3 |      |
|                  | Short-circuit duration                                  | DOUT to GND                                |      | Continuous            |      |
|                  | Continuous power dissipation<br>(T <sub>A</sub> = 70°C) | 16-pin SSOP (derate 7.14 mW/°C above 70°C) |      | 571                   | mW   |
|                  |                                                         | 20-pin SSOP (derate 8 mW/°C above 70°C)    |      | 640                   |      |
|                  |                                                         | 20-pin TSSOP (derate 7 mW/°C above 70°C)   |      | 559                   |      |
| T <sub>stg</sub> | Storage temperature range                               |                                            | −65  | 150                   | °C   |
|                  | Lead temperature (soldering, 10 s)                      |                                            |      | 300                   | °C   |

- (1) Stresses beyond those listed under "absolute maximum ratings" may cause permanent damage to the device. These are stress ratings only, and functional operation of the device at these or any other conditions beyond those indicated under "recommended operating conditions" is not implied. Exposure to absolute-maximum-rated conditions for extended periods may affect device reliability.
- (2)  $V+$  and  $V−$  can have maximum magnitudes of 7 V, but their absolute difference cannot exceed 13 V.

## Recommended Operating Conditions

See [Figure 4](#)

|                 |                                             |                                                |                                | MIN                   | NOM | MAX                   | UNIT |
|-----------------|---------------------------------------------|------------------------------------------------|--------------------------------|-----------------------|-----|-----------------------|------|
| Supply voltage  |                                             |                                                |                                | 2.25                  | 2.5 | 3                     | V    |
| V <sub>IH</sub> | Driver and control high-level input voltage | DIN, $\overline{\text{FORCEOFF}}$ ,<br>FORCEON | V <sub>CC</sub> = 2.5 V to 3 V | 0.7 × V <sub>CC</sub> |     | 5.5                   | V    |
| V <sub>IL</sub> | Driver and control low-level input voltage  | DIN, $\overline{\text{FORCEOFF}}$ ,<br>FORCEON | V <sub>CC</sub> = 2.5 V to 3 V | 0                     |     | 0.3 × V <sub>CC</sub> | V    |
| V <sub>I</sub>  | Receiver input voltage                      |                                                |                                | −25                   |     | 25                    | V    |
| T <sub>A</sub>  | Operating free-air temperature              | TRS3318C                                       |                                | 0                     |     | 70                    | °C   |
|                 |                                             | TRS3318I                                       |                                | −40                   |     | 85                    |      |

## Electrical Characteristics

$V_{CC} = 2.25\text{ V to }3\text{ V}$ ,  $C1–C4 = 0.1\text{ }\mu\text{F}$ ,  $T_A = T_{MIN}$  to  $T_{MAX}$  (unless otherwise noted)

| PARAMETER                                                                                           | TEST CONDITIONS                                           | MIN | TYP <sup>(1)</sup> | MAX | UNIT          |
|-----------------------------------------------------------------------------------------------------|-----------------------------------------------------------|-----|--------------------|-----|---------------|
| <b>DC Characteristics (<math>V_{CC} = 2.5\text{ V}</math>, <math>T_A = 25^\circ\text{C}</math>)</b> |                                                           |     |                    |     |               |
| Auto-powerdown plus supply current                                                                  | FORCEON = GND, FORCEOFF = $V_{CC}$ , All RIN and DIN idle |     | 1                  | 10  | $\mu\text{A}$ |
| Auto-powerdown supply current                                                                       | FORCEOFF = GND                                            |     | 1                  | 10  | $\mu\text{A}$ |
| Supply current                                                                                      | FORCEON = FORCEOFF = $V_{CC}$ , No load                   |     | 0.3                | 2   | mA            |

- (1) Typical values are at  $V_{CC} = 2.5\text{ V}$ ,  $T_A = 25^\circ\text{C}$ .

## ESD Protection

| PARAMETER | TEST CONDITIONS                        | TYP      | UNIT |
|-----------|----------------------------------------|----------|------|
| RIN, DOUT | Human-Body Model (HBM)                 | $\pm 15$ | kV   |
|           | IEC 61000-4-2 Air-Gap Discharge method | $\pm 8$  |      |
|           | IEC 61000-4-2 Contact Discharge method | $\pm 8$  |      |

## DRIVER SECTION

### Electrical Characteristics

over recommended ranges of supply voltage and operating free-air temperature,  
 $V_{CC} = 2.25\text{ V to }3\text{ V}$ ,  $C_1\text{--}C_4 = 0.1\text{ }\mu\text{F}$ ,  $T_A = T_{MIN}$  to  $T_{MAX}$  (unless otherwise noted) (see [Figure 4](#))

| PARAMETER                                            | TEST CONDITIONS                                                               | MIN  | TYP <sup>(1)</sup> | MAX | UNIT |
|------------------------------------------------------|-------------------------------------------------------------------------------|------|--------------------|-----|------|
| $V_{hys}$ Driver input hysteresis                    |                                                                               |      | 0.3                |     | V    |
| $I_{on}$ Input leakage current                       | FORCEON, DIN, $\overline{\text{FORCEOFF}}$                                    |      | ±0.01              | ±1  | μA   |
| $V_{om}$ Output voltage swing                        | All driver outputs loaded with 3 kΩ to ground                                 | ±3.7 | ±4                 |     | V    |
| $r_O$ Output resistance                              | $V_{CC} = 0$ , Driver output = ±2 V                                           | 300  | 10M                |     | Ω    |
| $I_{OS}$ Output short-circuit current <sup>(2)</sup> |                                                                               |      | ±25                | ±60 | mA   |
| $I_{off}$ Output leakage current                     | $V_{CC} = 0$ or 2.25 V to 3 V, $V_{OUT} = \pm 12\text{ V}$ , Drivers disabled |      |                    | ±25 | μA   |

(1) Typical values are at  $V_{CC} = 2.5\text{ V}$ ,  $T_A = 25^\circ\text{C}$ .

(2) Short-circuit durations should be controlled to prevent exceeding the device absolute power dissipation ratings, and not more than one output should be shorted at a time.

### Switching Characteristics

over recommended ranges of supply voltage and operating free-air temperature,  
 $V_{CC} = 2.25\text{ V to }3\text{ V}$ ,  $C_1\text{--}C_4 = 0.1\text{ }\mu\text{F}$ ,  $T_A = T_{MIN}$  to  $T_{MAX}$  (unless otherwise noted) (see [Figure 1](#))

| PARAMETER                                        | TEST CONDITIONS                                                                                                                                                                           | MIN | TYP <sup>(1)</sup> | MAX | UNIT |
|--------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----|--------------------|-----|------|
| Maximum data rate                                | $R_L = 3\text{ k}\Omega$ , $C_L = 1000\text{ pF}$ , One transmitter switching                                                                                                             | 460 |                    |     | kbps |
| $ t_{PHL} - t_{PLH} $ Driver skew <sup>(2)</sup> |                                                                                                                                                                                           |     | 100                |     | ns   |
| SR(tr) Transition-region slew rate               | $V_{CC} = 2.5\text{ V}$ , $T_A = 25^\circ\text{C}$ , $R_L = 3\text{ k}\Omega$ to $7\text{ k}\Omega$ , Measured from 3 V to –3 V or –3 V to 3 V, $C_L = 150\text{ pF}$ to $2500\text{ pF}$ | 4   |                    | 30  | V/μs |

(1) Typical values are at  $V_{CC} = 2.5\text{ V}$ ,  $T_A = 25^\circ\text{C}$ .

(2) Pulse skew is defined as  $|t_{PLH} - t_{PHL}|$  of each channel of the same device.

## RECEIVER SECTION

### Electrical Characteristics

over recommended ranges of supply voltage and operating free-air temperature,  
 $V_{CC} = 2.25\text{ V}$  to  $3\text{ V}$ ,  $C_1$ – $C_4 = 0.1\text{ }\mu\text{F}$ ,  $T_A = T_{MIN}$  to  $T_{MAX}$  (unless otherwise noted) (see [Figure 4](#))

| PARAMETER                              | TEST CONDITIONS            | MIN                 | TYP <sup>(1)</sup> | MAX                 | UNIT          |
|----------------------------------------|----------------------------|---------------------|--------------------|---------------------|---------------|
| $V_I$ Input voltage range              |                            | –25                 |                    | 25                  | V             |
| $V_{IT+}$ Input voltage threshold low  | $T_A = 25^\circ\text{C}$   |                     |                    | $0.3 \times V_{CC}$ | V             |
| $V_{IT-}$ Input voltage threshold high | $T_A = 25^\circ\text{C}$   | $0.7 \times V_{CC}$ |                    |                     | V             |
| $V_{hys}$ Input hysteresis             |                            |                     | 0.3                |                     | V             |
| $r_i$ Input resistance                 | $T_A = 25^\circ\text{C}$   | 3                   | 5                  | 7                   | k $\Omega$    |
| $I_{off}$ Output leakage current       |                            |                     | $\pm 0.05$         | $\pm 10$            | $\mu\text{A}$ |
| $V_{OL}$ Output voltage low            | $I_{OUT} = 0.5\text{ mA}$  |                     |                    | $0.1 \times V_{CC}$ | V             |
| $V_{OH}$ Output voltage high           | $I_{OUT} = -0.5\text{ mA}$ | $0.9 \times V_{CC}$ |                    |                     | V             |

(1) Typical values are at  $V_{CC} = 2.5\text{ V}$ ,  $T_A = 25^\circ\text{C}$ .

### Switching Characteristics

over recommended ranges of supply voltage and operating free-air temperature,  
 $V_{CC} = 2.25\text{ V}$  to  $3\text{ V}$ ,  $C_1$ – $C_4 = 0.1\text{ }\mu\text{F}$ ,  $T_A = T_{MIN}$  to  $T_{MAX}$  (unless otherwise noted) (see [Figure 4](#))

| PARAMETER                                          | TEST CONDITIONS                    | TYP <sup>(1)</sup> | UNIT          |
|----------------------------------------------------|------------------------------------|--------------------|---------------|
| $t_{PHL}$                                          | RIN to ROUT, $C_L = 150\text{ pF}$ | 0.175              | $\mu\text{s}$ |
| $t_{PLH}$                                          |                                    | 0.175              |               |
| $ t_{PHL} - t_{PLH} $ Receiver skew <sup>(2)</sup> |                                    | 50                 | ns            |

(1) Typical values are at  $V_{CC} = 2.5\text{ V}$ ,  $T_A = 25^\circ\text{C}$ .

(2) Pulse skew is defined as  $|t_{PLH} - t_{PHL}|$  of each channel of the same device.

## AUTO-POWERDOWN PLUS SECTION

### Electrical Characteristics

over recommended ranges of supply voltage and operating free-air temperature,  
 $V_{CC} = 2.25\text{ V to }3\text{ V}$ ,  $C1\text{--}C4 = 0.1\text{ }\mu\text{F}$ ,  $T_A = T_{MIN}$  to  $T_{MAX}$  (unless otherwise noted) (see [Figure 4](#))

| PARAMETER                                                    | TEST CONDITIONS            | MIN                 | MAX                 | UNIT |
|--------------------------------------------------------------|----------------------------|---------------------|---------------------|------|
| Receiver input threshold to $\overline{\text{INVALID}}$ high | Positive threshold         |                     | 2.7                 | V    |
|                                                              | Negative threshold         | –2.7                |                     |      |
| Receiver input threshold $\overline{\text{INVALID}}$ low     |                            | –0.3                | 0.3                 | V    |
| $\overline{\text{INVALID}}$ , READY voltage low              | $I_{OUT} = 0.5\text{ mA}$  |                     | $0.1 \times V_{CC}$ | V    |
| $\overline{\text{INVALID}}$ , READY voltage high             | $I_{OUT} = -0.5\text{ mA}$ | $0.8 \times V_{CC}$ |                     | V    |


### Switching Characteristics

over recommended ranges of supply voltage and operating free-air temperature,  
 $V_{CC} = 2.25\text{ V to }3\text{ V}$ ,  $C1\text{--}C4 = 0.1\text{ }\mu\text{F}$ ,  $T_A = T_{MIN}$  to  $T_{MAX}$  (unless otherwise noted) (see [Figure 4](#))

| PARAMETER                                                                              | TEST CONDITIONS         | MIN | TYP <sup>(1)</sup> | MAX | UNIT          |
|----------------------------------------------------------------------------------------|-------------------------|-----|--------------------|-----|---------------|
| $t_{INVH}$ Receiver positive or negative threshold to $\overline{\text{INVALID}}$ high | $V_{CC} = 2.5\text{ V}$ |     | 1                  |     | $\mu\text{s}$ |
| $t_{INVL}$ Receiver positive or negative threshold to $\overline{\text{INVALID}}$ low  | $V_{CC} = 2.5\text{ V}$ |     | 30                 |     | $\mu\text{s}$ |
| $t_{WU}$ Receiver or driver edge to driver enabled                                     | $V_{CC} = 2.5\text{ V}$ |     | 100                |     | $\mu\text{s}$ |
| $t_{AUTOPRDN}$ Receiver or driver edge to driver shutdown                              | $V_{CC} = 2.5\text{ V}$ | 15  | 30                 | 60  | s             |


(1) Typical values are at  $V_{CC} = 2.5\text{ V}$ ,  $T_A = 25^\circ\text{C}$ .

## PARAMETER MEASUREMENT INFORMATION




NOTES: A.  $C_L$  includes probe and jig capacitance.  
B. The pulse generator has the following characteristics: PRR = 250 kbit/s,  $Z_O = 50\ \Omega$ , 50% duty cycle,  $t_r \leq 10\text{ ns}$ ,  $t_f \leq 10\text{ ns}$ .

Figure 1. Driver Slew Rate



NOTES: A.  $C_L$  includes probe and jig capacitance.  
B. The pulse generator has the following characteristics: PRR = 250 kbit/s,  $Z_O = 50\ \Omega$ , 50% duty cycle,  $t_r \leq 10\text{ ns}$ ,  $t_f \leq 10\text{ ns}$ .


Figure 2. Driver Pulse Skew




NOTES: A.  $C_L$  includes probe and jig capacitance.  
B. The pulse generator has the following characteristics:  $Z_O = 50\ \Omega$ , 50% duty cycle,  $t_r \leq 10\text{ ns}$ ,  $t_f \leq 10\text{ ns}$ .

Figure 3. Receiver Propagation Delay Times


## PARAMETER MEASUREMENT INFORMATION



VOLTAGE WAVEFORMS




TEST CIRCUIT



† Auto power down disables drivers and reduces supply current to  $1\ \mu\text{A}$ .

Figure 4.  $\overline{\text{INVALID}}$  Propagation Delay Times and Supply Enabling Time

## APPLICATION INFORMATION



**Figure 5. Typical Application Circuit**

**PACKAGING INFORMATION**

| Orderable Device | Status <sup>(1)</sup> | Package Type | Package Drawing | Pins | Package Qty | Eco Plan <sup>(2)</sup>    | Lead/<br>Ball Finish | MSL Peak Temp <sup>(3)</sup> | Samples<br>(Requires Login) |
|------------------|-----------------------|--------------|-----------------|------|-------------|----------------------------|----------------------|------------------------------|-----------------------------|
| TRS3318CDB       | ACTIVE                | SSOP         | DB              | 20   |             | TBD                        | Call TI              | Call TI                      |                             |
| TRS3318CDBG4     | ACTIVE                | SSOP         | DB              | 20   |             | TBD                        | Call TI              | Call TI                      |                             |
| TRS3318CDBR      | ACTIVE                | SSOP         | DB              | 20   |             | TBD                        | Call TI              | Call TI                      |                             |
| TRS3318CDBRG4    | ACTIVE                | SSOP         | DB              | 20   |             | TBD                        | Call TI              | Call TI                      |                             |
| TRS3318CPW       | ACTIVE                | TSSOP        | PW              | 20   |             | TBD                        | Call TI              | Call TI                      |                             |
| TRS3318CPWG4     | ACTIVE                | TSSOP        | PW              | 20   |             | TBD                        | Call TI              | Call TI                      |                             |
| TRS3318CPWR      | ACTIVE                | TSSOP        | PW              | 20   |             | TBD                        | Call TI              | Call TI                      |                             |
| TRS3318CPWRG4    | ACTIVE                | TSSOP        | PW              | 20   |             | TBD                        | Call TI              | Call TI                      |                             |
| TRS3318IDB       | ACTIVE                | SSOP         | DB              | 20   |             | TBD                        | Call TI              | Call TI                      |                             |
| TRS3318IDBG4     | ACTIVE                | SSOP         | DB              | 20   |             | TBD                        | Call TI              | Call TI                      |                             |
| TRS3318IDBR      | ACTIVE                | SSOP         | DB              | 20   |             | TBD                        | Call TI              | Call TI                      |                             |
| TRS3318IDBRG4    | ACTIVE                | SSOP         | DB              | 20   |             | TBD                        | Call TI              | Call TI                      |                             |
| TRS3318IPW       | ACTIVE                | TSSOP        | PW              | 20   | 70          | Green (RoHS<br>& no Sb/Br) | CU NIPDAU            | Level-1-260C-UNLIM           |                             |
| TRS3318IPWG4     | ACTIVE                | TSSOP        | PW              | 20   | 70          | Green (RoHS<br>& no Sb/Br) | CU NIPDAU            | Level-1-260C-UNLIM           |                             |
| TRS3318IPWR      | ACTIVE                | TSSOP        | PW              | 20   |             | TBD                        | Call TI              | Call TI                      |                             |
| TRS3318IPWRG4    | ACTIVE                | TSSOP        | PW              | 20   |             | TBD                        | Call TI              | Call TI                      |                             |

<sup>(1)</sup> The marketing status values are defined as follows:

**ACTIVE:** Product device recommended for new designs.

**LIFEBUY:** TI has announced that the device will be discontinued, and a lifetime-buy period is in effect.

**NRND:** Not recommended for new designs. Device is in production to support existing customers, but TI does not recommend using this part in a new design.

**PREVIEW:** Device has been announced but is not in production. Samples may or may not be available.

**OBSOLETE:** TI has discontinued the production of the device.

<sup>(2)</sup> Eco Plan - The planned eco-friendly classification: Pb-Free (RoHS), Pb-Free (RoHS Exempt), or Green (RoHS & no Sb/Br) - please check <http://www.ti.com/productcontent> for the latest availability information and additional product content details.

**TBD:** The Pb-Free/Green conversion plan has not been defined.

**Pb-Free (RoHS):** TI's terms "Lead-Free" or "Pb-Free" mean semiconductor products that are compatible with the current RoHS requirements for all 6 substances, including the requirement that lead not exceed 0.1% by weight in homogeneous materials. Where designed to be soldered at high temperatures, TI Pb-Free products are suitable for use in specified lead-free processes.

**Pb-Free (RoHS Exempt):** This component has a RoHS exemption for either 1) lead-based flip-chip solder bumps used between the die and package, or 2) lead-based die adhesive used between the die and leadframe. The component is otherwise considered Pb-Free (RoHS compatible) as defined above.

---

**Green (RoHS & no Sb/Br):** TI defines "Green" to mean Pb-Free (RoHS compatible), and free of Bromine (Br) and Antimony (Sb) based flame retardants (Br or Sb do not exceed 0.1% by weight in homogeneous material)

<sup>(3)</sup> MSL, Peak Temp. -- The Moisture Sensitivity Level rating according to the JEDEC industry standard classifications, and peak solder temperature.

**Important Information and Disclaimer:** The information provided on this page represents TI's knowledge and belief as of the date that it is provided. TI bases its knowledge and belief on information provided by third parties, and makes no representation or warranty as to the accuracy of such information. Efforts are underway to better integrate information from third parties. TI has taken and continues to take reasonable steps to provide representative and accurate information but may not have conducted destructive testing or chemical analysis on incoming materials and chemicals. TI and TI suppliers consider certain information to be proprietary, and thus CAS numbers and other limited information may not be available for release.

In no event shall TI's liability arising out of such information exceed the total purchase price of the TI part(s) at issue in this document sold by TI to Customer on an annual basis.

PW (R-PDSO-G20)


PLASTIC SMALL OUTLINE



- NOTES:
- A. All linear dimensions are in millimeters. Dimensioning and tolerancing per ASME Y14.5M-1994.
  - B. This drawing is subject to change without notice.
  - C. Body length does not include mold flash, protrusions, or gate burrs. Mold flash, protrusions, or gate burrs shall not exceed 0,15 each side.
  - D. Body width does not include interlead flash. Interlead flash shall not exceed 0,25 each side.
  - E. Falls within JEDEC MO-153

PW (R-PDSO-G20)

PLASTIC SMALL OUTLINE



- NOTES:
- A. All linear dimensions are in millimeters.
  - B. This drawing is subject to change without notice.
  - C. Publication IPC-7351 is recommended for alternate design.
  - D. Laser cutting apertures with trapezoidal walls and also rounding corners will offer better paste release. Customers should contact their board assembly site for stencil design recommendations. Refer to IPC-7525 for other stencil recommendations.
  - E. Customers should contact their board fabrication site for solder mask tolerances between and around signal pads.

## DB (R-PDSO-G\*\*)

## PLASTIC SMALL-OUTLINE

28 PINS SHOWN



- NOTES: A. All linear dimensions are in millimeters.  
 B. This drawing is subject to change without notice.  
 C. Body dimensions do not include mold flash or protrusion not to exceed 0,15.  
 D. Falls within JEDEC MO-150

## IMPORTANT NOTICE

Texas Instruments Incorporated and its subsidiaries (TI) reserve the right to make corrections, enhancements, improvements and other changes to its semiconductor products and services per JESD46C and to discontinue any product or service per JESD48B. Buyers should obtain the latest relevant information before placing orders and should verify that such information is current and complete. All semiconductor products (also referred to herein as "components") are sold subject to TI's terms and conditions of sale supplied at the time of order acknowledgment.

TI warrants performance of its components to the specifications applicable at the time of sale, in accordance with the warranty in TI's terms and conditions of sale of semiconductor products. Testing and other quality control techniques are used to the extent TI deems necessary to support this warranty. Except where mandated by applicable law, testing of all parameters of each component is not necessarily performed.

TI assumes no liability for applications assistance or the design of Buyers' products. Buyers are responsible for their products and applications using TI components. To minimize the risks associated with Buyers' products and applications, Buyers should provide adequate design and operating safeguards.

TI does not warrant or represent that any license, either express or implied, is granted under any patent right, copyright, mask work right, or other intellectual property right relating to any combination, machine, or process in which TI components or services are used. Information published by TI regarding third-party products or services does not constitute a license to use such products or services or a warranty or endorsement thereof. Use of such information may require a license from a third party under the patents or other intellectual property of the third party, or a license from TI under the patents or other intellectual property of TI.

Reproduction of significant portions of TI information in TI data books or data sheets is permissible only if reproduction is without alteration and is accompanied by all associated warranties, conditions, limitations, and notices. TI is not responsible or liable for such altered documentation. Information of third parties may be subject to additional restrictions.

Resale of TI components or services with statements different from or beyond the parameters stated by TI for that component or service voids all express and any implied warranties for the associated TI component or service and is an unfair and deceptive business practice. TI is not responsible or liable for any such statements.

Buyer acknowledges and agrees that it is solely responsible for compliance with all legal, regulatory and safety-related requirements concerning its products, and any use of TI components in its applications, notwithstanding any applications-related information or support that may be provided by TI. Buyer represents and agrees that it has all the necessary expertise to create and implement safeguards which anticipate dangerous consequences of failures, monitor failures and their consequences, lessen the likelihood of failures that might cause harm and take appropriate remedial actions. Buyer will fully indemnify TI and its representatives against any damages arising out of the use of any TI components in safety-critical applications.

In some cases, TI components may be promoted specifically to facilitate safety-related applications. With such components, TI's goal is to help enable customers to design and create their own end-product solutions that meet applicable functional safety standards and requirements. Nonetheless, such components are subject to these terms.

No TI components are authorized for use in FDA Class III (or similar life-critical medical equipment) unless authorized officers of the parties have executed a special agreement specifically governing such use.

Only those TI components which TI has specifically designated as military grade or "enhanced plastic" are designed and intended for use in military/aerospace applications or environments. Buyer acknowledges and agrees that any military or aerospace use of TI components which have **not** been so designated is solely at the Buyer's risk, and that Buyer is solely responsible for compliance with all legal and regulatory requirements in connection with such use.

TI has specifically designated certain components which meet ISO/TS16949 requirements, mainly for automotive use. Components which have not been so designated are neither designed nor intended for automotive use; and TI will not be responsible for any failure of such components to meet such requirements.

### Products

|                        |                                                                                      |
|------------------------|--------------------------------------------------------------------------------------|
| Audio                  | <a href="http://www.ti.com/audio">www.ti.com/audio</a>                               |
| Amplifiers             | <a href="http://amplifier.ti.com">amplifier.ti.com</a>                               |
| Data Converters        | <a href="http://dataconverter.ti.com">dataconverter.ti.com</a>                       |
| DLP® Products          | <a href="http://www.dlp.com">www.dlp.com</a>                                         |
| DSP                    | <a href="http://dsp.ti.com">dsp.ti.com</a>                                           |
| Clocks and Timers      | <a href="http://www.ti.com/clocks">www.ti.com/clocks</a>                             |
| Interface              | <a href="http://interface.ti.com">interface.ti.com</a>                               |
| Logic                  | <a href="http://logic.ti.com">logic.ti.com</a>                                       |
| Power Mgmt             | <a href="http://power.ti.com">power.ti.com</a>                                       |
| Microcontrollers       | <a href="http://microcontroller.ti.com">microcontroller.ti.com</a>                   |
| RFID                   | <a href="http://www.ti-rfid.com">www.ti-rfid.com</a>                                 |
| OMAP Mobile Processors | <a href="http://www.ti.com/omap">www.ti.com/omap</a>                                 |
| Wireless Connectivity  | <a href="http://www.ti.com/wirelessconnectivity">www.ti.com/wirelessconnectivity</a> |

### Applications

|                               |                                                                                          |
|-------------------------------|------------------------------------------------------------------------------------------|
| Automotive and Transportation | <a href="http://www.ti.com/automotive">www.ti.com/automotive</a>                         |
| Communications and Telecom    | <a href="http://www.ti.com/communications">www.ti.com/communications</a>                 |
| Computers and Peripherals     | <a href="http://www.ti.com/computers">www.ti.com/computers</a>                           |
| Consumer Electronics          | <a href="http://www.ti.com/consumer-apps">www.ti.com/consumer-apps</a>                   |
| Energy and Lighting           | <a href="http://www.ti.com/energy">www.ti.com/energy</a>                                 |
| Industrial                    | <a href="http://www.ti.com/industrial">www.ti.com/industrial</a>                         |
| Medical                       | <a href="http://www.ti.com/medical">www.ti.com/medical</a>                               |
| Security                      | <a href="http://www.ti.com/security">www.ti.com/security</a>                             |
| Space, Avionics and Defense   | <a href="http://www.ti.com/space-avionics-defense">www.ti.com/space-avionics-defense</a> |
| Video and Imaging             | <a href="http://www.ti.com/video">www.ti.com/video</a>                                   |

**TI E2E Community** [e2e.ti.com](http://e2e.ti.com)