

TOSHIBA

Leading Innovation >>>

Semiconductor Catalog Sep. 2017

Part Number List: 32-Bit Microcontrollers 製品品番一覧表: 32ビットマイクロコントローラ



SEMICONDUCTOR & STORAGE PRODUCTS

<https://toshiba.semicon-storage.com/>

Downloaded from [Arrow.com](https://arrow.com)

32-Bit Microcontrollers / 32ビットマイクロコントローラ

TXZ3 Series / TXZ3 シリーズ

M3H Group / M3H グループ (1)

Part Number	ROM (Bytes)	RAM (Bytes)	Data Flash (Bytes)	Maximum Operating Frequency (MHz)	DMA Controller (ch)	UART (ch)	I ² C (ch)	TSPI/SIO (ch) (32)	12-Bit AD Converter (ch)	8-Bit DA Converter (ch)	32-Bit (16-Bit) Timer/Counter (ch) (38)	Remote Control Preprocessor (ch)	3-Phase PWM Generator (PMD) (ch)	Incremental Encoder Input (ch)	External Interrupt Pins (Pins)	RTC (ch)	Low Level Detection Circuit (LVD)	Oscillation Frequency Detector (OFD)	I/O Port (Pins)	Operating Voltage Range (V)	Operating Temperature (°C)	Package																			
TMPM3H6FWFG	**	128K	18K	40	32	3	3	2	16	2	6 (12)	1	1	1	16	1	Yes	Yes	87	2.7 to 5.5	-40 to 85	LQFP100 (14 x 14 mm)																			
TMPM3H6FWDFG	**																						40	32	3	3	2	16	2	6 (12)	1	1	1	16	1	Yes	Yes	87	2.7 to 5.5	-40 to 85	QFP100 (14 x 20 mm)
TMPM3H5FWFG	**																						40	32	3	3	2	10	2	6 (12)	1	1	1	15	1	Yes	Yes	67	2.7 to 5.5	-40 to 85	LQFP80 (12 x 12 mm)
TMPM3H5FWDFG	**																						40	32	3	3	2	10	2	6 (12)	1	1	1	15	1	Yes	Yes	67	2.7 to 5.5	-40 to 85	LQFP80 (14 x 14 mm)
TMPM3H4FWUG	**																						40	32	3	3	2	8	1	6 (12)	1	1	1	11	1	Yes	Yes	53	2.7 to 5.5	-40 to 85	LQFP64 (10 x 10 mm)
TMPM3H4FWFG	**																						40	32	3	3	2	8	1	6 (12)	1	1	1	11	1	Yes	Yes	53	2.7 to 5.5	-40 to 85	LQFP64 (14 x 14 mm)
TMPM3H3FWUG	**																						40	32	3	3	2	8	1	6 (12)	1	1	1	8	1	Yes	Yes	43	2.7 to 5.5	-40 to 85	LQFP52 (10 x 10 mm)
TMPM3H2FWDUG	**																						40	30	3	2	2	8	1	6 (12)	1	1	1	7	1	Yes	Yes	40	2.7 to 5.5	-40 to 85	LQFP48 (7 x 7 mm)
TMPM3H2FWQG	**																						40	30	3	2	2	8	1	6 (12)	1	1	1	7	1	Yes	Yes	40	2.7 to 5.5	-40 to 85	VQFN48 (6 x 6 mm)
TMPM3H1FWUG	**																						40	30	3	2	2	8	0	6 (12)	1	1	1	6	0	Yes	Yes	36	2.7 to 5.5	-40 to 85	LQFP44 (10 x 10 mm)
TMPM3H6FUFG	**	96K	14K	40	32	3	3	2	16	2	6 (12)	1	1	1	16	1	Yes	Yes	87	2.7 to 5.5	-40 to 85	LQFP100 (14 x 14 mm)																			
TMPM3H6FUDFG	**																						40	32	3	3	2	16	2	6 (12)	1	1	1	16	1	Yes	Yes	87	2.7 to 5.5	-40 to 85	QFP100 (14 x 20 mm)
TMPM3H5FUFG	**																						40	32	3	3	2	10	2	6 (12)	1	1	1	15	1	Yes	Yes	67	2.7 to 5.5	-40 to 85	LQFP80 (12 x 12 mm)
TMPM3H5FUDFG	**																						40	32	3	3	2	10	2	6 (12)	1	1	1	15	1	Yes	Yes	67	2.7 to 5.5	-40 to 85	LQFP80 (14 x 14 mm)
TMPM3H4FUUG	**																						40	32	3	3	2	8	1	6 (12)	1	1	1	11	1	Yes	Yes	53	2.7 to 5.5	-40 to 85	LQFP64 (10 x 10 mm)
TMPM3H4FUFG	**																						40	32	3	3	2	8	1	6 (12)	1	1	1	11	1	Yes	Yes	53	2.7 to 5.5	-40 to 85	LQFP64 (14 x 14 mm)
TMPM3H3FUUG	**																						40	32	3	3	2	8	1	6 (12)	1	1	1	8	1	Yes	Yes	43	2.7 to 5.5	-40 to 85	LQFP52 (10 x 10 mm)
TMPM3H2FUDUG	**																						40	30	3	2	2	8	1	6 (12)	1	1	1	7	1	Yes	Yes	40	2.7 to 5.5	-40 to 85	LQFP48 (7 x 7 mm)
TMPM3H2FUQG	**																						40	30	3	2	2	8	1	6 (12)	1	1	1	7	1	Yes	Yes	40	2.7 to 5.5	-40 to 85	VQFN48 (6 x 6 mm)
TMPM3H1FUUG	**																						40	30	3	2	2	8	0	6 (12)	1	1	1	6	0	Yes	Yes	36	2.7 to 5.5	-40 to 85	LQFP44 (10 x 10 mm)
TMPM3H6FSFG	**	64K	10K	40	32	3	3	2	16	2	6 (12)	1	1	1	16	1	Yes	Yes	87	2.7 to 5.5	-40 to 85	LQFP100 (14 x 14 mm)																			
TMPM3H6FSDFG	**																						40	32	3	3	2	16	2	6 (12)	1	1	1	16	1	Yes	Yes	87	2.7 to 5.5	-40 to 85	QFP100 (14 x 20 mm)
TMPM3H5FSFG	**																						40	32	3	3	2	10	2	6 (12)	1	1	1	15	1	Yes	Yes	67	2.7 to 5.5	-40 to 85	LQFP80 (12 x 12 mm)
TMPM3H5FSDFG	**																						40	32	3	3	2	10	2	6 (12)	1	1	1	15	1	Yes	Yes	67	2.7 to 5.5	-40 to 85	LQFP80 (14 x 14 mm)
TMPM3H4FSUG	**																						40	32	3	3	2	8	1	6 (12)	1	1	1	11	1	Yes	Yes	53	2.7 to 5.5	-40 to 85	LQFP64 (10 x 10 mm)
TMPM3H4FSFG	**																						40	32	3	3	2	8	1	6 (12)	1	1	1	11	1	Yes	Yes	53	2.7 to 5.5	-40 to 85	LQFP64 (14 x 14 mm)
TMPM3H3FSUG	**																						40	32	3	3	2	8	1	6 (12)	1	1	1	8	1	Yes	Yes	43	2.7 to 5.5	-40 to 85	LQFP52 (10 x 10 mm)
TMPM3H2FSDUG	**																						40	30	3	2	2	8	1	6 (12)	1	1	1	7	1	Yes	Yes	40	2.7 to 5.5	-40 to 85	LQFP48 (7 x 7 mm)
TMPM3H2FSQG	**																						40	30	3	2	2	8	1	6 (12)	1	1	1	7	1	Yes	Yes	40	2.7 to 5.5	-40 to 85	VQFN48 (6 x 6 mm)
TMPM3H1FSUG	**																						40	30	3	2	2	8	0	6 (12)	1	1	1	6	0	Yes	Yes	36	2.7 to 5.5	-40 to 85	LQFP44 (10 x 10 mm)
TMPM3H0FSUG	**	40	24	2	1	1	4	0	6 (12)	1	1	1	6	0	Yes	Yes	24	2.7 to 5.5	-40 to 85	LQFP32 (7 x 7 mm)																					
TMPM3H1FPUG	**	48K	8K	8K	40	30	3	2	2	8	0	6 (12)	1	1	1	6	0	Yes	Yes	36	2.7 to 5.5	-40 to 85	LQFP44 (10 x 10 mm)																		
TMPM3H0FMUG	**	32K			40	24	2	1	1	4	0	6 (12)	1	1	1	6	0	Yes	Yes	24	2.7 to 5.5	-40 to 85	LQFP32 (7 x 7 mm)																		

Note (32), (38): Please refer to page 14. / P.15 をご参照ください。

** : Under planning / 計画中

• All products listed above incorporate a watchdog timer, a clock gear, an on-chip debug unit, power-on reset and voltage detection circuits.

** : Under development / 開発中

• ウォッチドッグタイマ、クロックギア機能、オンチップデバッグ機能、パワーオンリセット、電圧検出回路は上記製品に内蔵されています。

M3H Group / M3Hグループ (2)

Part Number	ROM (Bytes)	RAM (Bytes)	Data Flash (Bytes)	Maximum Operating Frequency (MHz)	DMA Controller (ch)	UART (ch)	I ² C (ch)	TSPI/SIO (ch) ⁽³²⁾	12-Bit AD Converter (ch)	8-Bit DA Converter (ch)	32-Bit (16-Bit) Timer/Counter (ch) ⁽³⁸⁾	Remote Control Preprocessor (ch)	3-Phase PWM Generator (PMD) (ch)	Incremental Encoder Input (ch)	External Interrupt Pins (Pins)	RTC (ch)	Low Level Detection Circuit (LVD)	Oscillation Frequency Detector (OFD)	I/O Port (Pins)	Operating Voltage Range (V)	Operating Temperature (°C)	Package
TMPM3HQDFG **	512K			80	64	6	4	5	21	2	8 (16)	1	1	1	32	1	Yes	Yes	134	2.7 to 5.5	-40 to 85	LQFP144 (20 x 20 mm)
TMPM3HPDFG **				80	64	6	4	5	19	2	8 (16)	1	1	1	29	1	Yes	Yes	118	2.7 to 5.5	-40 to 85	LQFP128 (14 x 14 mm)
TMPM3HNFDFG **				80	64	6	3	4	13	2	8 (16)	1	1	1	19	1	Yes	Yes	92	2.7 to 5.5	-40 to 85	LQFP100 (14 x 14 mm)
TMPM3HNFDDFG **				80	64	6	3	4	13	2	8 (16)	1	1	1	19	1	Yes	Yes	92	2.7 to 5.5	-40 to 85	QFP100 (14 x 20 mm)
TMPM3HMFDFG **				80	62	6	3	4	10	2	8 (16)	1	1	1	15	1	Yes	Yes	72	2.7 to 5.5	-40 to 85	LQFP80 (12 x 12 mm)
TMPM3HQFZFG **	384K	66K	32K	80	64	6	4	5	21	2	8 (16)	1	1	1	32	1	Yes	Yes	134	2.7 to 5.5	-40 to 85	LQFP144 (20 x 20 mm)
TMPM3HPFZFG **				80	64	6	4	5	19	2	8 (16)	1	1	1	29	1	Yes	Yes	118	2.7 to 5.5	-40 to 85	LQFP128 (14 x 14 mm)
TMPM3HNFZFG **				80	64	6	3	4	13	2	8 (16)	1	1	1	19	1	Yes	Yes	92	2.7 to 5.5	-40 to 85	LQFP100 (14 x 14 mm)
TMPM3HNFZDFG **				80	64	6	3	4	13	2	8 (16)	1	1	1	19	1	Yes	Yes	92	2.7 to 5.5	-40 to 85	QFP100 (14 x 20 mm)
TMPM3HMFZFG **				80	62	6	3	4	10	2	8 (16)	1	1	1	15	1	Yes	Yes	72	2.7 to 5.5	-40 to 85	LQFP80 (12 x 12 mm)
TMPM3HQFYFG **	256K			80	64	6	4	5	21	2	8 (16)	1	1	1	32	1	Yes	Yes	134	2.7 to 5.5	-40 to 85	LQFP144 (20 x 20 mm)
TMPM3HPFYFG **				80	64	6	4	5	19	2	8 (16)	1	1	1	29	1	Yes	Yes	118	2.7 to 5.5	-40 to 85	LQFP128 (14 x 14 mm)
TMPM3HNFYFG **				80	64	6	3	4	13	2	8 (16)	1	1	1	19	1	Yes	Yes	92	2.7 to 5.5	-40 to 85	LQFP100 (14 x 14 mm)
TMPM3HNFYDFG **				80	64	6	3	4	13	2	8 (16)	1	1	1	19	1	Yes	Yes	92	2.7 to 5.5	-40 to 85	QFP100 (14 x 20 mm)
TMPM3HMFYFG **				80	62	6	3	4	10	2	8 (16)	1	1	1	15	1	Yes	Yes	72	2.7 to 5.5	-40 to 85	LQFP80 (12 x 12 mm)

Note (32),(38): Please refer to page 14. / P.15をご参照ください。

**: Under development / 開発中

- ・ All products listed above incorporate a watchdog timer, a clock gear, a CRC circuit, an on-chip debug unit, power-on reset and voltage detection circuits.
- ・ ウォッチドッグタイマ、クロックギア機能、CRC回路、オンチップデバッグ機能、パワーオンリセット、電圧検出回路は上記製品に内蔵されています。

TXZ4 Series / TXZ4 シリーズ
M4K Group / M4K グループ

Part Number	ROM (Bytes)	RAM (Bytes)	Data Flash (Bytes)	Maximum Operating Frequency (MHz)	DMA Controller (ch)	UART (ch)	I ² C (ch)	TSP/SIO (ch) ⁽³²⁾	12-Bit AD Converter (ch)	8-Bit DA Converter (ch)	32-Bit (16-Bit) Timer/Counter (ch)	3-Phase PWM Generator (A-PMG) (ch)	Advanced Vector Engine Plus (A-VE+) (ch)	Advanced Encoder (A-ENC) (ch)	Op Amp (ch)	Comparator (ch)	External Interrupt Pins (Pins)	RTC (ch)	Low Level Detection Circuit (LVD)	Oscillation Frequency Detector (OFD)	Non Break Debug (NBD) ⁽³⁷⁾	I/O Port (Pins)	Operating Voltage Range (V)	Operating Temperature (°C)	Package		
TMPM4K4FYAUG **	256K			80	32	4	1	4	13	6 (12)	2	1	1	3	11				Yes	Yes	Yes	52	2.7 to 5.5	-40 to 105	LQFP64 (10 x 10 mm)		
TMPM4K4FYAFG **				80	32	4	1	4	13	6 (12)	2	1	1	3	11					Yes	Yes	Yes	52	2.7 to 5.5	-40 to 105	LQFP64 (14 x 14 mm)	
TMPM4K2FYADUG **				80	26	3	1	2	11	6 (12)	2	1	1	3	10						Yes	Yes		40	2.7 to 5.5	-40 to 105	LQFP48 (7 x 7 mm)
TMPM4K1FYAUG **				80	24	2	1	2	10	6 (12)	1	1	1	3	9						Yes	Yes		36	2.7 to 5.5	-40 to 105	LQFP44 (10 x 10 mm)
TMPM4K4FWAUG **	128K			80	32	4	1	4	13	6 (12)	2	1	1	3	11				Yes	Yes	Yes	52	2.7 to 5.5	-40 to 105	LQFP64 (10 x 10 mm)		
TMPM4K4FWAFG **				80	32	4	1	4	13	6 (12)	2	1	1	3	11					Yes	Yes	Yes	52	2.7 to 5.5	-40 to 105	LQFP64 (14 x 14 mm)	
TMPM4K2FWADUG **				80	26	3	1	2	11	6 (12)	2	1	1	3	10						Yes	Yes		40	2.7 to 5.5	-40 to 105	LQFP48 (7 x 7 mm)
TMPM4K1FWAUG **				80	24	2	1	2	10	6 (12)	1	1	1	3	9						Yes	Yes		36	2.7 to 5.5	-40 to 105	LQFP44 (10 x 10 mm)
TMPM4K4FU AUG **	96K	18K		80	32	4	1	4	13	6 (12)	2	1	1	3	11				Yes	Yes	Yes	52	2.7 to 5.5	-40 to 105	LQFP64 (10 x 10 mm)		
TMPM4K4FU AFG **				80	32	4	1	4	13	6 (12)	2	1	1	3	11					Yes	Yes	Yes	52	2.7 to 5.5	-40 to 105	LQFP64 (14 x 14 mm)	
TMPM4K2FU ADUG **				80	26	3	1	2	11	6 (12)	2	1	1	3	10						Yes	Yes		40	2.7 to 5.5	-40 to 105	LQFP48 (7 x 7 mm)
TMPM4K1FU AUG **				80	24	2	1	2	10	6 (12)	1	1	1	3	9						Yes	Yes		36	2.7 to 5.5	-40 to 105	LQFP44 (10 x 10 mm)
TMPM4K4FSAUG **	64K			80	32	4	1	4	13	6 (12)	2	1	1	3	11				Yes	Yes	Yes	52	2.7 to 5.5	-40 to 105	LQFP64 (10 x 10 mm)		
TMPM4K4FSAFG **				80	32	4	1	4	13	6 (12)	2	1	1	3	11					Yes	Yes	Yes	52	2.7 to 5.5	-40 to 105	LQFP64 (14 x 14 mm)	
TMPM4K2FSADUG **				80	26	3	1	2	11	6 (12)	2	1	1	3	10						Yes	Yes		40	2.7 to 5.5	-40 to 105	LQFP48 (7 x 7 mm)
TMPM4K1FSAUG **				80	24	2	1	2	10	6 (12)	1	1	1	3	9						Yes	Yes		36	2.7 to 5.5	-40 to 105	LQFP44 (10 x 10 mm)
TMPM4K0FSADUG **				80	20	2		1	8	6 (12)	1	1	1	3	6				Yes	Yes		24	2.7 to 5.5	-40 to 105	LQFP32 (7 x 7 mm)		

Note (32),(37): Please refer to page 14. / P.15 をご参照ください。

** : Under development / 開発中

- All products listed above incorporate a watchdog timer, a clock gear, an on-chip debug unit, power-on reset and voltage detection circuits.
- ウォッチドッグタイマ、クロックギア機能、オンチップデバッグ機能、パワーオンリセット、電圧検出回路は上記製品に内蔵されています。

TX00 Series / TX00 シリーズ
M030 Group / M030 グループ

Part Number	ROM (Bytes)	SRAM (Bytes)	Maximum Operating Frequency (MHz)	LED Driver (ch)	LCD Driver (Seg. x Com.)	SSP (ch) ⁽²⁸⁾	UART/SIO (ch)	UART (ch)	I ² C (ch)	I ² C/SIO (ch)	CAN (ch)	USB Embedded Host (Full-Speed) (ch)	USB (Full-Speed) (ch)	10-Bit AD Converter (ch)	12-Bit AD Converter (ch)	24-Bit ΔΣ AD Converter (ch)	10-Bit DA Converter (ch)	16-Bit Timer/Counter (ch)	High-Res. 16-Bit Timer/PPG Gen. (ch)	3-Phase PWM Generator (PMD) (ch)	Multi-Purpose Timer (MPT) (ch)	Incremental Encoder Input (ch)	Power Calculation Engine	Temp. Sensor	External Interrupt Pins (Pins)	RTC (ch)	Dual Clocks	Trace Function	Oscillation Frequency Detector	Power-On Reset	Voltage Detecting Circuit	I/O Port (Pins)	Operating Voltage Range (V)	Operating Temperature (°C)	Package
TMPM036FWFG	128K	16K	20				6	2						8				14							6					Yes	Yes	86	2.3 to 3.6	-40 to 85	LQFP100 (14 x 14 mm)
TMPM037FWUG	128K	16K	20				5	1						8				10							6					Yes	Yes	52	2.3 to 3.6	-40 to 85	LQFP64 (10 x 10 mm)

Note (28): Please refer to page 14. / P.15 をご参照ください。

- ・ All products listed above incorporate a watchdog timer, a clock gear and an on-chip debug unit.
- ・ ウォッチドッグタイマ/クロックギア機能/オンチップデバッグ機能は上記製品に内蔵されています。

M060 Group / M060 グループ

Part Number	ROM (Bytes)	SRAM (Bytes)	Maximum Operating Frequency (MHz)	DMA Controller (ch)	LED Driver (ch)	LCD Driver (Seg. x Com.)	SSP (ch) ⁽²⁸⁾	UART/SIO (ch)	UART (ch)	I ² C (ch)	I ² C/SIO (ch)	TSP1 (ch)	USB (Full-Speed) (ch)	10-Bit AD Converter (ch)	12-Bit AD Converter (ch)	24-Bit ΔΣ AD Converter (ch)	10-Bit DA Converter (ch)	16-Bit Timer/Counter (ch)	High-Res. 16-Bit Timer/PPG Gen. (ch)	3-Phase PWM Generator (PMD) (ch)	Multi-Purpose Timer (MPT) (ch)	Incremental Encoder Input (ch)	Power Calculation Engine	Temp. Sensor	External Interrupt Pins (Pins)	RTC (ch)	Dual Clocks	Trace Function	Oscillation Frequency Detector	Power-On Reset	Voltage Detecting Circuit	I/O Port (Pins)	Operating Voltage Range (V)	Operating Temperature (°C)	Package
TMPM061FWFG	128K	8K	16		40 x 4		4				1			2		3		9					Yes	Yes	4	1	Yes			Yes	64	1.8 to 3.6	-40 to 85	LQFP100 (14 x 14 mm)	
TMPM066FWUG			24	28			2		2		1	1	8					11						6					Yes	48	LQFP64 (10 x 10 mm)				
TMPM067FWQG		16K	24	28				2		2		1	1	8					11						6					Yes	32			QFN48 (7 x 7 mm)	
TMPM068FWXBG			24	28				2		2		1	1	8					11						6					Yes	40			VFBA57 (5 x 5 mm)	

Note (28): Please refer to page 14. / P.15 をご参照ください。

- ・ All products listed above incorporate a watchdog timer, a clock gear and an on-chip debug unit.
- ・ ウォッチドッグタイマ/クロックギア機能/オンチップデバッグ機能は上記製品に内蔵されています。

M330 Group / M330 グループ

Part Number	ROM (Bytes)	SRAM (Bytes)	Maximum Operating Frequency (MHz) (11)	DMA Controller (ch)	SSP (ch) (28)	UART/SIO (ch)	UART (ch)	I ² C (ch)	I ² C/SIO (ch)	CAN (ch)	USB Embedded Host (Full-Speed) (ch)	USB (Full-Speed) (ch)	EtherMAC (ch)	10-Bit AD Converter (ch)	12-Bit AD Converter (ch)	10-Bit DA Converter (ch)	16-Bit Timer/Counter (ch)	High-Res. 16-Bit Timer/PPG Gen. (ch)	CEC (ch) (29)	Remote Control Preprocessor (ch)	Vector Engine (VE)	3-Phase PWM Generator (PMD) (ch)	Multi-Purpose Timer (MPT) (ch)	Incremental Encoder Input (ch)	Op Amp (ch)	Comparator (ch)	External Interrupt Pins (Pins)	CS/WAIT Controller (ch)	RTC (ch)	Oscillation Frequency Detector	I/O Port (Pins)	Operating Voltage Range (V)	Operating Temperature (°C)	Package
TMPM330FWFG	128K	8K	40		3			3						12		10		1	2								8	1	78	2.7 to 3.6	-20 to 85	LQFP100 (14 x 14 mm)		
TMPM332FWUG			40		2			2							8		10		1	1								5	1			44	LQFP64 (10 x 10 mm)	
TMPM333FWFG			40		3				3						12		10												8			1	78	
TMPM330FYFG	256K	16K	40		3			3						12		10		1	2									8	1	78	2.7 to 3.6	-40 to 85	LQFP100 (14 x 14 mm)	
TMPM330FYWFG			40		3			3							12		10		1	2								8	1	78				
TMPM333FYFG			40		3				3						12		10												8	1				78
TMPM330FDFG	512K	32K	40		3			3						12		10		1	2									8	1	78	2.7 to 3.6	-20 to 85		LQFP100 (14 x 14 mm)
TMPM330FDWFG			40		3			3							12		10		1	2								8	1	78				
TMPM333FDFG			40		3				3						12		10												8	1				

Note (11),(28),(29): Please refer to page 14. / P.15 をご参照ください。

- ・ All products listed above incorporate a watchdog timer, a clock gear and an on-chip debug unit.
- ・ ウォッチドッグタイマ、クロックギア機能、オンチップデバッグ機能は上記製品に内蔵されています。

M340 Group / M340 グループ

Part Number	ROM (Bytes)	SRAM (Bytes)	PSC SRAM (Bytes)	Maximum Operating Frequency (MHz)	DMA Controller (ch)	SSP (ch) (28)	UART/SIO (ch)	UART (ch)	I ² C (ch)	I ² C/SIO (ch)	TSP1 (ch) (32)	Variable Data Length Serial Interface (VSIO) (ch)	USB Embedded Host (Full-Speed) (ch)	USB (Full-Speed) (ch)	EtherMAC (ch)	12-Bit AD Converter (ch)	16-Bit ΔΣ AD Converter (ch)	10-Bit DA Converter (ch)	16-Bit Timer/Counter (ch)	High-Res. 16-Bit Timer/PPG Gen. (ch)	2-Phase Pulse Counter (PHC) (ch)	Enhanced 2-phase pulse counter (EPHC) (ch)	3-Phase PWM Generator (PMD) (ch)	Programmable Servo/Sequence controller (PSC) (ch)	Motor Driver (MCD) (ch)	Multi-Purpose Timer (MPT) (ch)	Incremental Encoder Input (ch)	Op Amp (ch)	Variable Gain Control Amp (ch)	Comparator (ch)	External Interrupt Pins (Pins)	CS/WAIT Controller (ch)	RTC (ch)	Trace Function	Oscillation Frequency Detector	I/O Port (Pins)	Operating Voltage Range (V)	Operating Temperature (°C)	Package
TMPM341FYXBG	256K	32K	54	4	1	5			2							15	2	10	2	4											12	2	Yes	Yes	86	1.65 to 3.6 (14)	-40 to 85	TFBGA113 (6 x 6 mm)	
TMPM342FYXBG		32K	4K	40	4	1	3	1	1		1						12 (31)	4 (31)	4	10	8	2			1	7.5			6	2	8		Yes	Yes	63	2.7 to 3.6 (15)	-40 to 85 (16)	VF BGA142 (7 x 7 mm)	
TMPM341FDXBG	512K	32K	54	4	1	5			2							15	2	10	2	4											12	2	Yes	Yes	86	1.65 to 3.6 (14)	-40 to 85	TFBGA113 (6 x 6 mm)	
TMPM343FDXBG		48K	32K	50	6	1	1	1	5								16	6	16	8	3	4	8					6	4	4	16		Yes	Yes	59	2.7 to 3.6 (30)		VF BGA162 (7 x 7 mm)	
TMPM343F10XBG	1024K	64K	32K	50	6	1	1	1	5							16	6	16	8	3	4	8						6	4	4	16		Yes	Yes	59	2.7 to 3.6 (30)	VF BGA162 (7 x 7 mm)		

Note (14),(15),(16),(28),(30),(31),(32): Please refer to page 14. / P.15 をご参照ください。

- ・ All products listed above incorporate a watchdog timer, a clock gear and an on-chip debug unit.
- ・ ウォッチドッグタイマ、クロックギア機能、オンチップデバッグ機能は上記製品に内蔵されています。

M370 Group / M370 グループ

Part Number	ROM (Bytes)	SRAM (Bytes)	Maximum Operating Frequency (MHz) (11)	DMA Controller (ch)	SSP (ch) (28)	UART/SIO (ch)	UART (ch)	I ² C (ch)	I ² C/SIO (ch)	CAN (ch)	USB Embedded Host (Full-Speed) (ch)	USB (Full-Speed) (ch)	EthernetMAC (ch)	10-Bit AD Converter (ch)	12-Bit AD Converter (ch)	10-Bit DA Converter (ch)	16-Bit Timer/Counter (ch)	High-Res. 16-Bit Timer/PPG Gen. (ch)	CEC (ch) (29)	Remote Control Preprocessor (ch)	Vector Engine (VE)	3-Phase PWM Generator (PMD) (ch)	Multi-Purpose Timer (MPT) (ch)	Incremental Encoder Input (ch)	Op Amp (ch)	Comparator (ch)	External Interrupt Pins (Pins)	CS/WAIT Controller (ch)	RTC (ch)	Oscillation Frequency Detector	I/O Port (Pins)	3-Phase Full-Wave Pre-Driver	Operating Voltage Range (V)	Operating Temperature (°C)	Package
TMPM375FSDMG	64K	4K	40		(12) 2			1						4	4						Yes	1		1	1		3			Yes	21	4.5 to 5.5	-40 to 105	SSOP30	
TMPM37AFSQG			40		1	1									5	4						Yes	1		1		3			Yes	13 ⁽³⁶⁾ Yes				-40 to 85
TMPM372FWUG	128K	6K	(a)80 (b)32			4								11	8						Yes	1		1		10			Yes	53	(a) -40 to 85 (b) -40 to 105		LQFP64 (10 x 10 mm)		
TMPM373FWDUG			(a)80 (b)32					3							7	8						Yes	1		1		8			Yes				37	LQFP48 (7 x 7 mm)
TMPM374FWUG			(a)80 (b)32					3							6	8						Yes	1		1		7			Yes				33	
TMPM370FYDFG	256K	10K	80			4								22	8						Yes	2		2	4	4	16		Yes	76	-40 to 85		QFP100 (14 x 20 mm)		
TMPM370FYFG			80					4							22	8						Yes	2		2	4	4	16		Yes				76	LQFP100 (14 x 14 mm)
TMPM376FDDFG	512K	32K	80			4		1						22	8						Yes	2		2		16		Yes	82	QFP100 (14 x 20 mm)					
TMPM376FDFG			80					4		1					22	8						Yes	2		2		16		Yes			82		LQFP100 (14 x 14 mm)	

Note (11),(12),(28),(29),(36): Please refer to page 14. / P.15をご参照ください。

- ・ All products listed above incorporate a watchdog timer, a clock gear, an on-chip debug unit, power-on reset and voltage detection circuits.
- ・ ウォッチドッグタイマ、クロックギア機能、オンチップデバッグ機能、パワーオンリセット、電圧検出回路は上記製品に内蔵されています。

TX03 Series / TX03シリーズ
M380 Group / M380グループ

Part Number	ROM (Bytes)		SRAM (Bytes)		Maximum Operating Frequency (MHz) ⁽¹¹⁾		DMA Controller (ch)		SSP (ch) ⁽²⁸⁾		UART/SIO (ch)		UART (ch)		I ² C (ch)		I ² C/SIO (ch)		CAN (ch)		USB Embedded Host (Full-Speed) (ch)		USB (Full-Speed) (ch)		EthernetMAC (ch)		10-Bit AD Converter (ch)		12-Bit AD Converter (ch)		10-Bit DA Converter (ch)		16-Bit Timer/Counter (ch)		High-Res. 16-Bit Timer/PPG Gen. (ch)		CEC (ch) ⁽²⁹⁾		Remote Control Preprocessor (ch)		Vector Engine (VE)		3-Phase PWM Generator (PMD) (ch)		Multi-Purpose Timer (MPT) (ch)		Incremental Encoder Input (ch)		Op Amp (ch)		Comparator (ch)		External Interrupt Pins (Pins)		CS/WAIT Controller (ch)		RTC (ch)		Oscillation Frequency Detector		I/O Port (Pins)		Operating Voltage Range (V)		Operating Temperature (°C)		Package	
	ROM (Bytes)	SRAM (Bytes)	Maximum Operating Frequency (MHz)	DMA Controller (ch)	SSP (ch)	UART/SIO (ch)	UART (ch)	I ² C (ch)	I ² C/SIO (ch)	CAN (ch)	USB Embedded Host (Full-Speed) (ch)	USB (Full-Speed) (ch)	EthernetMAC (ch)	10-Bit AD Converter (ch)	12-Bit AD Converter (ch)	10-Bit DA Converter (ch)	16-Bit Timer/Counter (ch)	High-Res. 16-Bit Timer/PPG Gen. (ch)	CEC (ch)	Remote Control Preprocessor (ch)	Vector Engine (VE)	3-Phase PWM Generator (PMD) (ch)	Multi-Purpose Timer (MPT) (ch)	Incremental Encoder Input (ch)	Op Amp (ch)	Comparator (ch)	External Interrupt Pins (Pins)	CS/WAIT Controller (ch)	RTC (ch)	Oscillation Frequency Detector	I/O Port (Pins)	Operating Voltage Range (V)	Operating Temperature (°C)	Package																																		
TMPM383FSEFG	64K	8K	40	1	2	1	1							10	8				1							8	1	Yes	48	3.9 to 5.5	-40 to 85	QFP64 (14 x 14 mm)																																				
TMPM383FSUG			40	1	2	1	1								10	8				1							8	1	Yes			48	LQFP64 (10 x 10 mm)																																			
TMPM380FWDFG	128K	12K	40	2	2	5		2						18	8				1		⁽¹⁰⁾ 2	3	2			16	1	Yes	84	4.0 to 5.5	-40 to 85	QFP100 (14 x 20 mm)																																				
TMPM380FWFG			40	2	2	5		2							18	8				1		⁽¹⁰⁾ 2	3	2			16	1	Yes			84	LQFP100 (14 x 14 mm)																																			
TMPM381FWDFG	128K	10K	40	1	3	1		1						18	8				1							16	1	Yes	84	3.9 to 5.5	-40 to 85	QFP100 (14 x 20 mm)																																				
TMPM381FWFG			40	1	3	1		1							18	8				1							16	1	Yes			84	LQFP100 (14 x 14 mm)																																			
TMPM383FWEFG		10K	40	1	2	1		1						10	8				1							8	1	Yes	48			QFP64 (14 x 14 mm)																																				
TMPM383FWUG			40	1	2	1		1							10	8				1							8	1	Yes			48	LQFP64 (10 x 10 mm)																																			
TMPM380FYDFG	256K	16K	40	2	2	5		2						18	8				1		⁽¹⁰⁾ 2	3	2			16	1	Yes	84	4.0 to 5.5	-40 to 85	QFP100 (14 x 20 mm)																																				
TMPM380FYFG			40	2	2	5		2							18	8				1		⁽¹⁰⁾ 2	3	2			16	1	Yes			84	LQFP100 (14 x 14 mm)																																			
TMPM380FDFG	512K	32K	40	2	2	5		2						18	8				1		⁽¹⁰⁾ 2	3	2			16	1	Yes	84	4.0 to 5.5	-40 to 85	LQFP100 (14 x 14 mm)																																				
TMPM384FDFG			40	2	2	5		2							22	12				1		⁽¹⁰⁾ 2	4	2			16	1	Yes			121	LQFP144 (20 x 20 mm)																																			

Note (10),(11),(28),(29): Please refer to page 14. / P.15をご参照ください。

- All products listed above incorporate a watchdog timer, a clock gear, an on-chip debug unit, power-on reset and voltage detection circuits.
- ウォッチドッグタイマ、クロックギア機能、オンチップデバッグ機能、パワーオンリセット、電圧検出回路は上記製品に内蔵されています。

M390 Group / M390グループ

Part Number	ROM (Bytes)		SRAM (Bytes)		Maximum Operating Frequency (MHz) ⁽¹¹⁾		DMA Controller (ch)		SSP (ch) ⁽²⁸⁾		UART/SIO (ch)		UART (ch)		I ² C (ch)		I ² C/SIO (ch)		CAN (ch)		USB Embedded Host (Full-Speed) (ch)		USB (Full-Speed) (ch)		EthernetMAC (ch)		10-Bit AD Converter (ch)		12-Bit AD Converter (ch)		10-Bit DA Converter (ch)		16-Bit Timer/Counter (ch)		High-Res. 16-Bit Timer/PPG Gen. (ch)		CEC (ch) ⁽²⁹⁾		Remote Control Preprocessor (ch)		Vector Engine (VE)		3-Phase PWM Generator (PMD) (ch)		Multi-Purpose Timer (MPT) (ch)		Incremental Encoder Input (ch)		Op Amp (ch)		Comparator (ch)		External Interrupt Pins (Pins)		CS/WAIT Controller (ch)		RTC (ch)		Oscillation Frequency Detector		I/O Port (Pins)		Operating Voltage Range (V)		Operating Temperature (°C)		Package	
	ROM (Bytes)	SRAM (Bytes)	Maximum Operating Frequency (MHz)	DMA Controller (ch)	SSP (ch)	UART/SIO (ch)	UART (ch)	I ² C (ch)	I ² C/SIO (ch)	CAN (ch)	USB Embedded Host (Full-Speed) (ch)	USB (Full-Speed) (ch)	EthernetMAC (ch)	10-Bit AD Converter (ch)	12-Bit AD Converter (ch)	10-Bit DA Converter (ch)	16-Bit Timer/Counter (ch)	High-Res. 16-Bit Timer/PPG Gen. (ch)	CEC (ch)	Remote Control Preprocessor (ch)	Vector Engine (VE)	3-Phase PWM Generator (PMD) (ch)	Multi-Purpose Timer (MPT) (ch)	Incremental Encoder Input (ch)	Op Amp (ch)	Comparator (ch)	External Interrupt Pins (Pins)	CS/WAIT Controller (ch)	RTC (ch)	Oscillation Frequency Detector	I/O Port (Pins)	Operating Voltage Range (V)	Operating Temperature (°C)	Package																																		
TMPM390FWFG **	128K	8K	20	1	3	1	1							12		10	1	2								8	1	Yes	74	1.7 to 3.6	-40 to 85	LQFP100 (14 x 14 mm)																																				
TMPM395FWAXBG			20	4	3	1	1								12		10	1	2								11	1	Yes			91	TFBGA120 (6 x 6 mm)																																			

Note (11),(28),(29): Please refer to page 14. / P.15をご参照ください。

** : Under development / 開発中

- All products listed above incorporate a watchdog timer, a clock gear, an on-chip debug unit, power-on reset and voltage detection circuits.
- ウォッチドッグタイマ、クロックギア機能、オンチップデバッグ機能、パワーオンリセット、電圧検出回路は上記製品に内蔵されています。

TX04 Series / TX04 シリーズ

M440 Group / M440 グループ

Part Number	ROM (Bytes)	SRAM (Bytes)	Maximum Operating Frequency (MHz)	DMA Controller (ch)	SSP (ch) ⁽²⁸⁾	UART/SIO (ch)	I ² C (ch)	I ² C/SIO (ch)	CAN (ch)	Enhanced Serial I/O (ESIO) (ch)	USB Embedded Host (Full-Speed) (ch)	USB (Full-Speed) (ch)	EtherMAC (ch)	10-Bit AD Converter (ch)	12-Bit AD Converter (ch)	10-Bit DA Converter (ch)	16-Bit Timer/Counter (ch)	32-Bit Timer (unit)	High-Res. 16-Bit Timer/PPG Gen. (ch)	2-Phase Pulse Counter (PHC) (ch)	Enhanced 2-phase pulse counter (EPHC) (ch)	Programmable Servo/Sequence controller (PSC) (ch)	CEC (ch) ⁽²⁹⁾	Remote Control Preprocessor (ch)	Multi-Purpose Timer (MPT) (ch)	External Interrupt Pins (Pins)	Key-On Wake-Up (KWUP) (ch)	Key Matrix Scan (KSCAN) (Column x Row)	CSWAIT Controller (ch)	RTC (ch)	Trace Function	Oscillation Frequency Detector	Power-On Reset	Low Voltage Detection Circuit (LVD)	I/O Port (Pins)	Operating Voltage Range (V)	Operating Temperature (°C)	Package
TMPM440FEXBG	768K	80K	100	6	6	2	1			3				20	2	20	20	1	4	2	1	1			24	40	8 x 8	2	1	Yes	Yes	Yes	228	2.7 to 3.6	-40 to 85	VFBGA289 (11 x 11 mm)		
TMPM440F10XBG	1024K	80K	100	6	6	2	1			3				20	2	20	20	1	4	2	1	1			24	40	8 x 8	2	1	Yes	Yes	Yes	228	2.7 to 3.6	-40 to 85	VFBGA289 (11 x 11 mm)		

Note (28),(29): Please refer to page 14. / P.15 をご参照ください。

M460 Group / M460 グループ

Part Number	ROM (Bytes)	SRAM (Bytes)	Maximum Operating Frequency (MHz)	DMA Controller (ch)	SSP (ch) ⁽²⁸⁾	UART/SIO (ch)	I ² C (ch)	I ² C/SIO (ch)	CAN (ch)	Enhanced Serial I/O (ESIO) (ch)	USB Embedded Host (Full-Speed) (ch)	USB (Full-Speed) (ch)	EtherMAC (ch)	10-Bit AD Converter (ch)	12-Bit AD Converter (ch)	10-Bit DA Converter (ch)	16-Bit Timer/Counter (ch)	32-Bit Timer (unit)	AES Processor (AES) (ch)	Secure Hash Algorithm Processor (SHA) (ch)	Entropy Seed Generator (ESG) (ch)	Multiple Length Arithmetic Coprocessor (MLA) (ch)	SLC NAND Flash Controller (ch)	CEC (ch) ⁽²⁹⁾	Remote Control Preprocessor (ch)	Multi-Purpose Timer (MPT) (ch)	External Interrupt Pins (Pins)	Key-On Wake-Up (KWUP) (ch)	Key Matrix Scan (KSCAN) (Column x Row)	CSWAIT Controller (ch)	RTC (ch)	Trace Function	Oscillation Frequency Detector	Power-On Reset	Low Voltage Detection Circuit (LVD)	I/O Port (Pins)	Operating Voltage Range (V)	Operating Temperature (°C)	Package
TMPM461F10FG		193K	120	32	3	6	2	5						20		16									1	1	2	⁽³⁴⁾ 16		4	1	Yes	Yes	Yes	111	2.7 to 3.6	-40 to 85	LQFP144 (20 x 20 mm)	
TMPM462F10FG	1024K		120	32	3	10	2	5						20		16									1	2	⁽³⁴⁾ 2	16		4	1	Yes	Yes	Yes	139			LQFP176 (20 x 20 mm)	
TMPM46BF10FG		514K	120	32	3	4	2	3						8		8			1	1	1	1	1			⁽³⁴⁾ 4	16		4	1	Yes		Yes	72	LQFP100 (14 x 14 mm)				
TMPM461F15FG		193K	120	32	3	6	2	5						20		16									1	1	⁽³⁴⁾ 2	16		4	1	Yes	Yes	Yes	111			LQFP144 (20 x 20 mm)	
TMPM462F15FG	1536K		120	32	3	10	2	5						20		16									1	2	⁽³⁴⁾ 2	16		4	1	Yes	Yes	Yes	139			LQFP176 (20 x 20 mm)	

Note (28),(29),(34): Please refer to page 14. / P.15 をご参照ください。

TX04 Series / TX04 シリーズ
M470 Group / M470 グループ

Part Number	ROM (Bytes)		SRAM (Bytes)		Maximum Operating Frequency (MHz) (11)		DMA Controller (ch)	SSP (ch) (28)	UART/SIO (ch)	UART (ch)	I ² C (ch)	I ² C/SIO (ch)	CAN (ch)	USB Embedded Host (Full-Speed) (ch)	USB (Full-Speed) (ch)	EtherMAC (ch)	10-Bit AD Converter (ch)	12-Bit AD Converter (ch)	10-Bit DA Converter (ch)	16-Bit Timer/Counter (ch)	High-Res. 16-Bit Timer/PPG Gen. (ch)	CEC (ch) (29)	Remote Control Preprocessor (ch)	Advanced Vector Engine (A-VE) (ch)	3-Phase PWM Generator (PMD) (ch)	Multi-Purpose Timer (MPT) (ch)	Advanced Encoder (A-ENC) (ch)	Op Amp (ch)	Comparator (ch)	External Interrupt Pins (Pins)	CS/WAIT Controller (ch)	RTC (ch)	Oscillation Frequency Detector	I/O Port (Pins)	Operating Voltage Range (V)	Operating Temperature (°C)	Package
	256K	18K	120	32	4	1																															
TMPM470FYFG	256K	18K	120	32	4	1											20	10					2	2	2			16		Yes	79	4.5 to 5.5	-40 to 85	LQFP100 (14 x 14 mm)			
TMPM475FYFG			120	32	4	1	1											20	10					2	2	2			16		Yes				79		
TMPM470FZFG	384K	34K	120	32	4	1											20	10					2	2	2			16		Yes	79						
TMPM475FZFG			120	32	4	1	1											20	10					2	2	2			16		Yes				79		
TMPM470FDFG	512K	34K	120	32	4	1											20	10					2	2	2			16		Yes	79						
TMPM475FDFG			120	32	4	1	1											20	10					2	2	2			16		Yes				79		

Note (11),(28),(29): Please refer to page 14. / P.15 をご参照ください。

- ・ All products listed above incorporate a watchdog timer, a clock gear, an on-chip debug unit, power-on reset and voltage detection circuits.
- ・ ウォッチドッグタイマ、クロックギア機能、オンチップデバッグ機能、パワーオンリセット、電圧検出回路は上記製品に内蔵されています。

32-Bit Microcontrollers for Automotive / 車載用32ビットマイクロコントローラ

TX03 Series / TX03 シリーズ

Part Number	ROM (Bytes)	SRAM (Bytes)	Maximum Operating Frequency (MHz)	CAN (ch)	DMA Controller (ch)	ESEI (ch)	UART/SIO (ch)	12-Bit AD Converter (ch)	Timer/Compare (32 bit) (ch)	Timer/Capture (32 bit) (ch)	PWM (24 bit) (ch)	Vector Engine (VE)	Programmable Motor Drive (PMD) (ch)	Resolver Digital Converter (RDC)	Watchdog Timer	On-Chip Debug Unit	Trace Function	I/O Port (Pins)	Supply Voltage (V)	Operating Temperature (°C)	Package
TMPM350FDTFG	512K	48K	88	2	32	1	2	20	3	7	6		1		Yes	Yes	Yes	43	⁽²³⁾	-40 to 105	LQFP100 (14 x 14 mm)
TMPM351F10TFG	1024K	64K	144	2	32	1	2	20	3	7	6		1		Yes	Yes	Yes	43	⁽³⁵⁾	-40 to 105	
TMPM358FDTFG ⁽²⁵⁾	512K	80K	40	3	32	3	2	20	5	3	3				Yes	Yes	Yes	35	4.5 to 5.5	-40 to 105	
TMPM354F10TAFG	1024K	64K	96	3	64	2	3	21	5	6	4	Yes	1	1	Yes	Yes	Yes	54	⁽²⁴⁾	-40 to 125	HQFP144 (20 x 20 mm)

Note (23),(24),(25),(35): Please refer to page 14. / P.15 をご参照ください。

Reference

- Note (1): Configurable as UART or SIO. Also, selectable from I²C and SIO.
One SIO channel can be used simultaneously. As for the TMP89FS60, up to two SIO channels can be used simultaneously.
- (2): The on-chip debug unit is available with the flash versions, but not with the mask ROM versions.
- (3): Minimum instruction execution times (a) to (c) correspond to (a) to (c) of both supply voltage and operating temperature.
- (4): The minimum instruction execution time in Low-Speed mode is 122 μ s (at 32.768 kHz).
- (5): The erase/program power supply voltage is 3.0 to 3.6 V.
- (6): Two ports are reserved for high-speed oscillator pins and cannot be used as I/O ports.
- (7): The AD conversion accuracy differs between the flash and mask ROM versions. For details, see the datasheet.
- (8): Dual power supplies: 1.4 V to 1.6 V for internal circuitry, 3.0 V to 3.6 V for input/output interface.
- (9): Minimum instruction execution times (a) and (b) correspond to (a) and (b) of operating temperature.
- (10): Either the Programmable Motor Driver (PMD) or the Multi-Purpose Timer (MPT) is selectable.
- (11): Maximum Operating Frequency (a) and (b) correspond to Operating Temperatures (a) and (b).
- (12): One channel is configurable only as UART.
- (13): 3.0 to 3.45 V when USB is used.
- (14): When the supply voltage is less than 2.7 V, part of the peripheral blocks (the external bus interface and the SSP) can be used.
- (15): MCD analog supply voltage: 3.1 V to 3.5 V
MCD motor supply voltage: 2.5 V to 5.5 V
- (16): The operating temperature of the Motor Control Driver (MCD) and the operating temperature of the D/A converter of the MCU are between -25 and 85°C .
When the operating temperature is between -40 and -25°C , the MCD is used in stand-by state, and the D/A converter of the MCU is used in stop state.
- (17): 48 MHz when USB is used.
- (18): The following three power supplies are available:
- (i) For general ports, and A/D converter: 3.0 V to 3.6 V
 - (ii) For USB Embedded Host: 3.15 V to 3.45 V
 - (iii) For internal circuitry: 1.1 V to 1.3 V
- (19): The on-chip ROM can be programmed only once and cannot be reprogrammed.
- (20): Configurable as SIO or UART.
- (21): Configurable as I²C or SIO. Up to two SIO channels can be used simultaneously.
- (22): Configurable as SEI or UART.
- (23): The following two power supplies are available:
- (i) For internal circuitry: 1.4 V to 1.65 V
 - (ii) For general ports and A/D converter: 4.5 V to 5.5 V
- (24): The following two power supplies are available:
- (i) For internal circuitry: 1.35 V to 1.65 V
 - (ii) For general ports and A/D converter: 4.5 V to 5.5 V
- (25): Low-power modes are available.
- (26): SEI: Serial Expansion Interface
- (27): SPI: Serial Peripheral Interface
- (28): SSP: Synchronous Serial Port
- (29): CEC: Consumer Electronics Control
- (30): MCD motor supply voltage: 2.5 V to 5.5 V
- (31): Built-in 12-bit SAR type AD converter: 2 units/12 (8+4) channels.
Built-in 16-bit $\Delta\Sigma$ type AD converter: 1 unit/4 channels.
- (32): TSPi: Toshiba Serial Peripheral Interface
- (33): It is the software IP.
- (34): 16-bit timer mode and IGBT mode are available.
- (35): The following two power supplies are available:
- (i) For internal circuitry: 1.08 V to 1.32 V
 - (ii) For general ports and A/D converter: 4.5 V to 5.5 V
- (36): Supply voltage $V_M = 6$ V to 32 V, Pre-driver is P-ch/N-ch configuration.
- (37): Debug interface for RAMScope of Yokogawa Digital Computer Corporation.
- (38): Became 32-Bit Timer/Counter by linking two 16-Bit Timer/Counter.
- (39): 2.9 V to 3.6 V when 24-Bit $\Delta\Sigma$ AD Converter is used.

参照

- Note (1): UARTまたはSIOのいずれか一方を選択可能です。I²CまたはSIOのいずれか一方を選択可能です。同時に使用できるSIOは1chとなります。TMP89FS60が、同時に使用できるSIOは2chとなります。
- (2): オンチップ機能はFlash版だけの対応です。
- (3): 最小命令実行時間の(a)–(c)は、それぞれ電源電圧、動作温度の(a)–(c)に対応しています。
- (4): 低速動作モードの最小命令実行時間は122 μs (32.768 kHz時)です。
- (5): 消去/書き込み時の電源電圧は3.0 to 3.6 Vとなります。
- (6): 2端子は高周波発振端子として使われるため、入出力ポートとして使用できません。
- (7): Flash品とMask品では、AD変換精度の保証値が異なります。詳細につきましては、テクニカルデータシートをご参照ください。
- (8): 電源電圧は、内部回路用: 1.4 V to 1.6 V、外部IO用: 3.0 V to 3.6 Vの2電源です。
- (9): 最小命令実行時間の(a)–(b)は、それぞれ動作温度の(a)–(b)に対応しています。
- (10): 3相PWM出力(PMD)は、多目的タイマ(MPT)と兼用です。
- (11): 最大動作周波数の(a)–(b)は、それぞれの動作温度の(a)–(b)に対応しています。
- (12): 1chはUARTだけです。
- (13): USB使用時は、3.0 V to 3.45 Vとなります。
- (14): 電圧範囲が2.7 V未満の場合、一部の周辺機能(外部バスインタフェース、SSP)が動作可能です。
- (15): MCD部アナログ電源電圧: 3.1 V to 3.5 V
MCD部モータ電源電圧: 2.5 V to 5.5 V
- (16): Motor Control Driver (MCD)部のファンクション動作温度およびMCU部のD/Aコンバータ動作温度は–25 ~ 85°Cの範囲です。
–40 ~ –25°Cの範囲ではMCD部はスタンバイ状態、MCU部のD/Aコンバータは停止状態でのご使用となります。
- (17): USB Embedded Host使用時は、48 MHzとなります。
- (18): 電源電圧は以下の3電源です。
- (i) I/O用, ADコンバータ用: 3.0 V to 3.6 V
(ii) USB Embedded Host用: 3.15 V to 3.45 V
(iii) 内部回路用: 1.1 V to 1.3 V
- (19): 書き込みは1回のみです。書き換えはできません。
- (20): UARTまたはSIOのいずれか一方を選択可能です。
- (21): I²CまたはSIOのいずれか一方を選択可能です。また同時に使用できるSIOは2chとなります。
- (22): SEIまたはUARTのいずれか一方を選択可能です。
- (23): 電源電圧は以下の2電源です。
- (i) 内部回路用: 1.4 V to 1.65 V
(ii) I/O用, ADコンバータ用: 4.5 V to 5.5 V
- (24): 電源電圧は以下の2電源です。
- (i) 内部回路用: 1.35 V to 1.65 V
(ii) I/O用, ADコンバータ用: 4.5 V to 5.5 V
- (25): 低消費モードを内蔵しています。
- (26): SEI : シリアル拡張インタフェース
- (27): SPI : シリアルバス的一种
- (28): SSP: 同期式シリアルインタフェース
- (29): CEC: Consumer Electronics Control
- (30): MCD部モータ電源電圧: 2.5 V to 5.5 V
- (31): SAR型12ビットADコンバータが2ユニット/8+4チャンネル、 $\Delta\Sigma$ 型16ビットADコンバータが1ユニット/4チャンネル内蔵されています。
- (32): TSPi: 東芝シリアルペリフェラルインタフェース
- (33): ソフトウェアIPとなります。
- (34): IGBT制御と16ビットタイマが内蔵されています。
- (35): 電源電圧は以下の2電源です。
- (i) 内部回路用: 1.08 V to 1.32 V
(ii) I/O用, ADコンバータ用: 4.5 V to 5.5 V
- (36): 電源電圧 $V_M = 6 V$ to 32 V。ブリドライバはPch/Nch構成です。
- (37): 横河デジタルコンピュータ株式会社製のRAMScopeに対応するデバッグインタフェースです。
- (38): 2つの16ビットタイマ/カウンタをつなげることで、32ビットタイマ/カウンタになります。
- (39): 24ビット $\Delta\Sigma$ ADコンバータ使用時は、2.9 V ~ 3.6 Vになります。

RESTRICTIONS ON PRODUCT USE

Toshiba Corporation and its subsidiaries and affiliates are collectively referred to as "TOSHIBA". Hardware, software and systems described in this document are collectively referred to as "Product".

- ▶ TOSHIBA reserves the right to make changes to the information in this document and related Product without notice.
- ▶ This document and any information herein may not be reproduced without prior written permission from TOSHIBA. Even with TOSHIBA's written permission, reproduction is permissible only if reproduction is without alteration/omission.
- ▶ Though TOSHIBA works continually to improve Product's quality and reliability, Product can malfunction or fail. Customers are responsible for complying with safety standards and for providing adequate designs and safeguards for their hardware, software and systems which minimize risk and avoid situations in which a malfunction or failure of Product could cause loss of human life, bodily injury or damage to property, including data loss or corruption. Before customers use the Product, create designs including the Product, or incorporate the Product into their own applications, customers must also refer to and comply with (a) the latest versions of all relevant TOSHIBA information, including without limitation, this document, the specifications, the data sheets and application notes for Product and the precautions and conditions set forth in the "TOSHIBA Semiconductor Reliability Handbook" and (b) the instructions for the application with which the Product will be used with or for. Customers are solely responsible for all aspects of their own product design or applications, including but not limited to (a) determining the appropriateness of the use of this Product in such design or applications; (b) evaluating and determining the applicability of any information contained in this document, or in charts, diagrams, programs, algorithms, sample application circuits, or any other referenced documents; and (c) validating all operating parameters for such designs and applications. **TOSHIBA ASSUMES NO LIABILITY FOR CUSTOMERS' PRODUCT DESIGN OR APPLICATIONS.**
- ▶ **PRODUCT IS NEITHER INTENDED NOR WARRANTED FOR USE IN EQUIPMENTS OR SYSTEMS THAT REQUIRE EXTRAORDINARILY HIGH LEVELS OF QUALITY AND/OR RELIABILITY, AND/OR A MALFUNCTION OR FAILURE OF WHICH MAY CAUSE LOSS OF HUMAN LIFE, BODILY INJURY, SERIOUS PROPERTY DAMAGE AND/OR SERIOUS PUBLIC IMPACT ("UNINTENDED USE").** Except for specific applications as expressly stated in this document, Unintended Use includes, without limitation, equipment used in nuclear facilities, equipment used in the aerospace industry, medical equipment, equipment used for automobiles, trains, ships and other transportation, traffic signaling equipment, equipment used to control combustions or explosions, safety devices, elevators and escalators, devices related to electric power, and equipment used in finance-related fields. **IF YOU USE PRODUCT FOR UNINTENDED USE, TOSHIBA ASSUMES NO LIABILITY FOR PRODUCT.** For details, please contact your TOSHIBA sales representative.
- ▶ Do not disassemble, analyze, reverse-engineer, alter, modify, translate or copy Product, whether in whole or in part.
- ▶ Product shall not be used for or incorporated into any products or systems whose manufacture, use, or sale is prohibited under any applicable laws or regulations.
- ▶ The information contained herein is presented only as guidance for Product use. No responsibility is assumed by TOSHIBA for any infringement of patents or any other intellectual property rights of third parties that may result from the use of Product. No license to any intellectual property right is granted by this document, whether express or implied, by estoppel or otherwise.
- ▶ **ABSENT A WRITTEN SIGNED AGREEMENT, EXCEPT AS PROVIDED IN THE RELEVANT TERMS AND CONDITIONS OF SALE FOR PRODUCT, AND TO THE MAXIMUM EXTENT ALLOWABLE BY LAW, TOSHIBA (1) ASSUMES NO LIABILITY WHATSOEVER, INCLUDING WITHOUT LIMITATION, INDIRECT, CONSEQUENTIAL, SPECIAL, OR INCIDENTAL DAMAGES OR LOSS, INCLUDING WITHOUT LIMITATION, LOSS OF PROFITS, LOSS OF OPPORTUNITIES, BUSINESS INTERRUPTION AND LOSS OF DATA, AND (2) DISCLAIMS ANY AND ALL EXPRESS OR IMPLIED WARRANTIES AND CONDITIONS RELATED TO SALE, USE OF PRODUCT, OR INFORMATION, INCLUDING WARRANTIES OR CONDITIONS OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, ACCURACY OF INFORMATION, OR NONINFRINGEMENT.**
- ▶ Do not use or otherwise make available Product or related software or technology for any military purposes, including without limitation, for the design, development, use, stockpiling or manufacturing of nuclear, chemical, or biological weapons or missile technology products (mass destruction weapons). Product and related software and technology may be controlled under the applicable export laws and regulations including, without limitation, the Japanese Foreign Exchange and Foreign Trade Law and the U.S. Export Administration Regulations. Export and re-export of Product or related software or technology are strictly prohibited except in compliance with all applicable export laws and regulations.
- ▶ Product may include products subject to foreign exchange and foreign trade control laws.
- ▶ Please contact your TOSHIBA sales representative for details as to environmental matters such as the RoHS compatibility of Product. Please use Product in compliance with all applicable laws and regulations that regulate the inclusion or use of controlled substances, including without limitation, the EU RoHS Directive. **TOSHIBA ASSUMES NO LIABILITY FOR DAMAGES OR LOSSES OCCURRING AS A RESULT OF NONCOMPLIANCE WITH APPLICABLE LAWS AND REGULATIONS.**

製品取り扱い上のお願い

株式会社東芝およびその子会社ならびに関係会社を以下「当社」といいます。本資料に掲載されているハードウェア、ソフトウェアおよびシステムを以下「本製品」といいます。

- ▶ 本製品に関する情報等、本資料の掲載内容は、技術の進歩などにより予告なしに変更されることがあります。
- ▶ 文書による当社の事前の承諾なしに本資料の転載複製を禁じます。また、文書による当社の事前の承諾を得て本資料を転載複製する場合でも、記載内容に一切変更を加えたり、削除したりしないでください。
- ▶ 当社は品質、信頼性の向上に努めていますが、半導体・ストレージ製品は一般に誤作動または故障する場合があります。本製品をご使用頂く場合は、本製品の誤作動や故障により生命・身体・財産が侵害されることのないように、お客様の責任において、お客様のハードウェア・ソフトウェア・システムに必要な安全設計を行うことをお願いします。なお、設計および使用に際しては、本製品に関する最新の情報(本資料、仕様書、データシート、アプリケーションノート、半導体信頼性ハンドブックなど)および本製品が使用される機器の取扱説明書、操作説明書などをご確認の上、これに従ってください。また、上記資料などに記載の製品データ、図、表などに示す技術的な内容、プログラム、アルゴリズムその他応用回路例などの情報を使用する場合は、お客様の製品単独およびシステム全体で十分に評価し、お客様の責任において適用可否を判断してください。
- ▶ 本製品は、特別に高い品質・信頼性が要求され、またはその故障や誤作動が生命・身体に危害を及ぼす恐れ、膨大な財産損害を引き起こす恐れ、もしくは社会に深刻な影響を及ぼす恐れのある機器(以下「特定用途」という)に使用されることは意図されていませんし、保証もされていません。特定用途には原子力関連機器、航空・宇宙機器、医療機器、車載・輸送機器、列車・船舶機器、交通信号機器、燃焼・爆発制御機器、各種安全関連機器、昇降機器、電力機器、金融関連機器などが含まれますが、本資料に個別に記載する用途は除きます。特定用途に使用された場合には、当社は一切の責任を負いません。なお、詳細は当社営業窓口までお問い合わせください。
- ▶ 本製品を分解、解析、リバースエンジニアリング、改造、改変、翻案、複製等しないでください。
- ▶ 本製品を、国内外の法令、規則及び命令により、製造、使用、販売を禁止されている製品に使用することはできません。
- ▶ 本資料に掲載してある技術情報は、製品の代表的動作・応用を説明するためのもので、その使用に際して当社及び第三者の知的財産権その他の権利に対する保証または実施権の許諾を行うものではありません。
- ▶ 別途、書面による契約またはお客様と当社が合意した仕様書がない限り、当社は、本製品および技術情報に関して、明示的にも黙示的にも一切の保証(機能動作の保証、商品性の保証、特定目的への合致の保証、情報の正確性の保証、第三者の権利の非侵害保証を含む)がこれに限らない。)をしておりません。
- ▶ 本製品、または本資料に掲載されている技術情報を、大量破壊兵器の開発等の目的、軍事利用の目的、あるいはその他軍事用途の目的で使用しないでください。また、輸出に際しては、「外国為替及び外国貿易法」、「米国輸出管理規則」等、適用ある輸出関連法令を遵守し、それらの定めるところにより必要な手続を行ってください。
- ▶ 本製品には、外国為替及び外国貿易法により、輸出または海外への提供が規制されているものがあります。
- ▶ 本製品のRoHS適合性など、詳細につきましては製品個別に必ず当社営業窓口までお問い合わせください。本製品のご使用に際しては、特定の物質の含有・使用を規制するRoHS指令等、適用ある環境関連法令を十分調査の上、かかる法令に適合するようご使用ください。お客様がかかる法令を遵守しないことにより生じた損害に関して、当社は一切の責任を負いかねます。

【お問い合わせ先】

TOSHIBA

© 2017 TOSHIBA ELECTRONIC DEVICES & STORAGE CORPORATION

Previous edition: BCA0085G

TOSHIBA ELECTRONIC DEVICES & STORAGE CORPORATION

東芝デバイス&ストレージ株式会社

https://toshiba.semicon-storage.com/