

www.tripplite.com



# 4-Port Desktop KVM Switch (USB)

MODEL NUMBER: B006-VU4-R







### Description

Tripp Lite's 4-port Desktop USB KVM Switch is the optimal solution for controlling up to 4 USB computers from one VGA monitor and USB keyboard/mouse. Manually switch between connected computers using pushbuttons or hotkey controls; or, monitor connected computers automatically via Auto Scan Mode. The B006-VU4-R is operating system independent, and works with all computers that have an available VGA and USB port. It supports video resolutions up to 2048 x 1536, and features a compact design that does not require software or complicated set-up procedures. Constructed of heavy-duty steel housing. Order P758 Cables separately.

#### **Features**

- Control up to 4 USB computers from a single VGA monitor and USB keyboard/mouse
- Order P758 Cables separately
- Port LEDs illuminate Light Orange to indicate a computer is connected, and Bright Orange to indicate it is the selected port
- Supports video resolutions up to 2048 x 1536, DDC2B
- No software or complicated set-up procedures required
- Manually switch between connected computers via front panel pushbuttons or hotkey commands
- · Automatically monitor connected computers via Auto Scan Mode
- Compatible with all major operating systems
- · Compatibile with most mice; including scroll mice
- Constructed of heavy-duty steel housing

### Highlights

- Control up to 4 USB computers from a single VGA monitor and USB keyboard/mouse
- Switch between connected computers via pushbuttons or hotkey commands
- Auto Scan Mode allows monitoring of connected computers without manually switching between them
- Compatible with all major operating systems
- Supports video resolutions up to 2048 x 1536, DDC2B

### **Applications**

 Small Office/Home Office (SOHO). Control up to 4 USB computers from a single VGA monitor and USB keyboard/mouse.

### Package Includes

- B006-VU4-R 4-port USB KVM Switch
- External Power Supply (Input: 100-230V, 50/60Hz, 0.5A / Output: 5.3V, 190mA)
- Owner's manual

## **Specifications**

OVERVIEW	
Users	1
Console	No





Max CPU	4
PHYSICAL	
Shipping Dimensions (hwd / in.)	3.5 x 9.8 x 8.7
Shipping Dimensions (hwd / cm)	8.89 x 24.89 x 22.10
Shipping Weight (lbs.)	2.2
Shipping Weight (kg)	1.00
Unit Dimensions (hwd / in.)	1.7 x 7.9 x 2.9
Unit Dimensions (hwd / cm)	4.32 x 20.07 x 7.37
Unit Weight (lbs.)	1.5
Unit Weight (kg)	0.68
LCD Monitor (in.)	N/A
LCD Monitor (cm)	Not Applicable
COMMUNICATIONS	
Port Control	Push Buttons, Hotkeys
IP Remote Access	No
CONNECTIONS	
Ports	4
Other Ports	None
Computer/Server Ports - Port 1	(x4) HD15 Male
Computer/Server Ports - Port 2	(x4) USB B Female
PC/Server Connections	USB
Local Console Ports - Port 1	HD15 Female
Local Console Ports - Port 2	(x2) USB A Female
SPECIAL FEATURES	
Cat5 KVM Switch	No
CERTIFICATIONS	
NIAP-Certified Secure	No
WARRANTY	



Tripp Lite
1111 W. 35th Street
Chicago, IL 60609 USA
Telephone: 773.869.1234
www.tripplite.com

Product Warranty Period (Worldwide)

1-year limited warranty

© 2015 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies: http://www.tripplite.com/products/product-certification-agencies