

# 1-ft. Active HDMI Video with Audio Signal Extender Equalizer with Audio 1920x1200,1080p at 24Hz (HDMI M/F)

MODEL NUMBER: B123-001



#### Description

Tripp Lite's B123-001 HDMI Signal Extender increases the distance a 1080p @ 24Hz (or 1920 x 1200) signal can be transmitted beyond the recommended 16 ft. (5 m.). It supports computer video resolutions up to 1920 x 1200, and HD resolutions up to 1080p @ 24Hz, at a maximum distance of 150 ft. from the source. Use P568-Series HDMI cables in most applications. When extending a 1080p @ 24Hz (or 1920 x 1200) signal more than 75 ft., use cable made with 24Awg wiring, such as the P568-100-HD. (Lengths over 100 ft. are available from Tripp Lite as a custom order) 24Awg HDMI cable is also needed when extending a 3D signal more than 50 ft.. A 3D signal can be extended up to 125 ft. using 24Awg HDMI cable. Simply connect the longer cable between the source and the B123-001, and then connect the built-in cable to the monitor. Software or drivers are not required. HDCP compliant. Compatible with the Federal Trade Agreements Act (TAA) for GSA Schedule purchases.

#### **Highlights**

- Extend a 1080p @ 24Hz (or 1920 x 1200) HDMI signal up to 150 ft.
   from the source
- When extending a 1080p @
  24Hz (or 1920 x 1200) signal more than 75 ft., use cable made with 24Awg wiring, such as the P568-100-HD
- 24Awg HDMI cable is also needed when extending a 3D signal more than 50 ft.. A 3D signal can be extended up to 125 ft. using 24Awg HDMI cable
- Supports DTS-HD, Dolby True HD and 7.1 Channel Surround Sound Audio
- Compliant with the Federal Trade Agreements Act (TAA) for GSA Schedule purchases

#### **Applications**

 When an HDTV display is located a long distance from the video source.

#### **Package Includes**

 HDMI Active Extender Cable, M/F, 1 ft.

#### **Features**

- Extend a 1080p @ 24Hz (or 1920 x 1200) HDMI signal up to 150 ft. from the source
- Use P568-Series HDMI cables in most applications
- When extending a 1080p @ 24Hz (or 1920 x 1200) signal more than 75 ft., use cable made with 24Awg wiring, such as the P568-100-HD. (Lengths over 100 ft. are available from Tripp Lite as a custom order)
- 24Awg HDMI cable is also needed when extending a 3D signal more than 50 ft.. A 3D signal can be extended up to 125 ft. using 24Awg HDMI cable
- Supports DTS-HD, Dolby True HD and 7.1 Channel Surround Sound Audio
- HDCP compliant
- . No software or drivers required
- Compliant with the Federal Trade Agreements Act (TAA) for GSA Schedule purchases

# **Specifications**



OVERVIEW		
Intended Application	Connecting Devices	
Cable Type	HDMI	
Display Style	Signal Booster	
INPUT		
Cable Length (ft.)	1	
Cable Length (m)	0.30	
CONNECTIONS		
Connector A	HDMI (MALE)	
Connector B	HDMI (FEMALE)	
Number of Connectors	2	
WARRANTY		
Product Warranty Period (Worldwide)	1-year limited warranty	

## **Related Items**

### **Required Products**

Model Number	Description	Qty.
P568-025	25-ft. High Speed v1.3 HDMI Digital Video Gold Cable (HDMI M/M)	1

## **Optional Products**

Model Number	Description	Qty.
B122-000	HDMI Signal Extender ( 24Hz ) (HDMI F/F)	1

More information, including related products, owner's manuals, and additional technical specifications, can be found online at: http://www.tripplite.com/sku/B123-001.

© 2014 Tripp Lite. All rights reserved. All trademarks are the sole property of their respective owners. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Photos may differ slightly from final products.