



## 4 Port HDMI Video with Audio Extender Splitter over UTP Cat5 / Cat6, Transmitter, 1920x1200 1080p at 60Hz

MODEL NUMBER: **B126-004**



### Description

The B126-004 transmits a 1080p (60Hz) signal to four monitors up to 150 ft. away using Cat5e/6 cable. To achieve maximum distance and resolution, use 24Awg Solid Wire Cat5e/6 cable. (Tripp Lite's N202-Series) Daisychain up to three B126-004 transmitters to connect up to 13 monitors (1 Local, 12 Remote). Supports 24-bit True Color (8-bits per channel), HDCP, 3D, and both stereo audio and 7.1 channel surround sound audio (7.1 channel surround sound signal will be Multi-Channel or PCM).

Installation is simple. Connect the B126-004 transmitter to an HDMI source using a Tripp Lite P568-Series HDMI cable (not included). Connect a Tripp Lite B126-series receiver (not included) to each display using a Tripp Lite P568-Series HDMI cable (not included). Finally, each remote receiver is connected to an RJ45 port on the B126-004 using a single Cat5e/6 cable.

For longer extension distances, use a [B126-1A0](#) or [B126-1A0-WP-1](#) active receiver:

- A 1080p (60Hz) signal can be transmitted up to 150 ft.
- A 1080i (60Hz) signal can be transmitted up to 200 ft.
- A 3D signal can be transmitted up to 125 ft.

For shorter distances, use a [B126-1P0](#) or [B126-1P0-WP](#) passive receiver:

- A 1080p (60Hz) signal can be transmitted up to 50 ft.
- A 1080i (60Hz) signal can be transmitted up to 100 ft.
- Cannot be use for a 3D signal

Further extend the signal range or add more displays by using a Tripp Lite [B126-110](#) Remote Repeater unit:

### Highlights

- Supports computer video resolutions up to 1920 x 1200, and HD resolutions up to 1080p (60Hz)
- HDCP and 3D compatible
- Compatible with both stereo audio and 7.1 channel surround sound audio (7.1 channel surround sound signal will be Multi-Channel or PCM)
- Supports 24-bit True Color (8-bits per channel)
- Features an additional HDMI port for the connection of a local monitor
- The local monitor port can be used to daisychain up to three B126-004 transmitters
- Can further expand the range and number of monitors by adding repeaters
- Mounting hardware included

### Package Includes

- B126-004 HDMI Over Cat5 Extender/Splitter, 4-Port
- 1 ft. HDMI daisychain cable
- Mounting hardware
- External power supply (Input: 100-240V, 50/60Hz, 0.5A Output: 5V, 2A)
- Owner's Manual



**Tripp Lite**  
1111 W. 35th Street  
Chicago, IL 60609 USA  
Telephone: 773.869.1234  
www.tripplite.com

- Add up to three repeaters on each channel of the B126-004 for a total of 4 displays per channel (*A receiver should be the last unit in a channel*)
- A 1080p (60Hz) signal can be extended up to 125 ft. for each repeater added into a channel
- A 1080i (60Hz) signal can be extended up to 175 ft. for each repeater added into a channel
- A 3D signal can be extended up to 100 ft. for each repeater added into a channel

## Features



- Supports computer video resolutions up to 1920 x 1200, and HD resolutions up to 1080p (60Hz)
- 24Awg, Solid Wire Cat5e/6 cable, such as Tripp Lite's N202-Series, is required to achieve maximum distance and resolution.
- Use Tripp Lite P568-Series HDMI cables to connect to HDMI source and monitor.
- Extends a 1080p (60Hz) signal up to 150 ft. when used with a [B126-1A0](#) or [B126-1A0-WP-1](#) active remote receiver unit.
- Extends a 1080p (60Hz) signal up to 50 ft. when used with a [B126-1P0](#) or [B126-1P0-WP](#) passive remote receiver unit.
- Extends a 3D signal up to 125 ft. when used with an active remote receiver unit. A 3D signal cannot be extended using a passive remote receiver unit.
- Features an additional HDMI port for the connection of a local monitor, or to daisychain additional units.
- Connect up to 13 monitors (1 Local, 12 Remote) by daisychaining up to three B126-004 transmitters.
- Mount up to 3 B126-004 transmitters in 1U of rack space using a Tripp Lite [B132-004-RB](#) rackmount bracket
- Further extend the signal range or add more displays by using a Tripp Lite [B126-110](#) Remote Repeater unit.
- Connect up to 4 remote units in a repeater chain (3 repeaters and 1 active receiver), with a monitor at each location.
- Extends a 1080p (60Hz) signal up to 125 ft., or a 3D signal up to 100 ft., from the B126-004 transmitter to the first repeater unit in the installation
- Extends a 1080p (60Hz) signal up to an additional 125 ft., or a 3D signal up to an additional 100 ft., from each repeater unit to the next unit in the installation
- Supports 24-bit True Color (8-bits per channel)
- Compatible with both stereo audio and 7.1 channel surround sound audio (*7.1 channel surround sound signal will be Multi-Channel or PCM*).
- HDCP compatible
- Mounting hardware included
- Compatible with all operating systems
- Plug and play; No drivers required
- Compliant with the Federal Trade Agreements Act (TAA) for GSA Schedule purchases

## Specifications

OVERVIEW	
Cable Type	HDMI
Display Style	Splitter
PHYSICAL	
Optional mounting accessory notes	Up to three <a href="#">B126-004</a> local units can be mounted in 1U of rack space using a Tripp Lite <a href="#">B132-004-RB</a> Extender/Splitter 19in rackmount bracket
Unit Dimensions (HWD/in)	1.125 x 5 x 4
Unit Dimensions (HWD/cm)	2.86 x 12.7 x 10.16
Mounting accessories included	Yes
Color	Black



**Tripp Lite**  
1111 W. 35th Street  
Chicago, IL 60609 USA  
Telephone: 773.869.1234  
[www.tripplite.com](http://www.tripplite.com)

ENVIRONMENTAL	
Operating Temperature Range	0 to 40 C (32 to 104 F)
Storage Temperature Range	-20 to 60 C (-4 to 140 F)
Relative Humidity	20 to 90%
CONNECTIONS	
Connector A	 (X4) RJ45 (FEMALE)
Connector B	 (X2) HDMI (FEMALE)
WARRANTY	
Product Warranty Period (Worldwide)	1-year limited warranty

## Related Items

### Required Products

Model Number	Description	Qty.
<a href="#">B126-1A0</a>	HDMI Video with Audio Extender Over UTP Cat5 / Cat6, Receiver, 1920x1200 1080p at 60Hz	1

### Recommended Products

Model Number	Description	Qty.
<a href="#">N202-025-BL</a>	25-ft. Cat6 Gigabit Solid Conductor Snagless Patch Cable (RJ45 M/M ) - Blue	1

### Optional Products

Model Number	Description	Qty.
<a href="#">B110-INT</a>	International AC Adapter for Tripp Lite Video over CAT5 Extenders	1

More information, including related products, owner's manuals, and additional technical specifications, can be found online at:

<http://www.tripplite.com/sku/B126-004>.

© 2014 Tripp Lite. All rights reserved. All trademarks are the sole property of their respective owners. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Photos may differ slightly from final products.