

HDBaseT Lite HDMI Over Cat5e/6/6a Extender Transceiver with Serial and IR Passthrough, 4Kx2K UHD / 1080p, Up to 230-ft. (70M)

MODEL NUMBER: **BHDBT-TR-SI**



Description

The BHDBT-TR-SI HDBaseT Lite Extender Transceiver unit allows you to extend and expand your Tripp Lite HDBaseT Lite installation by connecting multiple monitors at different points in a chain. Transmitting HDMI audio and video, RS-232 serial and IR Remote Control signals between the transmitter and receiver units, it allows you to extend a 1080p (60Hz) signal up to 230-ft. (70M) from the previous unit in the chain. A 4Kx2K Ultra High Definition (UHD) 3840 x 2160 video signal can be extended up to 130-ft. (40M) from the previous unit in the chain. Add up to five BHDBT-TR-SI transceivers between your Tripp Lite HDBaseT Lite transmitter and receiver units to extend the range of your installation to up to 780-ft. (3840 x 2160) or 1,380-ft. (1080p), with a monitor connected at each point in the chain. (For use with Tripp Lite's [BHDBT-K-SI](#))

RS-232 Serial signals are passed through the transceiver(s), providing your installation the ability to control RS-232 serial devices, such as touchscreen displays or scanners, at baud rates up to 115 Kbps. IR Remote Control signals (@ 39 KHz) are also passed through the transceiver, allowing you to control your Blu-ray player using its remote when at the remote monitor, or to control your remote monitor using its remote when at the Blu-ray player. Locking HDMI ports (ideal for use with Tripp Lite's High-Speed HDMI cables with locking connectors, such as [P569-006-LOCK](#)) on all Tripp Lite HDBaseT Lite models prevent cables from coming loose or undone, ensuring an intact signal.

7.1-channel surround sound, DTS-HD and Dolby TrueHD audio are supported, as well as 3D video, EDID and HDCP. Included mounting hardware lets you attach each unit to a wall, rack or pole. There's no software to download or install, and you can set up your installation quickly. Compliant with the Federal Trade Agreements Act (TAA) for GSA Schedule purchases.

Features

Supports the Latest Video and Audio Applications

- Extends an Ultra High Definition (UHD) 3840 x 2160 (4K x 2K) signal up to 130-ft. (40M)
- Extends a High Definition 1920 x 1080 (1080p) @ 60 Hz signal up to 230-ft. (70M)

Highlights

- Extend and expand your Tripp Lite HDBaseT Lite installation by connecting multiple monitors at different points in a chain
- Insert the transceiver in between your Tripp Lite HDBaseT Lite transmitter and receiver units (For use with Tripp Lite's [BHDBT-K-SI](#))
- Up to 5 transceivers and 1 receiver can be connected in a chain, with each unit capable of extending its maximum distance from the previous unit in the chain
- Extends a 4Kx2K UHD 3840 x 2160 (24Hz or 30Hz) signal up to 130-ft. (40M)
- Extends a 1080p (60Hz) signal up to 230-ft. (70M)
- Supports 7.1-channel surround sound, DTS-HD and Dolby TrueHD audio
- Transmits RS-232 serial and IR Control signals between the transmitter and receiver units

Package Includes

- Transceiver unit
- External power supply (Input: 100–240V, 50/60 Hz, 0.5A; Output: 5V, 3A)
- Mounting hardware
- Owner's manual



Tripp Lite
1111 W. 35th Street
Chicago, IL 60609 USA
Telephone: 773.869.1234
www.tripplite.com

- Add up to five BHDBT-TR-SI transceivers to extend the range of your installation up to 780-ft. (3840 x 2160) or 1,380-ft. (1080p)
- Supports 7.1-channel surround sound, DTS-HD and Dolby TrueHD audio
- Supports 36-bit Deep Color (12 bits per channel), CEC pass-through, 3D video, EDID and HDCP 2.0

RS-232 Serial and IR Control Passthrough

- IR Remote Control signals are passed through the transceiver, letting you use your Blu-ray player with its remote while standing at the remote monitor (and vice versa)
- RS-232 serial signals are also passed through, giving you the ability to control RS-232 serial devices such as scanners and touchscreen monitors

Easy to Set Up and Use

- Plug-and-play engineering means no software or drivers to download and install
- Simply insert the BHDBT-TR-SI in between your Tripp Lite HDBaseT Lite Transmitter and Receiver units
- Included mounting hardware lets you install each unit on a wall, rack or pole
- Locking HDMI ports (for use with Tripp Lite High Speed HDMI cables with locking connectors, such as [P569-006-LOCK](#)) prevent cables from coming loose or disconnected, ensuring an intact signal

TAA-Compliant

- Compliant with the Federal Trade Agreements Act (TAA) for GSA Schedule purchases

Specifications

OVERVIEW	
Display Style	Extender
Cable Type	Cat5/5e; Cat6; Cat6/6a; Cat6a; HDMI
PHYSICAL	
Unit Dimensions (hwd / in.)	1.2 x 5 x 4
Included Mounting Accessories	Y
Color	Black
Unit Weight Details	1lb.
ENVIRONMENTAL	
Operating Temperature Range	0 to 40 C (32 to 104 F)
Storage Temperature Range	-20 to 60 C (-4 to 140 F)
Relative Humidity	20 to 90%
CONNECTIONS	
Connector A	HDMI (FEMALE)
Connector B	RJ45 (FEMALE) (X2)



Tripp Lite
1111 W. 35th Street
Chicago, IL 60609 USA
Telephone: 773.869.1234
www.tripplite.com

SPECIAL FEATURES	
Chromebook Compatible	Yes
CERTIFICATIONS	
Approvals	CE, FCC, RoHS, REACH
WARRANTY	
Product Warranty Period (Worldwide)	1-year limited warranty

© 2015 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies:
<http://www.tripplite.com/products/product-certification-agencies>