

1111 W. 35th Street Chicago, IL 60609 USA Telephone: 773.869.1234 www.tripplite.com



HDBaseT HDMI over Cat5e/6/6a 4x4 Extender Matrix Transmitter, Serial and IR, 4K x 2K @ 24/30Hz UHD / 1080p @ 60Hz, 4 Input, 4 Output,

MODEL NUMBER: BHDBT-T-SI-4X4









Description

The BHDBT-T-SI-4X4 HDBaseT HDMI over Cat5e/6/6a 4x4 Extender Matrix Transmitter works in tandem with the Tripp Lite BHDBT-Series receiver in your HDBaseT installation to extend uncompressed HDMI video and audio, RS-232 serial and IR remote control signals. It features four HDMI input ports and four RJ45 output ports, letting you route any source to any display or the same source to all displays.

Using a single Cat5e/6/6a cable, the BHDBT-T-SI-4X4 can extend an Ultra High Definition (UHD) 3840 x 2160 (4K x 2K) @ 24/30 Hz signal up to 328 feet (100 m) or a high-definition 1920 x 1080 (1080p) @ 60 Hz signal up to 500 feet (150 m). To further extend and expand your installation, you can insert up to five BHDBT-Series Extender Transceivers between the transmitter and receiver for a total range up to 3,000 feet with a monitor connected to each transceiver.** The sources connect to locking HDMI ports that prevent the cable from coming loose or undone, ensuring an intact signal.

The BHDBT-T-SI-4X4 supports 7.1-channel surround sound, DTS-HD and Dolby TrueHD audio, as well as 3D video, EDID and HDCP. Included mounting hardware lets you attach the unit to a wall, rack or pole. Sets up quickly with no software to download or install.

** Maximum supported extension distance and video resolutions depend on the receivers and/or transceivers being used. See the receiver (BHDBT-R-SI, BHDBT-R-SI-ER, BHDBT-R-SI-LR) and transceiver (BHDBT-TR-SI, BHDBT-TR-SI-ER, BHDBT-TR-SI-LR) pages for details.

Features

Highlights

- Features 4 HDMI input ports and 4 RJ45 output ports
- Supports video resolutions up to 3840 x 2160 (4K x 2K) @ 24/30Hz*
- Supports 7.1-channel surround sound, DTS-HD and Dolby TrueHD
- · Mounts easily to wall, rack or
- Plug and play—no software or drivers to install

Package Includes

- BHDBT-T-SI-4X4 HDBaseT HDMI over Cat5e/6/6a 4x4 **Extender Matrix Transmitter**
- · Remote control
- IR extension cable
- 3.5 mm Male to DB9 Female adapter cable
- External power supply w/NEMA 5-15P plug (Input: 100-240V, 50/60 Hz, 1.5A; Output: 12V, 5A)
- Mounting hardware
- · Owner's manual





Supports the Latest Video and Audio Applications

- Connects to Tripp Lite BHDBT-Series receivers and transceivers with a single Cat5e/6/6a cable
- Extends a 1920 x 1080 (1080p) @ 60 Hz signal up to 500 ft. (150 m)***
- Extends an Ultra High Definition (UHD) 3840 x 2160 (4K x 2K) @ 24/30 Hz signal up to 328 ft. (100 m)***
- Supports 7.1-channel surround sound, DTS-HD and Dolby TrueHD audio
- Supports 36-bit Deep Color (12 bits per channel), CEC pass-through, 3D video, EDID and HDCP 2.0
- Add up to 5 BHDBT-Series Extender Transceivers to further expand the range of your installation up to 3,000 feet (1080p) with a monitor attached to each transceiver***

4 HDMI Input Ports and 4 RJ45 Output Ports

- Can route any source to any display or the same source to all displays
- Control inputs and outputs using unit pushbuttons, included remote control or your computer's Terminal Emulation Software

Allows You to Control Other Devices

- 2-way 39 KHz IR Remote Control functionality lets you control your Blu-ray player with its remote while standing at the remote monitor (and vice versa)
- RS-232 serial port supports 115 Kbps full-duplex baud rates for devices such as scanners and touchscreen monitors

Easy to Set Up and Use

- Plug-and-play engineering—no software or drivers to download and install
- Included mounting hardware lets you install each unit on a wall, rack or pole
- Locking HDMI ports (ideal for use with Tripp Lite's <u>P569-006</u>-LOCK HDMI cables) prevent cables from coming loose or disconnected, ensuring an intact signal

TAA-Compliant

• Compliant with the Federal Trade Agreements Act (TAA) for GSA Schedule purchases

BHDBT-R-SIBHDBT-R-SIBHDBT-TR-SIBHDBT-TR-SIBHDBT-TR-SI

Specifications

MODEL TEXT	
Key Benefit	Works with a Tripp Lite HDBaseT receiver to extend uncompressed HDMI video and audio, RS-232 serial and IR remote control signals over a Cat5e/6/6a cable up to 500 ft. to 4 projectors, monitors or televisions.



OVERVIEW		
AC Adapter	Input: 100-240V, 50/60Hz, 0.5A; Output: 5V, 3A	
INPUT		
Nominal Input Voltage(s) Supported	100V AC; 110V AC; 115V AC; 120V AC; 127V AC; 140V AC; 200V AC; 208V AC; 220V AC; 230V AC; 240V AC	
Input Frequency	50/60Hz	
Input Current	120V (1.3A) / 230V (0.7A)	
PHYSICAL		
Unit Dimensions (hwd / in.)	1.7 x 17.3 x 4.7	
Included Mounting Accessories	Y	
Color	Black	
Unit Weight Details	3.50	
ENVIRONMENTAL		
Operating Temperature Range	0 to 40 C (32 to 104 F)	
Storage Temperature Range	-20 to 60 C (-4 to 140 F)	
Relative Humidity	20 to 90%	
COMMUNICATIONS		
Max 1024 x 768 Range (ft)	500	
Max 480P Range (ft)	500	
Max 1440 x 900 Range (ft)	500	
Max 1080i Range (ft)	500	
Max 1080P Range (ft)	500	
Max 1920 x 1440 Range (ft)	328	
Max 2560 x 1600 Range (ft)	328	
Max 4K UHD Range (ft)	328	
Max 480i Range (ft)	500	
Max 640 x 480 Range (ft)	500	
Max 800 x 600 Range (ft)	500	
Max 1600 x 1200 Range (ft)	500	
Max 720P Range (ft)	500	
CONNECTIONS		



Tripp Lite
1111 W. 35th Street
Chicago, IL 60609 USA
Telephone: 773.869.1234

Ports	4	
Side A - Connector 1	(4) HDMI (FEMALE)	
Side A - Connector 2	DB9 (FEMALE)	
Side B - Connector 1	(4) RJ45 (FEMALE)	
CERTIFICATIONS		
Approvals	CE, FCC, RoHS, REACH	
WARRANTY		
Product Warranty Period (Worldwide)	1-year limited warranty	

© 2017 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies: https://www.tripplite.com/products/product-certification-agencies