

Isolation Transformer

Medical Grade line noise reduction and spike suppression



Model #: IS1800HG

- ▶ Complete line isolation, noise filtering and surge suppression; ideal for sensitive equipment
- ▶ 1800 watts, 6 outlets, 6-ft. power cord
- ▶ Hospital-grade plug and receptacles
- ▶ 2-year limited product warranty
- ▶ MSRP: \$463.00

DESCRIPTION

Isolator Series UL60601-1 Listed Medical Grade Isolation Transformers offer line isolation, continuous noise filtering and enhanced common mode surge suppression. An internal low-impedance isolation transformer component offers 100% isolation from the input AC line. Full UL60601-1 medical-grade listing with hospital-grade plug and outlet receptacles makes Isolator medical-grade transformers ideal for protection of sensitive electronic equipment in patient-care areas. Faraday shield reduces the cumulative leakage current of the Isolator and connected equipment to levels as low as 100 microamps. Secondary neutral-to-ground bonding virtually eliminates common mode noise, providing an isolated neutral-ground reference for sensitive equipment, and an inexpensive alternative to dedicated circuits and site electrical upgrades. Removes EMI/RFI noise, utility switching transients and harmonics generated by other on-site loads and utility or lightning related surge conditions. Additional surge suppression components placed at the line input and output combined with full line isolation offer continuous filtering of a full range of power line noise in all modes. Active transformer filtering provides continuous common-mode noise rejection with no wearable parts. Unique ability to reduce surges in the worst of power environments to harmless levels. Reduces 6000V IEEE587 Cat A&B ring wave and combination wave test surges to only 0.5V common mode. Model IS1800HG includes 6 widely spaced NEMA 5-15R hospital-grade output receptacles, a 6-ft. power cord, hospital-grade input plug, circuit breaker overload protection, and lighted power switch. Rugged all-metal unit housing; ships ready for placement in any industrial, medical, office or network environment. 2-year warranty.

PLUG/OUTLETS: Input—NEMA 5-20P Hospital Grade; Output—6 NEMA 5-20R Hospital Grade (Package includes NEMA 5-15P user-installable hospital-grade replacement plug for compatibility with common 15A wall receptacles)

ELECTRICAL: 120V AC, 60Hz, 2.1A (Requires NEMA 5-15R wall receptacle)

FORMAT: Upright tower

ISOLATION: Transformer-based line isolation with Faraday shield

KEY BUYING POINTS

- The IS1800HG Medical Grade Isolation Transformer offers line isolation, continuous noise filtering and enhanced common mode surge suppression.
- Internal low-impedance isolation transformer with Faraday shield offers 100% isolation from the input AC line
- Full UL60601-1 medical-grade listing with hospital-grade plug and outlet receptacles makes Isolator Hospital Grade transformers ideal for the protection of sensitive electronic equipment in patient-care areas.
- Reduces the cumulative leakage current of the Isolator and connected equipment to levels as low as 100 microamps. Secondary neutral to ground bonding eliminates common mode noise, providing an isolated ground reference for sensitive equipment
- Serves as an inexpensive alternative to dedicated circuits and site electrical upgrades
- Removes EMI/RFI noise, utility switching transients, load-generated harmonics and ground loops
- Additional surge suppression components placed at the line input and output combined with full line isolation provide continuous filtering of a full range of power line noise in all modes
- Active transformer filtering offers continuous common-mode noise rejection with no wearable parts; unique ability to reduce surges in the worst of power environments to harmless levels
- Reduces 6000V IEEE587 Cat A&B ring wave and combination wave test surges to only 0.5V common mode
- Includes 6 widely spaced NEMA5-20R hospital-grade output receptacles, a 6-ft. power cord, hospital-grade input plug, circuit breaker

overload protection, and lighted power switch

- Ships with NEMA5-20P input plug installed, package includes NEMA5-15P user-installable hospital-grade replacement plug for compatibility with common 15A wall receptacles
- Rugged all-metal unit housing; ships ready for upright tower placement in any industrial, medical, office or network environment
- 2-year limited product warranty

PACKAGE INCLUDES

- IS1800HG Isolation Transformer
- NEMA5-15P replacement plug
- User manual with warranty information

COMPLETE SPECIFICATIONS

Nominal Voltage / Frequency	120V / 60Hz
VA / Watt Capacity	1800
Amp Capacity	15A at 120V AC
Transformer Type	Hospital Grade, low impedance transformer-based line isolation transformer
Total Harmonic Distortion	Less than 1%
Over Current Protection	Yes, 20A circuit breaker
Output Receptacle Qty / Type	6 NEMA 5-20R Hospital Grade Outlets
Input Plug Type	NEMA 5-20P Hospital Grade Plug
Input Cord Length	6.00 ft. / 1.83 m
Leakage Current	As low as 100 microamps
Efficiency	96%
Suppression Joule Rating	1190 (1020 input / 170 output)
Noise Suppression Rating	35-65 DB
Surge Test Conditions	Per ANSI/IEEE C62.41 - IEEE587 Cat. A & B test waveforms
Let-through Voltage (Ring Wave)	L-N: 20V L-G: 20V N-G: 0.5V
Let-through Voltage (Combination Wave)	L-N: 250V L-G: 250V N-G: 0.5V
Cooling Method	Convection
Form Factor	Small tower format
Unit Dimensions (HWD/in.)	7.75 x 8.25 x 12.25
Shipping Weight	58.00 lbs. / 26.31 kg
Warranty	2-year limited product warranty
Approvals	UL (UL Series AGIS1800YWN), cUL

*The policy of Tripp Lite is one of continuous improvement.
Specifications are subject to change without notice.
Therefore, your product may vary slightly from what is currently listed.*



Tripp Lite World Headquarters
1111 W. 35th Street
Chicago, IL 60609 USA

Customer Support
(773) 869-1234

© 2006 Tripp Lite. All Rights Reserved.