

## Isolation Transformer-Based Power Conditioner - Superior line noise reduction and spike suppression

MODEL NUMBER: IS500



### Description

Tripp Lite Isolator series isolation transformer-based power conditioners offer complete line isolation, continuous noise filtering and enhanced normal and common mode surge suppression. Internal low-impedance isolation transformer component with Faraday Shield offers 100% isolation from the input AC line. Secondary neutral to ground bonding eliminates common mode noise, providing an isolated ground reference for sensitive equipment and an inexpensive alternative to the installation of dedicated circuits and site electrical upgrades. Removes EMI/RFI noise, utility switching transients, background spikes generated by other on-site loads and utility or lightning related surge conditions. Additional surge suppression components placed at both the line input and transformer output combined with full line isolation offers continuous line filtering of a full range of power line noise in all modes. Continuous transformer filtering with no wearable parts uniquely reduces surges in the worst of power environments to harmless levels. Reduces 6000V IEEE C62.41 Cat A&B ring wave and combination wave test surges to only 0.5V common mode. Model IS500 offers 500 watts capacity with 4 widely spaced output receptacles, a 6-ft power cord, circuit breaker overload protection and lighted power switch. Rugged all-metal unit housing ships ready for upright tower or wallmount placement in industrial, medical, office or network environment.

### Features

- Tripp Lite Isolator series isolation transformer-based power conditioners offer complete line isolation, continuous noise filtering and enhanced common mode surge suppression
- Supports combined loads up to 500 watts continuous/4.2A at 120V
- Isolation transformer with Faraday Shield offers 100% isolation from the input AC line
- Neutral to ground bonding at the secondary eliminates common mode noise and provides an isolated ground reference for sensitive equipment
- Isolation transformer design serves as an inexpensive alternative to the installation of dedicated circuits and site electrical upgrades
- Removes EMI/RFI noise, utility switching transients, background spikes and power problems generated by other on-site loads, utility grid-switching and lightning related surges
- Line isolation with additional surge suppression components offer continuous line filtering of a full range of power line noise in all modes
- Continuous transformer filtering with no wearable parts reduces surges in the worst of power environments to harmless levels

### Highlights

- Complete line isolation, noise filtering and surge suppression is ideal for sensitive equipment
- 500 watts, 4 outlets, 6-ft. power cord
- Compliant with the Federal Trade Agreements Act (TAA) for GSA Schedule purchases

### Applications

- Offers fully isolated ground reference with enhanced surge and noise filtering for sensitive point of sale (POS) equipment, telecommunications systems, diagnostic testing and precise measurement devices, sophisticated CAD/CAM workstations, computer networking equipment and other pieces of sensitive electronic equipment.

### Package Includes

- IS500 Isolation transformer system
- Instruction manual with warranty information



**Tripp Lite**  
1111 W. 35th Street  
Chicago, IL 60609 USA  
Telephone: 773.869.1234  
www.tripplite.com

- Includes 4 widely-spaced NEMA5-15R output receptacles, 6 ft power cord, circuit breaker overload protection and lighted power switch
- Rugged all-metal housing ships ready for upright tower or wallmount installation

## Specifications

| OVERVIEW                               |  |
|--|--|
| Amp Capacity                           | 4.2A at 120V AC  |
| Efficiency                             | 96%  |
| Form Factor                            | Small tower format, wall mountable                         |
| Input Plug Type                        | NEMA 5-15P   |
| Let-through Voltage (Combination Wave) | L-N:   |
| Let-through Voltage (Ring Wave)        | L-N:   |
| Noise Suppression Rating               | 33-65dB normal mode; > 80dB common mode                    |
| Nominal Voltage / Frequency            | 120V / 60Hz  |
| Output Receptacle Qty / Type           | 4 NEMA 5-15R   |
| Over Current Protection                | Yes, 4.5A circuit breaker                                  |
| Suppression Joule Rating               | 680 Joules   |
| Surge Test Conditions                  | Per ANSI/IEEE C62.41 - (IEEE587) Cat. A & B test waveforms |
| Total Harmonic Distortion              | less than 1%   |
| Transformer Type                       | Low impedance isolation transformer                        |
| VA / Watt Capacity                     | 500  |
| INPUT                                  |  |
| Input cord length (ft.)                | 6  |
| Input cord length (m)                  | 1.83   |
| PHYSICAL                               |  |
| Shipping Dimensions (HWD/in)           | 7.25 x 13.25 x 6   |
| Shipping Dimensions (HWD/cm)           | 18.42 x 33.66 x 15.24                                      |
| Shipping weight (lbs)                  | 23.6   |
| Shipping weight (kg)                   | 10.71  |
| Unit Dimensions (HWD/in)               | 5.5 x 6.25 x 8.5   |
| Unit Dimensions (HWD/cm)               | 13.97 x 15.88 x 21.59                                      |
| Unit weight (lbs)                      | 22.6   |
| Unit weight (kg)                       | 10.25  |



**Tripp Lite**  
1111 W. 35th Street  
Chicago, IL 60609 USA  
Telephone: 773.869.1234  
[www.tripplite.com](http://www.tripplite.com)

|                                     |                         |
|-------------------------------------|-------------------------|
| Cooling method                      | Convection              |
| <b>WARRANTY</b>                     |                         |
| Product Warranty Period (Worldwide) | 2-year limited warranty |

© 2014 Tripp Lite. All rights reserved. All trademarks are the sole property of their respective owners. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Photos may differ slightly from final products.