



1U Rackmount Power Strip with 6 Rear-Facing Outlets and 15-ft. Cord

MODEL NUMBER: RS-0615-R





Description

Tripp Lite's RS-0615-R power strip offers 15 amp capacity AC power distribution in a versatile multi-mount cabinet. Detachable mounting flanges are configurable for rackmount, wallmount and under-counter installation. Uses only 1 rack space (1U) when installed in any 19 inch rack meeting EIA standards. Unfiltered electrical pass-through makes RS-0615-R ideal for distributing alternate waveform UPS or generator power in rack

enclosures, network closets and more. Includes 6 rear-facing NEMA5-15R outlets, 15 ft AC power cord and lighted switch with latching safety cover prevents risk of accidental turn-off.

PLUG/OUTLETS: Input: NEMA 5-15P/Output: 6 Rear-facing NEMA5-15R

ELECTRICAL: 120V AC, 50/60Hz, 15A (Requires standard NEMA 5-15R wall receptacle)

FORMAT: Supports 19 in. rackmount (uses 1 rack space/1U), wallmount, under-counter and more

Features

- Versatile all-metal cabinet with detachable mounting flanges allows rackmount, wallmount, undercounter and other creative mounting options
- Uses one rack space (1U) in standard 19 inch rack ("zero U" mounting possible in many racks)
- Unfiltered electrical pass-through reliably distributes alternate waveform AC power from UPS or generator to supported equipment
- 6 rear facing NEMA5-15R output receptacles
- 15 foot AC cord NEMA5-15P plug connection
- Lighted power switch confirms power on/off status
- · Latching switch guard prevents accidental turn off
- 15 amp electrical capacity with circuit breaker
- 120VAC, 50/60Hz electrical compatibility

Specifications

Highlights

- . 6 rear facing outlets
- 15 ft. cord
- 19" 1U rackmount
- All-metal housing

Applications

 Offers multiple outlet power distribution for multiple loads in 19 inch rackmount, wallmount and under- counter applications, such as internetworking, PC systems, telecommunications, audio/video, security, sound reinforcement and more. Ideal for distribution of UPS, generator or commercially derived AC power to protected equipment.

Package Includes

- RS-0615-R Power Strip
- Warranty information
- Instruction manual



OVERVIEW		
Intended Application	Computer Networks	
ОИТРИТ		
Frequency Compatibility	50 / 60 Hz	
Circuit Breaker (amps)	15	
Outlet Quantity / Type	6 NEMA 5-15R	
INPUT		
Nominal Input Voltage(s) Supported	120V AC	
Recommended Electrical Service	15A 120V	
Input Connection Type	NEMA 5-15P	
Input Cord Length (ft.)	15	
Input Cord Length (m)	4.572	
Voltage Compatibility (VAC)	120	
LEDS ALARMS & SWITCHES		
Switches	Red illuminated 2 positon switch controls power to all outlets	
Locking Switch Cover	Transparent locking switch cover prevents accidental shutoff	
PHYSICAL		
Unit Dimensions (hwd / in.)	1.75 (1U) x 17.5 x 4.5	
Unit Dimensions (hwd / cm)	4.445 x 44.45 x 11.4	
Unit Weight (lbs.)	4.5	
Unit Weight (kg)	2.04	
Material of Construction	Sheet metal	
Receptacle Color	Black	
Color (AC Line Cord)	Black	
Style	Rackmount	
Form Factors Supported	1U rackmount, wall-mount and undercounter installation supported	
Outlets Measurement (Center to Center)	Distance between grouped outlets = 38.90mm; Distance between groups = 75.4mm; Distance between duplex outlets = 114.3mm	
SPECIAL FEATURES		
TVSS Grounding	Back panel nut and bolt grounding lug	
CERTIFICATIONS		
	2/3	



Tripp Lite
1111 W. 35th Street
Chicago, IL 60609 USA
Telephone: 773.869.1234
www.tripplite.com

NOM (Mexico)	NOM
UL1363 (Power Tap)	UL1363 (UR status)
cUL / CSA (Canada)	cUL
WARRANTY	
Product Warranty Period (Worldwide)	Lifetime limited warranty

© 2014 Tripp Lite. All rights reserved. All trademarks are the sole property of their respective owners. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Photos may differ slightly from final products.