

USB C to HDMI External Video Adapter (M/F), Displayport Alternate Mode, 3840 x 2160 (4K x 2K) @ 30Hz

MODEL NUMBER: **U444-06N-HD-AM**



Description

The U444-06N-HD-AM USB 3.1 Gen 1 to HDMI Alternate Mode Dual/Multi-Monitor External Video Graphics Card Adapter supports USB DisplayPort Alternate Mode for displaying audio/video signals on an HDMI monitor or projector via your computer, tablet, laptop or smartphone's USB-C™ port. It's an ideal tool for multitasking, viewing large spreadsheets, editing documents, giving presentations at trade shows and conferences, or playing games and watching movies on large screens.

You can extend video from your primary display to another, duplicate the same video on both displays, or change the second display to your primary display. No external power supply is needed. Connect the adapter's USB-C male plug to the USB-C port on your smartphone, tablet, Ultrabook or computer. Then, connect the adapter's HDMI female port to a monitor using an HDMI cable (such as Tripp Lite's P568-Series) to see and hear full DisplayPort audio and video.

The U444-06N-HD-AM supports Ultra High Definition (UHD) 4K x 2K video resolutions up to 3840 x 2160 (@ 24/25/30 Hz). It also supports data transfer rates up to 5 Gbps, 36-bit Deep Color (12 bits per channel) and per-lane transfer rates of 5.4 Gbps (HBR2—High Bit Rate 2), 2.7 Gbps (HBR—High Bit Rate) and 1.62 Gbps (RBR—Reduced Bit Rate). Compatible with USB-C devices that support USB DisplayPort Alternate Mode.

Features

Easy to Add a Display

- Supports USB DisplayPort Alternate Mode for transmitting video to an HDMI display via your computer, tablet, laptop or smartphone's USB-C port
- Extend video to a second monitor, duplicate the same video on both monitors, or make the second

Highlights

- Supports USB DisplayPort Alternate Mode for transmitting video
- Extend video to a second display or duplicate one video on both
- Supports UHD 4K x 2K video resolutions up to 3840 x 2160
- Supports USB 3.1 Gen 1 data transfer rates up to 5 Gbps
- No external power supply or drivers required

System Requirements

- USB-C device that supports USB DisplayPort Alternate Mode
- HDMI-enabled monitor

Package Includes

- U444-06N-HD-AM USB 3.1 Gen 1 to HDMI Alternate Mode Dual/Multi-Monitor External Video Graphics Card Adapter
- Quick Start Guide



Tripp Lite
1111 W. 35th Street
Chicago, IL 60609 USA
Telephone: 773.869.1234
www.tripplite.com

monitor your primary display

- Ideal for multitasking, viewing spreadsheet data, editing documents, giving presentations, watching movies and playing video games
- No external power supply or drivers required
- Compatible with USB-C devices that support USB DisplayPort Alternate Mode

Vibrant, Superior Video Quality

- Supports Ultra High Definition (UHD) 4K x 2K video resolutions up to 3840 x 2160 (@ 24/25/30 Hz)
- Supports USB 3.1 Gen 1 data transfer rates up to 5 Gbps
- Supports per-lane transfer rates of 5.4 Gbps (HBR2), 2.7 Gbps (HBR) and 1.62 Gbps (RBR)
- Supports 36-bit Deep Color (12 bits per channel)

Specifications

MODEL TEXT	
Key Benefit	Connect an HDMI monitor or projector to the USB Type-C™ port on your computer or laptop. Ideal for multitasking, presenting at trade shows and conferences, editing documents, playing games and watching movies.
PHYSICAL	
Color	White
CONNECTIONS	
Side A - Connector 1	USB C (MALE)
Side B - Connector 1	HDMI (FEMALE)
WARRANTY	
Product Warranty Period (Worldwide)	1-year limited warranty

© 2017 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies:

<https://www.tripplite.com/products/product-certification-agencies>