S19 - VERSASENSE BUZZER ACTUATOR

PRODUCT DESCRIPTION

The VersaSense Buzzer Actuator (\$19) emits a constant audio tone when it is actuated.

VERSASENSE SENSORS

VersaSense Sensors are self-identifying sensors and actuators that connect to VersaSense Wireless Devices to provide plugand-play sensing and control.

The VersaSense software automatically installs and configures all drivers, eliminating the cost and complexity of deploying an IoT network.

Note: only one peripheral of this type may be connected to a VersaSense Wireless Device.

APPLICATIONS

The buzzer actuator provides a simple audio alarm. Applications include:

- ★ Alerting of detected environmental phenomena
- ★ Alarm systems

CORE COMPONENTS

The **\$19** is based on the SMA-21LC-P10 from Sonitron[®], for more information please visit:

Sonitron_SMA-21LC-P10.pdf

S19 CHARACTERISTICS

Characteristic	Value	Unit
Audio output level	91	dB(a)
Audio frequency	3800	Hz
Avg current (ON)	1.10	mA
Avg current (OFF)	0.00	μΑ
Min/Max period between updates	10 / 86400*	S

^{*} The latency of actuation is constrained by network configuration. This may range from a few seconds for small networks, up to a few minutes for large networks.

Note: avg current values represent the current that this sensor draws from a VersaSense Wireless Device. This value excludes message transmission.

RELATED PRODUCTS

Item **\$19** requires a VersaSense Wireless Device such as **Pxx** or **Lxx**. This item is compatible with all items in the VersaSense catalog:

versasense.com/files/VersaSense-Catalog.pdf

INFORMATION/SUPPORT

Web: www.versasense.com
Sales: sales@versasense.com
Help: support@versasense.com
Other: info@versasense.com

Post: VersaSense NV, Kapeldreef 60, 3001

Leuven, Belgium.