


Surface Mount, Molded Inductor



STANDARD ELECTRICAL SPECIFICATIONS

IND. (μ H)	TOL.	Q MIN.	TEST FREQ. L & Q (MHz)	SELF- RESONANT FREQ. MIN. (MHz)	DCR MAX. (Ohms)	RATED* DC CURRENT (mA)
0.010	$\pm 20\%$	50	50.0	1000	0.20	450
0.012	$\pm 20\%$	50	50.0	1000	0.20	450
0.018	$\pm 20\%$	50	50.0	1000	0.20	450
0.022	$\pm 20\%$	50	50.0	1000	0.20	450
0.027	$\pm 20\%$	50	50.0	1000	0.20	450
0.033	$\pm 20\%$	50	50.0	1000	0.30	450
0.039	$\pm 20\%$	50	50.0	1000	0.30	450
0.047	$\pm 20\%$	50	50.0	1000	0.30	450
0.056	$\pm 20\%$	40	50.0	900	0.35	450
0.068	$\pm 20\%$	40	50.0	800	0.35	450
0.082	$\pm 20\%$	40	50.0	700	0.40	450
0.10	$\pm 20\%$	30	25.2	650	0.32	450
0.12	$\pm 20\%$	30	25.2	600	0.30	450
0.15	$\pm 20\%$	30	25.2	500	0.30	450
0.18	$\pm 20\%$	30	25.2	400	0.35	450
0.22	$\pm 20\%$	30	25.2	350	0.40	450
0.27	$\pm 20\%$	30	25.2	300	0.45	450
0.33	$\pm 20\%$	30	25.2	250	0.55	430
0.39	$\pm 20\%$	30	25.2	220	0.70	380
0.47	$\pm 10\%$	30	25.2	190	0.80	355
0.56	$\pm 10\%$	30	25.2	170	1.20	285
0.68	$\pm 10\%$	30	25.2	150	1.40	270
0.82	$\pm 10\%$	30	25.2	140	1.60	250
1.0	$\pm 10\%$	50	7.96	100	0.50	450
1.2	$\pm 10\%$	50	7.96	80.0	0.55	430
1.5	$\pm 10\%$	50	7.96	70.0	0.60	410
1.8	$\pm 10\%$	50	7.96	60.0	0.65	390
2.2	$\pm 10\%$	50	7.96	55.0	0.70	380
2.7	$\pm 10\%$	50	7.96	50.0	0.75	370
3.3	$\pm 10\%$	50	7.96	45.0	0.80	355
3.9	$\pm 10\%$	50	7.96	40.0	0.90	330
4.7	$\pm 10\%$	50	7.96	35.0	1.00	315
5.6	$\pm 10\%$	50	7.96	33.0	1.10	300
6.8	$\pm 10\%$	50	7.96	27.0	1.20	285
8.2	$\pm 10\%$	50	7.96	25.0	1.40	270
10.0	$\pm 10\%$	50	2.52	20.0	1.60	250
12.0	$\pm 10\%$	50	2.52	18.0	2.00	225
15.0	$\pm 10\%$	50	2.52	17.0	2.50	200
18.0	$\pm 10\%$	50	2.52	15.0	2.80	190
22.0	$\pm 10\%$	50	2.52	13.0	3.20	180
27.0	$\pm 10\%$	50	2.52	12.0	3.60	170
33.0	$\pm 10\%$	50	2.52	11.0	4.00	160
39.0	$\pm 10\%$	50	2.52	11.0	4.50	150
47.0	$\pm 10\%$	50	2.52	10.0	5.00	140
56.0	$\pm 10\%$	50	2.52	9.0	5.50	135
68.0	$\pm 10\%$	50	2.52	9.0	6.00	130
82.0	$\pm 10\%$	50	2.52	8.0	7.00	120
100.0	$\pm 10\%$	40	0.79	8.0	8.00	110
120.0	$\pm 10\%$	40	0.79	6.0	8.00	110
150.0	$\pm 10\%$	40	0.79	5.0	9.00	105
180.0	$\pm 10\%$	40	0.79	5.0	9.50	102
220.0	$\pm 10\%$	40	0.79	4.0	10.0	100
270.0	$\pm 10\%$	40	0.79	4.0	12.0	92
330.0	$\pm 10\%$	40	0.79	3.5	14.0	85
390.0	$\pm 10\%$	40	0.79	3.0	16.0	80
470.0	$\pm 10\%$	40	0.79	3.0	26.0	62
560.0	$\pm 10\%$	30	0.79	3.0	30.0	50
680.0	$\pm 10\%$	30	0.79	3.0	30.0	50
820.0	$\pm 10\%$	30	0.79	2.5	35.0	30
1000.0	$\pm 10\%$	30	0.25	2.5	40.0	30

FEATURES

- Molded construction provides superior strength and moisture resistance
- Tape and reel packaging for automatic handling, 2000/reel, EIA 481
- Printed marking
- Compatible with vapor phase and infrared reflow soldering
- 100 % lead (Pb)-free and RoHS compliant

RoHS
COMPLIANT


ELECTRICAL SPECIFICATIONS

Inductance Range: 0.010 μ H to 1000 μ HInductance Tolerance: $\pm 20\%$ for 0.010 μ H to 0.39 μ H
 $\pm 10\%$ for 0.47 μ H to 1000 μ H standard
 $\pm 10\%$, $\pm 5\%$, $\pm 3\%$ availableTemperature Range: - 55 $^{\circ}$ C to + 125 $^{\circ}$ CCoilform Material: Non-magnetic for 0.010 μ H to 0.82 μ H
Powdered Iron for 1.0 μ H to 120 μ H. Ferrite for 150 μ H to 1000 μ H

TEST EQUIPMENT

- H/P 4342A Q meter with Vishay Dale test fixture or equivalent
- H/P 4191A RF Impedance Analyzer (for SRF measurements)
- Wheatstone bridge

DIMENSIONS in inches [millimeters]



* Recommended minimum spacing between components

PART MARKING

- Vishay Dale
- Inductance value
- Date code

DESCRIPTION

IMC-1812	10 μ H	$\pm 10\%$	ER	e3
MODEL	INDUCTANCE VALUE	INDUCTANCE TOLERANCE	PACKAGE CODE	JEDEC LEAD FREE STANDARD

GLOBAL PART NUMBER

GLOBAL PART NUMBER												
I	M	C	1	8	1	2	E	R	1	0	0	K
PRODUCT FAMILY			SIZE				PACKAGE CODE		INDUCTANCE VALUE			TOL.



Notice

Specifications of the products displayed herein are subject to change without notice. Vishay Intertechnology, Inc., or anyone on its behalf, assumes no responsibility or liability for any errors or inaccuracies.

Information contained herein is intended to provide a product description only. No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document. Except as provided in Vishay's terms and conditions of sale for such products, Vishay assumes no liability whatsoever, and disclaims any express or implied warranty, relating to sale and/or use of Vishay products including liability or warranties relating to fitness for a particular purpose, merchantability, or infringement of any patent, copyright, or other intellectual property right.

The products shown herein are not designed for use in medical, life-saving, or life-sustaining applications. Customers using or selling these products for use in such applications do so at their own risk and agree to fully indemnify Vishay for any damages resulting from such improper use or sale.