



## Optocoupler, Photodarlington Output, High Gain (Quad Channel)


Quad Channel



SMD



i179011-2



### FEATURES

- Isolation test voltage, 5300 V<sub>RMS</sub>
- High isolation resistance, 10<sup>11</sup> Ω typical
- Low coupling capacitance
- Standard plastic DIP package
- Compliant to RoHS Directive 2002/95/EC and in accordance to WEEE 2002/96/EC


**RoHS**  
COMPLIANT

### AGENCY APPROVALS



- UL1577, file no. E52744 system code H, double protection
- cUL tested to CSA 22.2 bulletin 5A
- DIN EN 60747-5-2 (VDE 0884)/DIN EN 60747-5-5 (pending), available with option 1
- BSI IEC 60950; IEC 60065

### DESCRIPTION

The ILQ32 is optically coupled isolators with a gallium arsenide infrared LED and a silicon photodarlington sensor. Switching can be achieved while maintaining a high degree of isolation between driving and load circuits.

These optocouplers can be used to replace reed and mercury relays with advantages of long life, high speed switching and elimination of magnetic fields.

### ORDERING INFORMATION



| AGENCY CERTIFIED/PACKAGE | CTR (%)                    |
|--------------------------|----------------------------|
| <b>UL, cUL, BSI</b>      | <b>≥ 500</b>               |
| DIP-16                   | ILQ32                      |
| SMD-16, option 7         | ILQ32-X007T <sup>(1)</sup> |
| SMD-16, option 9         | ILQ32-X009T <sup>(1)</sup> |
| <b>VDE, UL, cUL, BSI</b> | <b>≥ 500</b>               |
| DIP-16                   | ILQ32-X001                 |

### Notes

- Additional options may be possible, please contact sales office.
- <sup>(1)</sup> Also available in tubes, do not put T on the end.

| ABSOLUTE MAXIMUM RATINGS ( $T_{amb} = 25^{\circ}\text{C}$ , unless otherwise specified) |                                                        |       |            |               |                        |
|-----------------------------------------------------------------------------------------|--------------------------------------------------------|-------|------------|---------------|------------------------|
| PARAMETER                                                                               | TEST CONDITION                                         | PART  | SYMBOL     | VALUE         | UNIT                   |
| <b>INPUT</b>                                                                            |                                                        |       |            |               |                        |
| Peak reverse voltage                                                                    |                                                        |       | $V_R$      | 3             | V                      |
| Forward continuous current                                                              |                                                        |       | $I_F$      | 60            | mA                     |
| Power dissipation                                                                       |                                                        |       | $P_{diss}$ | 100           | mW                     |
| Derate linearly from $25^{\circ}\text{C}$                                               |                                                        |       |            | 1.33          | mW/ $^{\circ}\text{C}$ |
| <b>OUTPUT</b>                                                                           |                                                        |       |            |               |                        |
| Collector emitter breakdown voltage                                                     |                                                        |       | $BV_{CEO}$ | 30            | V                      |
| Collector (load) current                                                                |                                                        |       | $I_C$      | 125           | mA                     |
| Power dissipation                                                                       |                                                        |       | $P_{diss}$ | 150           | mW                     |
| Derate linearly from $25^{\circ}\text{C}$                                               |                                                        |       |            | 2             | mW/ $^{\circ}\text{C}$ |
| <b>COUPLER</b>                                                                          |                                                        |       |            |               |                        |
| Isolation test voltage between emitter and detector                                     | $t = 1\text{ s}$                                       |       | $V_{ISO}$  | 5300          | $V_{RMS}$              |
| Creepage distance                                                                       |                                                        |       |            | $\geq 7$      | mm                     |
| Clearance distance                                                                      |                                                        |       |            | $\geq 7$      | mm                     |
| Comparative tracking index per DIN IEC 112/VDE 0303, part 1                             |                                                        |       | CTI        | $\geq 175$    |                        |
| Isolation resistance                                                                    | $V_{IO} = 500\text{ V}, T_{amb} = 25^{\circ}\text{C}$  |       | $R_{IO}$   | $10^{12}$     | $\Omega$               |
|                                                                                         | $V_{IO} = 500\text{ V}, T_{amb} = 100^{\circ}\text{C}$ |       | $R_{IO}$   | $10^{11}$     | $\Omega$               |
| Total dissipation                                                                       |                                                        | ILQ32 | $P_{tot}$  | 500           | mW                     |
| Derate linearly from $25^{\circ}\text{C}$                                               |                                                        | ILQ32 |            | 6.67          | mW/ $^{\circ}\text{C}$ |
| Storage temperature                                                                     |                                                        |       | $T_{stg}$  | - 55 to + 150 | $^{\circ}\text{C}$     |
| Operating temperature                                                                   |                                                        |       | $T_{amb}$  | - 55 to + 100 | $^{\circ}\text{C}$     |
| Lead soldering time at $260^{\circ}\text{C}$                                            |                                                        |       |            | 10            | s                      |

## Note

- Stresses in excess of the absolute maximum ratings can cause permanent damage to the device. Functional operation of the device is not implied at these or any other conditions in excess of those given in the operational sections of this document. Exposure to absolute maximum ratings for extended periods of the time can adversely affect reliability.

| ELECTRICAL CHARACTERISTICS ( $T_{amb} = 25^{\circ}\text{C}$ , unless otherwise specified) |                                                  |             |      |      |      |               |
|-------------------------------------------------------------------------------------------|--------------------------------------------------|-------------|------|------|------|---------------|
| PARAMETER                                                                                 | TEST CONDITION                                   | SYMBOL      | MIN. | TYP. | MAX. | UNIT          |
| <b>INPUT</b>                                                                              |                                                  |             |      |      |      |               |
| Forward voltage                                                                           | $I_F = 10\text{ mA}$                             | $V_F$       |      | 1.25 | 1.5  | V             |
| Reverse current                                                                           | $V_R = 3\text{ V}$                               | $I_R$       |      | 0.1  | 100  | $\mu\text{A}$ |
| Capacitance                                                                               | $V_R = 0\text{ V}$                               | $C_O$       |      | 25   |      | pF            |
| <b>OUTPUT</b>                                                                             |                                                  |             |      |      |      |               |
| Collector emitter breakdown voltage                                                       | $I_C = 100\text{ }\mu\text{A}, I_F = 0\text{ A}$ | $BV_{CEO}$  | 30   |      |      | V             |
| Breakdown voltage emitter collector                                                       | $I_E = 100\text{ }\mu\text{A}$                   | $BC_{ECO}$  | 5    | 10   |      | V             |
| Collector emitter leakage current                                                         | $V_{CE} = 10\text{ V}, I_F = 0\text{ A}$         | $I_{CEO}$   |      | 1    | 100  | nA            |
| <b>COUPLER</b>                                                                            |                                                  |             |      |      |      |               |
| Collector emitter                                                                         | $I_C = 2\text{ mA}, I_F = 8\text{ mA}$           | $V_{CEsat}$ |      |      | 1    | V             |
| Capacitance (input to output)                                                             |                                                  | $C_{IO}$    |      | 0.5  |      | pF            |

## Note

- Minimum and maximum values are testing requirements. Typical values are characteristics of the device and are the result of engineering evaluation. Typical values are for information only and are not part of the testing requirements.

**CURRENT TRANSFER RATIO** ( $T_{amb} = 25\text{ }^{\circ}\text{C}$ , unless otherwise specified)

| PARAMETER              | TEST CONDITION                                | SYMBOL | MIN. | TYP. | MAX. | UNIT |
|------------------------|-----------------------------------------------|--------|------|------|------|------|
| Current transfer ratio | $I_F = 10\text{ mA}$ , $V_{CE} = 10\text{ V}$ | CTR    | 500  |      |      | %    |

**SWITCHING CHARACTERISTICS** ( $T_{amb} = 25\text{ }^{\circ}\text{C}$ , unless otherwise specified)

| PARAMETER     | TEST CONDITION                                                              | SYMBOL    | MIN. | TYP. | MAX. | UNIT          |
|---------------|-----------------------------------------------------------------------------|-----------|------|------|------|---------------|
| Turn-on time  | $V_{CC} = 10\text{ V}$ , $I_F = 5\text{ mA}$ ,<br>$R_L = 100\text{ }\Omega$ | $t_{on}$  |      | 15   |      | $\mu\text{s}$ |
| Turn-off time | $V_{CC} = 10\text{ V}$ , $I_F = 5\text{ mA}$ ,<br>$R_L = 100\text{ }\Omega$ | $t_{off}$ |      | 30   |      | $\mu\text{s}$ |

**SAFETY AND INSULATION RATINGS**

| PARAMETER                                               | TEST CONDITION         | SYMBOL | MIN.   | TYP.      | MAX. | UNIT               |
|---------------------------------------------------------|------------------------|--------|--------|-----------|------|--------------------|
| Climatic classification<br>(according to IEC 68 part 1) |                        |        |        | 55/100/21 |      |                    |
| Comparative tracking index                              |                        | CTI    | 175    |           | 399  |                    |
| $V_{IOTM}$                                              |                        |        | 10 000 |           |      | V                  |
| $V_{IORM}$                                              |                        |        | 890    |           |      | V                  |
| $P_{SO}$                                                |                        |        |        |           | 400  | mW                 |
| $I_{SI}$                                                |                        |        |        |           | 275  | mA                 |
| $T_{SI}$                                                |                        |        |        |           | 175  | $^{\circ}\text{C}$ |
| Creepage distance                                       |                        |        | 7      |           |      | mm                 |
| Clearance distance                                      |                        |        | 7      |           |      | mm                 |
| Insulation thickness,<br>reinforced rated               | per IEC 60950 2.10.5.1 |        | 0.4    |           |      | mm                 |

**Note**

- As per IEC 60747-5-2, § 7.4.3.8.1, this optocoupler is suitable for "safe electrical insulation" only within the safety ratings. Compliance with the safety ratings shall be ensured by means of protective circuits.



**TYPICAL CHARACTERISTICS** ( $T_{amb} = 25\text{ }^{\circ}\text{C}$ , unless otherwise specified)


Fig. 1 - Forward Voltage vs. Forward Current


Fig. 2 - Normalized Non-saturated and Saturated  $CTR_{CE}$  vs. LED Current




Fig. 3 - Normalized Non-Saturated and Saturated Collector Emitter Current vs. LED Current




Fig. 6 - Switching Timing




Fig. 4 - Low to High Propagation Delay vs. Collector Load Resistance and LED Current




Fig. 7 - Switching Schematic





Fig. 5 - High to low Propagation Delay vs. Collector Load Resistance and LED Current


### Optocoupler, Photodarlington Output, High Gain (Quad Channel)

Vishay Semiconductors

### PACKAGE DIMENSIONS in millimeters



## PACKAGE MARKING



## Notes

- Only options 1 and 7 reflected in the package marking
- The VDE logo is only marked on option 1 parts
- Tape and reel suffix (T) is not part of the package marking



## Disclaimer

ALL PRODUCT, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE TO IMPROVE RELIABILITY, FUNCTION OR DESIGN OR OTHERWISE.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained in any datasheet or in any other disclosure relating to any product.

Vishay makes no warranty, representation or guarantee regarding the suitability of the products for any particular purpose or the continuing production of any product. To the maximum extent permitted by applicable law, Vishay disclaims (i) any and all liability arising out of the application or use of any product, (ii) any and all liability, including without limitation special, consequential or incidental damages, and (iii) any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.

Statements regarding the suitability of products for certain types of applications are based on Vishay's knowledge of typical requirements that are often placed on Vishay products in generic applications. Such statements are not binding statements about the suitability of products for a particular application. It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application. Parameters provided in datasheets and / or specifications may vary in different applications and performance may vary over time. All operating parameters, including typical parameters, must be validated for each customer application by the customer's technical experts. Product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein.

Except as expressly indicated in writing, Vishay products are not designed for use in medical, life-saving, or life-sustaining applications or for any other application in which the failure of the Vishay product could result in personal injury or death. Customers using or selling Vishay products not expressly indicated for use in such applications do so at their own risk. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay. Product names and markings noted herein may be trademarks of their respective owners.