

Industrial Ethernet EBR-MODULE RS232

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 16
D-32758 Detmold
Germany
Fon: +49 5231 14-0
Fax: +49 5231 14-292083
www.weidmueller.com



External module for backing up and restoring the configuration

- Reduced system downtime by simple reconfiguration if equipment is swapped over
- Plug&Play system backup and recovery
- Compact and robust design
- Can be used with all Weidmüller Managed Switches in the Value and PremiumLine as well as the Weidmüller WLAN Access Point

General ordering data

Type	EBR-MODULE RS232
Order No.	1241430000
Version	Configuration module, IP 40, 0 °C...+60 °C
GTIN (EAN)	4050118029086
Qty.	1 pc(s).

Industrial Ethernet EBR-MODULE RS232

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 16
D-32758 Detmold
Germany
Fon: +49 5231 14-0
Fax: +49 5231 14-292083
www.weidmueller.com

Technical data

Dimensions and weights

Width	32.5 mm	Height	12 mm
Depth	97 mm	Weight	50 g
Net weight	50 g		

EMC conformity and approvals

EMC standards	FCC Part 15, CISPR (EN55022) Class A, EN 61000-4-2 (ESD), Stage 2, EN 61000-4-3 (RS), Stage 3, EN 61000-4-4 (EFT), Stage 3, EN 61000-4-5 (surge voltage), Stage 3, EN 61000-4-6 (CS), Stage 3
---------------	---

Environmental conditions

Humidity	5 to 95 % (non-condensing)	Operating temperature, max.	60 °C
Operating temperature, min.	0 °C	Storage temperature, max.	70 °C
Storage temperature, min.	-20 °C		

Guarantee

Time interval	5 years
---------------	---------

Order data

Operating temperature	0 °C...+60 °C
-----------------------	---------------

Power supply

Connection type	RJ45-Port, RS232	Input voltage	3 to 5 V DC (via the RTS signal of the RS-232 port)
-----------------	------------------	---------------	---

Technical data

Cable length	0.35 m	Housing main material	PVC casting
Protection degree	IP 40	Type of fixing	M4 screw (<4 mm)

Classifications

eClass 6.2	19-17-01-06	eClass 7.1	19-17-01-06
------------	-------------	------------	-------------

Approvals

ROHS	Conform
------	---------

Downloads

Package insert	Hardware Installation Guide
Declaration of Conformity	K424_01_11.pdf
	3-D model