

PLUGSERIES
PLED 24Vdc

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 16
D-32758 Detmold
Germany
Fon: +49 5231 14-0
Fax: +49 5231 14-292083
www.weidmueller.com



High power/currents can be safely switched with the PLUGSERIES. The modular system enables conventional relays and LED indicators simply to be plugged in. Retaining and disassembly clips provide a secure mount. Pre-assembled relays with 1 or 2 changeover contacts and input voltages from 24V to 230V round of the product range. Plug-in ZQV 2.5 cross-connectors enable relay multiplexers to be set up quickly thanks to simple side-by-side mounting.

General ordering data

Type	PLED 24Vdc
Order No.	8536710000
Version	PLUGSERIES, Relays, Plug-in connection
GTIN (EAN)	4032248171972
Qty.	20 pc(s).

PLUGSERIES
PLED 24Vdc

Weidmüller Interface GmbH & Co. KG
 Klingenbergstraße 16
 D-32758 Detmold
 Germany
 Fon: +49 5231 14-0
 Fax: +49 5231 14-292083
 www.weidmueller.com

Technical data
Dimensions and weights

Width	15 mm	Height	10 mm
Depth	31.5 mm	Net weight	1.8 g

Temperatures

Operating temperature	-40 °C...+50 °C	Ambient temperature	-40 °C...+50 °C
Storage temperature			

Input

Protective circuit	Integrated free-wheel diode	Status indicator	Green LED
--------------------	-----------------------------	------------------	-----------

general data

Wire connection method	Plug-in connection	UL 94 flammability rating	V-0
Ambient temperature	-40 °C...+50 °C		

Insulation coordination

Protection degree	IP 20
-------------------	-------

Other technical data

Version	Relay accessory - LED with free-wheel diode	Protective circuit	Integrated free-wheel diode
Status indicator	Green LED		

Connection data

Wire connection method	Plug-in connection
------------------------	--------------------

Classifications

ETIM 3.0	EC000996	UNSPSC	32-11-15-03
eClass 5.1	27-11-06-35	eClass 6.2	27-11-06-35
eClass 7.1	27-11-06-35		

Product information

Descriptive text technical data	Cross-connectors and markers - refer to PLUGSERIES accessories
---------------------------------	--

Approvals

Approvals



ROHS	Conform
------	---------