




A Dimensions: [mm]













Scale - 10:1

B Recommended land pattern: [mm]



C Schematic:



D Absolute Maximum Ratings (Ambient Temperature 25°C):


Properties	Test conditions		Value	Unit
Power dissipation		P _{Diss}	60	mW
Peak Forward Current	duty/10@1kHz	I _{F Peak}	100	mA
Continuous Forward Current		ΙF	25	mA
Reverse Voltage		V _{Rev}	5	V
ESD Threshold/ Human Body Modell		V _{ESD HBM}	2000	V

E General information:

- •Operating temperature: -40°C to +80°C
- •Storage temperature (on tape & reel): -40°C to +85°C; 60% RH max.

Optical Properties:

Properties	Value
Chip Technology	AllnGaP
Emitting Color	Yellow
Lens Type	Rectangular



Würth Elektronik eiSos GmbH & Co. KG EMC & Inductive Solutions Max-Eyth-Str. 1 74638 Waldenburg Tel. +49 (0) 79 42 945 - 0 www.we-online.com

DESCRIPTION

WL-SMRW SMD mono-color reverse mount waterclear

Order.- No.

156120YS75000



SIZE A4

This electronic component has been designed and developed for usage in general electronic equipment only. This product is not authorized for use in equipment only. This product is reasonably expected to cause severe personal injury or death, unless the parties have executed an agreement specifically governing such use. Moreover Würth Elektronik eiSos GmbH & Co KG products are neither designed nor intended for use in areas such as military, aerospace, aviation, nuclear control, strip control), transportation (automotive control, train control, strip control), transportation (automotive control, train control, strip control), transportation (automotive control, train control, trai the design-in stage. In addition, sufficient reliability evaluation checks for safety must be performed on every electronic component which is used in electrical circuits that require high safety and reliability functions or performance.



D Electrical & Optical Properties:

Properties	Test conditions		Value			Unit	
Troporado	Tool containions		min.	typ.	max.		
Peak Wavelength	20 mA	λ_{Peak}		592		nm	
Dominant wavelength	20 mA	λ _{Dom}		589		nm	
Luminous Intensity	20 mA	IV	40	80		mcd	
Forward voltage	20 mA	V _F		2.0	2.4	V	
Spectral Bandwidth	20 mA	Δλ		15		nm	
Reverse Current	5 V	I _{Rev}			10	μА	
Viewing angle	20 mA	2 θ _{50%}		140		0	


				Projection ————————————————————————————————————		DESCRIPTION WL-SMRW SMD		
1.3	2013-04-11	SSt	SSt	Würth Elektronik eiSos Gmbl EMC & Inductive Solutions	waterclear			
1.2	2013-04-11	SSt	HOe	Max-Eyth-Str. 1 74638 Waldenburg		Order No.		
1.1	2012-12-10	SSt	SSt	Germany Tel. +49 (0) 79 42 945 - 0		4504000005000		
1.0	2012-11-05	SSt	H0e	www.we-online.com eiSos@we-online.com		156120YS75000		
REV	DATE	BY	CHECKED	CIOOSSWC ONINIE.COM		Size: 1206		




A4



F Viewing Angle:




F Spectral:




				Projection		DESCRIPTION				
					WL-SMRW SMD mono-color reverse moun					
				Würth Elektronik eiSos Gmbl	H & Co. KG	waterclear				
1.3	2013-04-11	SSt	SSt	EMC & Inductive Solutions Max-Eyth-Str. 1						
1.2	2013-02-11	SSt	H0e	74638 Waldenburg		Order No.	COMPLIANT	SI7F		
1.1	2012-12-10	SSt	SSt	Germany Tel. +49 (0) 79 42 945 - 0		45040000055000	ROHS&REACH HALOGENFREE	SIZL		
1.0	2012-11-05	SSt	H0e	www.we-online.com eiSos@we-online.com		156120YS75000	5000 VIALOGENIAL			
REV	DATE	BY	CHECKED	- GIOOSWWG-UIIIIIIE.CUIII		Size: 1206				



F Forward Current vs. Forward Voltage:




F Luminous Intensity vs. Forward Current:



				Projection -		DESCRIPTION WL-SMRW SMD n	nono-color reverse	mount		
1.3	2013-04-11	SSt	SSt	Würth Elektronik eiSos Gmbl EMC & Inductive Solutions	H & Co. KG	waterclear				
1.2	2013-02-11	SSt	H0e	- Max-Eyth-Str. 1 74638 Waldenburg		Order No.	COMPLIANT	SIZE		
1.1	2012-12-10	SSt	SSt	Germany Tel. +49 (0) 79 42 945 - 0		4504000075000	ROHS&REACH HALOGENFREE	SIZE		
1.0	2012-11-05	SSt	H0e	www.we-online.com eiSos@we-online.com		156120YS75000	- THEOGENTHEE	A4		
REV	DATE	BY	CHECKED	GOODS NO CHIIIIC.COM		Size: 1206				




F Derating Curve:







G Packaging Specification: [mm]








		A0	В0	w	P1	Т	T1	T2	D0	E1	E2	F	P0	P2	Таре	Packaging Unit
	tolerance	typ.	typ.	+0,3 -0,1	± 0,1	± 0,1	max.	typ.	+0,1 -0,0	± 0,1	min.	± 0,05	± 0,1	± 0,05		
size	1206	1,71	3,50	8,00	4,00	0,22	0,10	1,50	1,50	1,75	6,25	3,50	4,00	2,00	Polystyrene	2000



Packaging is referred to the international standard IEC 60286 -3:2007







eiSos@we-online.com


Würth Elektronik eiSos GmbH & Co. KG EMC & Inductive Solutions Max-Eyth-Str. 1 74638 Waldenburg Germany Tel. +49 (0) 79 42 945 - 0 www.we-online.com







	Α	В	С	D	N	W1	W2	W3	W3
tolerance	± 2,0	min.	± 0,8	min.	min.	+ 1,5	max.	min.	max.
Tape width 8 mm	178,00	1,50	13,00	20,20	50,00	8,40	14,40	7,90	10,90





WL-SMRW SMD mono-color reverse mount waterclear

Size: 1206

156120YS75000




SIZE A4

This electronic component has been designed and developed for usage in general electronic equipment only. This product is not authorized for use in equipment only. This product is reasonably expected to cause severe personal injury or death, unless the parties have executed an agreement specifically governing such use. Moreover Würth Elektronik eiSos GmbH & Co KG products are neither designed nor intended for use in areas such as military, aerospace, aviation, nuclear control, strip control), transportation (automotive control, train control, strip control), transportation (automotive control, train control, strip control), transportation (automotive control, train control, trai the design-in stage. In addition, sufficient reliability evaluation checks for safety must be performed on every electronic component which is used in electrical circuits that require high safety and reliability functions or performance.

H Soldering Specifications:



H1: Classification Reflow Profile for SMT components:



H2: Classification Reflow Profile:

Profile Feature	Pb-Free Assembly	
Preheat - Temperature Min (T _{smin}) - Temperature Max (T _{smax}) - Time (t _s) from (T _{smin} to T _{smax})	150°C 200°C 120 seconds max.	
Ramp-up rate (T _L to T _P)	3°C/ second max.	
Liquidous temperature (T_L) Time (t_L) maintained above T_L	217°C 60 seconds max.	
Peak package body temperature (Tp)	250°C max.	
Time within 5°C of actual peak temperature (t _p)	10 seconds max.	
Ramp-down rate (T _P to T _L)	6°C/ second max.	
Time 25°C to peak temperature	220 seconds max.	
Applied cycles	2 cycles max.	

				Projection +		DESCRIPTION				
				WL-SMI		WL-SMRW SMD mono-color reverse moun				
				Würth Elektronik eiSos GmbH &	& Co. KG	waterclear				
1.3	2013-04-11	SSt	SSt	EMC & Inductive Solutions Max-Eyth-Str. 1						
1.2	2013-02-11	SSt	H0e	74638 Waldenburg		Order No.	SIZE			
1.1	2012-12-10	SSt	SSt	Germany Tel. +49 (0) 79 42 945 - 0		ROHS&REACH HALOGENEREE	OIZE			
1.0	2012-11-05	SSt	H0e	www.we-online.com eiSos@we-online.com		156120YS75000				
REV	DATE	BY	CHECKED	Clobs@wc Offinic.com		Size: 1206				

I Cautions and Warnings:

The following conditions apply to all goods within the product series of WL-SMRW of Würth Elektronik eiSos GmbH & Co. KG:

General:

All recommendations according to the general technical specifications of the data-sheet have to be complied with.

The disposal and operation of the product within ambient conditions which probably alloy or harm the component surface has to be avoided.

If the product is potted in customer applications, the potting material might shrink during and after hardening. Accordingly to this the product is exposed to the pressure of the potting material with the effect that the LED body, pins or termination is possibly damaged by this pressure and so the electrical as well as the mechanical characteristics are endanger to be affected. After the potting material is cured, the LED body, pins or termination of the product have to be checked if any reduced electrical or mechanical functions or destructions have occurred.

The responsibility for the applicability of customer specific products and use in a particular customer design is always within the authority of the customer. All technical specifications for standard products do also apply for customer specific products.

Washing varnish agent that is used during the production to clean the application might damage or change the characteristics of the LED body, pins or termination. The washing varnish agent could have a negative effect on the long term function of the product.

Direct mechanical impact to the product shall be prevented as the material of the LED body, pins or termination could flake or in the worst case it could break.



Product specific:

Follow all instructions mentioned in the datasheet, especially:

- The solder profile has to be complied with according to the technical reflow/ or wave soldering specification, otherwise no warranty will be sustained.
- •All products shall be used before the end of the period of 12 months based on the product date-code, if not a 100% solderability can't be warranted.
- Violation of the technical product specifications such as exceeding the absolute maximum ratings will result in the loss of warranty.
- •It is also recommended to return the LEDs to the original moisture proof bag and reseal the moisture proof bag again.
- Certain LED surfaces consist of soft material. Pressure on the top surface has to be handeled carefully to prevent negative influence to the function and reliability of the LEDs.
- •ESD prevention methods need to be applicated for manual handling and processing by machinery.
- Resistors for protection are obligatory.
- •LED products in operation could harm human vision, therefore direct light impact has to be avoided.



J Important Notes:

The following conditions apply to all goods within the product range of Würth Elektronik eiSos GmbH & Co. KG:

1. General Customer Responsibility

Some goods within the product range of Würth Elektronik eiSos GmbH & Co. KG contain statements regarding general suitability for certain application areas. These statements about suitability are based on our knowledge and experience of typical requirements concerning the areas, serve as general guidance and cannot be estimated as binding statements about the suitability for a customer application. The responsibility for the applicability and use in a particular customer design is always solely within the authority of the customer. Due to this fact it is up to the customer to evaluate, where appropriate to investigate and decide whether the device with the specific product characteristics described in the product specification is valid and suitable for the respective customer application or not.

2. Customer Responsibility related to Specific, in particular Safety-Relevant Applications

It has to be clearly pointed out that the possibility of a malfunction of electronic components or failure before the end of the usual lifetime cannot be completely eliminated in the current state of the art, even if the products are operated within the range of the specifications.

In certain customer applications requiring a very high level of safety and especially in customer applications in which the malfunction or failure of an electronic component could endanger human life or health it must be ensured by most advanced technological aid of suitable design of the customer application that no injury or damage is caused to third parties in the event of malfunction or failure of an electronic component.

Therefore, customer is cautioned to verify that data sheets are current before placing orders. The current data sheets can be downloaded at www.we-online.com.

3. Best Care and Attention

Any product-specific notes, cautions and warnings must be strictly observed. Any disregard will result in the loss of warranty.

4. Customer Support for Product Specifications

Some products within the product range may contain substances which are subject to restrictions in certain jurisdictions in order to serve specific technical requirements. Necessary information is available on request. In this case the field sales engineer or the internal sales person in charge should be contacted who will be happy to support in this matter.

5. Product R&D

Due to constant product improvement product specifications may change from time to time. As a standard reporting procedure of the Product Change Notification (PCN) according to the JEDEC-Standard inform about minor and major changes. In case of further queries regarding the PCN, the field sales engineer or the internal sales person in charge should be contacted. The basic responsibility of the customer as per Section 1 and 2 remains unaffected.



6. Product Life Cycle

Due to technical progress and economical evaluation we also reserve the right to discontinue production and delivery of products. As a standard reporting procedure of the Product Termination Notification (PTN) according to the JEDEC-Standard we will inform at an early stage about inevitable product discontinuance. According to this we cannot guarantee that all products within our product range will always be available. Therefore it needs to be verified with the field sales engineer or the internal sales person in charge about the current product availability expectancy before or when the product for application design-in disposal is considered.

The approach named above does not apply in the case of individual agreements deviating from the foregoing for customer-specific products.

7. Property Rights

All the rights for contractual products produced by Würth Elektronik eiSos GmbH & Co. KG on the basis of ideas, development contracts as well as models or templates that are subject to copyright, patent or commercial protection supplied to the customer will remain with Würth Elektronik eiSos GmbH & Co. KG.

Würth Elektronik eiSos GmbH & Co. KG does not warrant or represent that any license, either expressed or implied, is granted under any patent right, copyright, mask work right, or other intellectual property right relating to any combination, application, or process in which Würth Elektronik eiSos GmbH & Co. KG components or services are used.

8. General Terms and Conditions

Unless otherwise agreed in individual contracts, all orders are subject to the current version of the "General Terms and Conditions of Würth Elektronik eiSos Group", last version available at www.we-online.com.

				Projection							
				Würth Elektronik eiSos GmbH & Co. KG							
1.3	2013-04-11	SSt	SSt	EMC & Inductive Solutions Max-Eyth-Str. 1 74638 Waldenburg							
1.2	2013-02-11	SSt	H0e								
1.1	2012-12-10	SSt	SSt	Germany Tel. +49 (0) 79 42 945 - 0 www.we-online.com eiSos@we-online.com							
1.0	2012-11-05	SSt	H0e								
REV/	DATE	RV	CHECKED	CIOOS@WC-OHIIIIC.COH							

DESCRIPTION

WL-SMRW SMD mono-color reverse mount waterclear

Order.- No

Size: 1206

156120YS75000



SIZE A4

This electronic component has been designed and developed for usage in general electronic equipment only. This product is not authorized for use in equipment where a higher safety standard and reliability standard and reliability standard and reliability standard and reliability standard is especially required or where a failure of the products are neither designed nor intended for use in areas such as military, aerospace, aviation, nuclear control, submarine, transportation signal, disaster prevention, medical, public information network etc.. Würth Elektronik eSos GmbH & Co KG must be informed about the intent of such usage before the design-in stage. In addition, sufficient reliability evaluation checks for safety must be performed on every electronic component which is used in electrical circuits that require high safety and reliability functions or performance.