



NOTES

注释

1. CONTACT CURRENT RATING: 10 A
触点额定电流: 10 A
2. CONTACT RESISTANCE: 50 mΩ MAX.
接触电阻: 最大50 mΩ
3. INSULATION RESISTANCE: 100MΩ MIN,
绝缘电阻: 最小100MΩ ,
4. DIELECTRIC WITHSTANDING: 36V AC MIN.
耐介质电压: 36V AC MIN.
5. DURABILITY: 5,000 CYCLES MIN.;
耐久性: 最小 5000 次循环;
6. CONNECTOR MATING FORCES: 29.4N(3.00Kgf) MAX
最大连接器配合力为 29.4N (3.00Kgf)。
7. CONNECTOR UNMATING FORCES: 2.94N(0.30Kgf) MIN
连接器最小不匹配力为 2.94N (0.30Kgf)。

P.C.B LAYOUT TOP VIEW

	MATERIAL	PLATING
axis support	Brass	silver
plastic	Pbt	
terminal 1	Brass	silver
terminal 2	Phosphor Bronze	silver
terminal 3	Brass	silver

广东星坤科技股份有限公司

ΔX	日期
ΔX	日期
ΔX	日期
MARK	DESCRIPTION

文件工程章

REVISIONS	DATE	REVISED	APPROVED	DESCRIPTION

www.helloxkb.com www.helloxkb.cn www.xk-dg.cn

ANGLAR	±5°
L ≤ 4	±0.2
4 < L ≤ 16	±0.3
16 < L ≤ 63	±0.4
L > 63	±0.5

UNSPECIFIED TOLERANCES

XKB

XKB INDUSTRIAL PRECISION CO., LIMITED

DSND	SCALE: N/A	MODEL TYPE: DC POWER JACK
DWN	VIEW:	PART NO.: DC-042E
CHKD	UNIT: mm/in	DWG NO.:
APPD	SIZE: A4	
	WEIGHT	SHEET
		1/1
	REVISIC	A0