



NOTES:

注释

- 1.CONTACT CURRENT RATING:7A
触点额定电流: 7A
- 2.CONTACT RESISTANCE:50 mΩ MAX
接触电阻: 最大50 mΩ
3. INSULATION RESISTANCE:100MΩ MIN
绝缘电阻: 100MΩ MIN
- 4.DIELECTRIC WITHSTANDING: 500V AC MIN.
耐介质: 最小500V AC。
- 5.DURABILITY:5.000 CYCLES MIN.
耐久性: 至少5.000次循环。
- 6.CONNECTOR MATING FORCES:29.4N(3.00Kgf)MAX.;
连接器配合力: 最大29.4N (3.00Kgf)。
- 7.CONNECTOR UNMATING FORCES:2.94N(0.30Kgf) MIN
连接器脱离力: 最小2.94N (0.30Kgf)

SCHMATIC	M4(+)/PIN M1(-)/TIP SPRING
Model	DC-044AE
Center Pin	Ø2.0 mm
	Ø2.5 mm

	MATERIAL	PLATING
axis support	Brass	silver
center pin	Brass	silver
plastic	Pbt	
terminal 1	Brass	silver
terminal 2	Phosphor Bronze	silver
terminal 3	Brass	silver

广东星坤科技股份有限公司

MARK	DESCRIPTION	DATE	REVISED	APPROVED	ANGLAR	±5°
Δx					X.X	±0.2mm
Δx					X.XX	±0.1mm
Δx					X.XXX	±0.05mm

文件工程章

REVISIONS	UNSPECIFIED TOLERANCES
www.xk-dg.cn www.helloxkb.com www.helloxkb.cn	

DSND		DATE		SCALE: N/A	MODEL TYPE: DC POWER JACK	
DWN		DATE		VIEW:	PART NO.:	
CHKD		DATE		UNIT: mm/in	DWG NO.:	
APPD		DATE		SIZE: A4	DC-044AE-2.5	
				WEIGHT	SHEET	REVISIO
XKB INDUSTRIAL PRECISION CO.,LIMITED				1.0g	1/1	A0