



P.C.B LAYOUT TOP VIEW

SPECIFICATION

规格

Rating: DC 20V 5.5A

额定值: 直流20V 5.5A

Contact resistance:  $\leq 0.03\Omega$

接触电阻:  $\leq 0.03\Omega$

Insulation resistance:  $\geq 100M\Omega$

绝缘电阻:  $\geq 100M\Omega$

Withstand voltage :AC500V(50Hz)/min

耐受电压: AC500V (50Hz) /min

Insertion and extraction: 3-20N

插入和提取: 3-20N

Use temperature range: -30-70 °C

使用温度范围: -30-70 °C

Life test :5000 cycles

寿命试验: 5000次循环

SCHEMATIC	
Model	DC-C300-5.5A
Center Pin	Ø1.65 mm
	Ø2.0 mm
	Ø2.5 mm

	MATERIAL	PLATING
center pin	Brass	tin
coat	Brass	
cover palte	Sus	
terminal 1	Phosphor Bronze	tin
terminal 2	Phosphor Bronze	tin
terminal 3	Phosphor Bronze	tin
plastic	Ppa	

广东星坤科技股份有限公司

ΔX	日期
ΔX	日期
ΔX	日期
MARK	DESCRIPTION

文件工程章

REVISIONS	DATE	REVISED	APPROVED	UNSPECIFIED TOLERANCES
				ANGLAR ±5°
				L ≤ 4 ±0.2
				4 < L ≤ 16 ±0.3
				16 < L ≤ 63 ±0.4
				L > 63 ±0.5

**XKIB**

XKB INDUSTRIAL PRECISION CO., LIMITED

DSND	SCALE: N/A	MODEL TYPE: DC POWER JACK
DWN	VIEW:	PART NO.: DC-C300-5.5A-2.5
CHKD	UNIT: mm/in	DWG NO.:
APPD	SIZE: A4	
	WEIGHT	SHEET
		1/1
	REVISIC	A0