

CIRCUIT DIAGRAM

FEATURES

特征

Light operating force.

轻操作力。

Long term low contact resistance.

长期接触电阻低。

Momentary or latching operation.

固定或闭锁操作。

Short stroke 1.5mm to latch.

短行程1.5毫米至闭锁。

SPECIFICATIONS





1.ELECTRICAL

Contact rating	0.1A,30VDC
Contact resistance	50mWMax.
Insulation resistance	100MWMin. at 250VDC
Dielectric strength	250VAC Min. for 60 sec.

2.MECHANICAL AND ENVIRONMENTAL

Temperature rating	Operating:-15℃ to+55℃ Storage: -25℃ to +65℃
Operation force	250±50gf
Stroke	Lock Stroke: 1.5+0.2mm Full Stroke: 2.0+0.2mm
Operating life	full load: 1x10 ⁴ cycles no load: 1 x10 ⁵ cycles
Contact form	DPDT

PAPT NO	XKB5858-X-F-75
OPERATION	W:NO LOCK Z:LOCK



PCB LAYOUT

⑦	Contact	—	2	Phosphor bronze	Plating silvering	—
⑥	Terminal	—	6	Brass	Plating silvering	—
⑤	Spring	—	1	Sus	Natural	—
④	Base	—	1	Ppa		—
③	Crochet Needle	—	1	Sus	Natural	—
②	Cover	—	1	Ppa		—
①	Keystake	—	1	Ppa		—
ITEM	PAPT NAMF	TER.NO	QTY	MATERIAL	FINISHING	REMARK

广东星坤科技股份有限公司

ΔX		日期
ΔX		
ΔX		
MARK		

文件工程章

DESCRIPTION	DATE	REVISED	APPROVED	UNSPECIFIED TOLERANCES
REVISIONS				
www.helloxkb.com www.helloxkb.cn www.xk-dg.cn				

DSND		SCALE: N/A	MODEL TYPE: KEY SWITCH
DWN		VIEW:	PART NO.: XKB5858-X-F-75
CHKD		UNIT: mm/in	DWG NO.:
APPD		SIZE: A4	
XKB INDUSTRIAL PRECISION CO.,LIMITED			WEIGHT
			SHEET
			REVISIC
			1/1
			A0