

FEATURES

- Light operating force.
- Long term low contact resistance.
- Momentary or latching operation.
- Short stroke 1.9mm to latch.
- Compact spacing on PCB of 7.0mm.

SPECIFICATIONS

1. ELECTRICAL


● Contact rating	0.1A30VDC
● Contact resistance	50mWMax.
● Insulation resistance	100MWMin.at250VDC
● Dielectric strength	250VAC Min. for 60 sec

2.MECHANICAL AND ENVIRONMENTAL

● Temperature rating	Storage:-25℃to +65℃ Operating:-15℃to+55℃
● Operation force	160+80gf
● Stroke	Lock Stroke:1.9±0.2mm Full Stroke:2.4±0.2mm
● Operating life	full load: 1x10 ⁴ cyclesno load: 1x10 ⁵ cycles
● Contact form	DPDT

PAPT NO	XKB7070-X
OPERATION	W:NO LOCK Z:LOCK

⑦	Contact	—	2	Phosphor bronze	Plating silvering	—
⑥	Terminal	—	6	Brass	Plating silvering	—
⑤	Spring	—	1	Sus	Natural	—
④	Base	—	1	Pbt		—
③	Crochet Needle	—	1	Sus	Natural	—
②	Cover	—	1	Pom		—
①	Keystake	—	1	Pom		—
ITEM	PAPT NAMF	TER,NO	QTY	MATERIAL	FINISHING	REMARK



常态: 2-3导通 5-6导通
按下: 1-2导通 4-5导通

广东星坤科技股份有限公司

ΔX		日期
ΔX		日期
ΔX		日期
MARK		日期

文件工程章

DESCRIPTION	DATE	REVISED	APPROVED	UNSPECIFIED TOLERANCES
REVISIONS				
www.helloxkb.com www.helloxkb.cn www.xk-dg.cn				

DSND		SCALE: N/A	MODEL TYPE: KEY SWITCH
DWN		VIEW:	PART NO.: XKB7070-X
CHKD		UNIT: mm/in	DWG NO.:
APPD		SIZE: A4	
XKB INDUSTRIAL PRECISION CO.,LIMITED			WEIGHT
			SHEET
			REVISIC
			1/1
			A0