


# Molded Wirewound Power Resistors Axial Leads




## FEATURES

- 2 W
- Excellent stability = typical drift  $\pm 1\%$  after 2000 h
- Low ohmic values =  $0.025\ \Omega$  available
- Electrical insulation
- Climatic protection
- Material categorization: for definitions of compliance please see [www.vishay.com/doc?99912](http://www.vishay.com/doc?99912)


RoHS  
COMPLIANT

## DIMENSIONS in millimeters



| MODEL | PROTECTION   |               |               |            |
|-------|--------------|---------------|---------------|------------|
|       | A            | Ø B           | Ø C $\pm 0.1$ | WEIGHT (g) |
| 63BSI | $10 \pm 0.2$ | $3.7 \pm 0.1$ | 0.6           | 0.45       |

## STANDARD ELECTRICAL SPECIFICATIONS

| MODEL | SIZE | RESISTANCE RANGE $\Omega$ | RATED POWER $P_{25\ ^\circ\text{C}}$ W | LIMITING ELEMENT VOLTAGE V | TOLERANCE $\pm \%$ | TEMPERATURE COEFFICIENT $\pm \text{ppm}/^\circ\text{C}$ |
|-------|------|---------------------------|----------------------------------------|----------------------------|--------------------|---------------------------------------------------------|
| 63BSI | 063  | 0.025 to 4K               | 2                                      | 120                        | 0.5, 1, 2, 5       | 100, 300                                                |

## TECHNICAL SPECIFICATIONS

| VISHAY SFERNICE SERIES     |                                      |                          | 63BSI                            |
|----------------------------|--------------------------------------|--------------------------|----------------------------------|
| Ohmic range in relation to | $\pm 100\ \text{ppm}/^\circ\text{C}$ | $\pm 0.5\%$<br>$\pm 5\%$ | 0.1 $\Omega$<br>4 k $\Omega$     |
| Temperature coefficient    | $\pm 300\ \text{ppm}/^\circ\text{C}$ | $\pm 1\%$<br>$\pm 5\%$   | 0.025 $\Omega$<br>< 0.1 $\Omega$ |

## MECHANICAL SPECIFICATIONS


|                       |                     |
|-----------------------|---------------------|
| Mechanical Protection | Molded              |
| Resistive Element     | CuNi or CrNi        |
| Substrate             | Alumina             |
| Connections           | Sn/Ag/Cu 99/0.3/0.7 |

## ENVIRONMENTAL SPECIFICATIONS


|                   |                                               |
|-------------------|-----------------------------------------------|
| Temperature Range | -55 $^\circ\text{C}$ to +275 $^\circ\text{C}$ |
| Climatic Category | 55/200/56                                     |

| PERFORMANCE                   |                                                                                                                    |                                                      |                                                     |
|-------------------------------|--------------------------------------------------------------------------------------------------------------------|------------------------------------------------------|-----------------------------------------------------|
| TESTS                         | CONDITIONS                                                                                                         | REQUIREMENTS                                         | TYPICAL VALUES AND DRIFTS                           |
| Dielectric Strength           | IEC 60115-1<br>1000 V <sub>RMS</sub> for 923 to 947<br>500 V <sub>RMS</sub> for 58 to 523                          | ± (0.1 % + 0.05 Ω)                                   | ± (0.1 % + 0.05 Ω)                                  |
| Short Time Overload           | IEC 60115-1<br>5 P <sub>n</sub> / 5 s for P <sub>r</sub> < 5 W<br>10 P <sub>n</sub> / 5 s for P <sub>r</sub> ≥ 5 W | ± (0.2 % + 0.05 Ω)                                   | ± (0.1 % + 0.05 Ω)                                  |
| Endurance                     | IEC 60115-1<br>90' / 30' P <sub>r</sub> at 25 °C, 2000 h                                                           | ± (1 % + 0.05 Ω)                                     | ± (0.1 % + 0.05 Ω)                                  |
| Endurance at High Temperature | 250 h at 275 °C                                                                                                    | ± (0.5 % + 0.05 Ω)                                   | ± (0.3 % + 0.05 Ω)                                  |
| Thermal Shock                 | Load at 100 % P <sub>r</sub> followed<br>by cold temp. exposure<br>at -55 °C                                       | ± (0.2 % + 0.05 Ω)                                   | ± (0.1 % + 0.05 Ω)                                  |
| Climatic Sequence             | IEC 60115-1<br>-55 °C / +200 °C<br>5 cycles                                                                        | ± (0.5 % + 0.05 Ω)<br>Insulation resistance ≥ 100 MΩ | ± (0.3 % + 0.05 Ω)<br>Insulation resistance > 10 GΩ |
| Damp Heat, Steady State       | IEC 60115-1 / IEC 60068-2-78<br>56 days, 40 °C, 93 % RH                                                            | ± (0.5 % + 0.05 Ω)<br>Insulation resistance ≥ 100 MΩ | ± (0.3 % + 0.05 Ω)<br>Insulation resistance > 10 GΩ |
| Moisture Resistance           | MIL-STD-202<br>method 106                                                                                          | ± (0.2 % + 0.05 Ω)<br>Insulation resistance ≥ 100 MΩ | ± (13 % + 0.05 Ω)<br>Insulation resistance > 10 GΩ  |
| Shock                         | MIL-STD-202<br>100 g method 205 - test C                                                                           | ± (0.1 % + 0.05 Ω)                                   | ± (0.05 % + 0.05 Ω)                                 |
| Vibration                     | MIL-STD-202<br>method 204 - Test D: 20 g<br>10Hz / 2000 Hz                                                         | ± (0.1 % + 0.05 Ω)                                   | ± (0.05 % + 0.05 Ω)                                 |

## POWER RATING



## TEMPERATURE RISE



## MARKING

GEKA trademark, model, style, nominal resistance (in Ω), tolerance (in %), manufacturing date.  
Because of lack of space, small styles are marked with ohmic value (in Ω), and tolerance (in %) only.

| ORDERING INFORMATION |       |             |           |                         |           |                |
|----------------------|-------|-------------|-----------|-------------------------|-----------|----------------|
| BSI                  | 63    | U22         | 2 %       | ± 100 ppm/°C            | TR300     | e1             |
| MODEL                | STYLE | OHMIC VALUE | TOLERANCE | TEMPERATURE COEFFICIENT | PACKAGING | LEAD (Pb)-FREE |

| GLOBAL PART NUMBER INFORMATION |      |   |                                                                                                                                                                                                                         |   |   |   |   |                                            |   |                                                                                                                                                                                                                              |   |   |                           |   |  |
|--------------------------------|------|---|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---|---|---|---|--------------------------------------------|---|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---|---|---------------------------|---|--|
| B                              | S    | I | 0                                                                                                                                                                                                                       | 6 | 3 | 2 | R | 8                                          | 7 | 0                                                                                                                                                                                                                            | F | R | 2                         | 2 |  |
| GLOBAL<br>MODEL                | SIZE |   | OHMIC VALUE                                                                                                                                                                                                             |   |   |   |   | TOLERANCE                                  |   | PACKAGING                                                                                                                                                                                                                    |   |   | SPECIAL                   |   |  |
| BSI                            | 063  |   | The first digits are significant figures and the last digit specifies the number of zeros to follow.<br>R designates decimal point.<br><br>2R870 = 2.87 Ω<br>1R200 = 1.2 Ω<br>10001 = 10 000 Ω<br>R3300 = 0.33 Ω<br>... |   |   |   |   | D = 0.5 %<br>F = 1 %<br>G = 2 %<br>J = 5 % |   | Size 058:<br>R26 = reel<br>(5000 pieces)<br>size 063:<br>R22 = reel<br>(3000 pieces)<br>size 68, 516, 523:<br>R17 = reel<br>(1250 pieces)<br>size 923, 932, 947:<br>B19 = box<br>(30 pieces)<br><br>Other packaging existing |   |   | As applicable<br>Ex = BP1 |   |  |



## Disclaimer

ALL PRODUCT, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE TO IMPROVE RELIABILITY, FUNCTION OR DESIGN OR OTHERWISE.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained in any datasheet or in any other disclosure relating to any product.

Vishay makes no warranty, representation or guarantee regarding the suitability of the products for any particular purpose or the continuing production of any product. To the maximum extent permitted by applicable law, Vishay disclaims (i) any and all liability arising out of the application or use of any product, (ii) any and all liability, including without limitation special, consequential or incidental damages, and (iii) any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.

Statements regarding the suitability of products for certain types of applications are based on Vishay's knowledge of typical requirements that are often placed on Vishay products in generic applications. Such statements are not binding statements about the suitability of products for a particular application. It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application. Parameters provided in datasheets and / or specifications may vary in different applications and performance may vary over time. All operating parameters, including typical parameters, must be validated for each customer application by the customer's technical experts. Product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein.

Hyperlinks included in this datasheet may direct users to third-party websites. These links are provided as a convenience and for informational purposes only. Inclusion of these hyperlinks does not constitute an endorsement or an approval by Vishay of any of the products, services or opinions of the corporation, organization or individual associated with the third-party website. Vishay disclaims any and all liability and bears no responsibility for the accuracy, legality or content of the third-party website or for that of subsequent links.

Vishay products are not designed for use in life-saving or life-sustaining applications or any application in which the failure of the Vishay product could result in personal injury or death unless specifically qualified in writing by Vishay. Customers using or selling Vishay products not expressly indicated for use in such applications do so at their own risk. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay. Product names and markings noted herein may be trademarks of their respective owners.