

WT-BASE LS HF 4 BK - Cable binder base



3240707

<https://www.phoenixcontact.com/us/products/3240707>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.

Cable binder base, for cable binders up to 4 mm wide, self-adhesive (rubber) and screwable, 4 mm fixing hole, 4-sided cable binder feed-through



Commercial data

| | |
|--------------------------------------|---------------|
| Item number | 3240707 |
| Packing unit | 100 pc |
| Minimum order quantity | 100 pc |
| Sales key | BE07 |
| Product key | BE713Z |
| GTIN | 4046356703949 |
| Weight per piece (including packing) | 0.682 g |
| Weight per piece (excluding packing) | 0.696 g |
| Customs tariff number | 39269097 |
| Country of origin | HR |

WT-BASE LS HF 4 BK - Cable binder base



3240707

<https://www.phoenixcontact.com/us/products/3240707>

Technical data

Product properties

| | |
|----------------------|-----------|
| Product type | Cable tie |
| Type | Fixing |
| Tensile strength GRP | 120 N |

Dimensions

| | |
|------------------------|--------|
| Width | 19 mm |
| Height | 5 mm |
| Length | 19 mm |
| Hole diameter | 4.1 mm |
| Diameter mounting hole | 4 mm |

Internal dimensions

| | |
|--------------|------|
| Width_inside | 4 mm |
|--------------|------|

Material specifications

| | |
|--|--------------------------------|
| Color | black (RAL 9005) |
| Material | ABS |
| Flammability rating according to UL 94 | HB |
| Components | free from silicone and halogen |

Cable/line

| | |
|------------------|-------|
| Tensile strength | 120 N |
|------------------|-------|

Environmental and real-life conditions

Ambient conditions

| | |
|---------------------------------|------------------|
| Ambient temperature (operation) | -40 °C ... 60 °C |
| Ambient temperature (assembly) | 15 °C ... 40 °C |

Mounting

| | |
|---------------|----------------|
| Mounting type | Screw mounting |
| | adhesive |

WT-BASE LS HF 4 BK - Cable binder base



3240707

<https://www.phoenixcontact.com/us/products/3240707>

Classifications

ECLASS

| | |
|-------------|----------|
| ECLASS-13.0 | 23159090 |
|-------------|----------|

ETIM

| | |
|----------|----------|
| ETIM 9.0 | EC011571 |
|----------|----------|

UNSPSC

| | |
|-------------|----------|
| UNSPSC 21.0 | 39121700 |
|-------------|----------|

WT-BASE LS HF 4 BK - Cable binder base



3240707

<https://www.phoenixcontact.com/us/products/3240707>

Environmental product compliance

| | |
|---|--|
| EU RoHS | |
| Fulfills EU RoHS substance requirements | Yes, No exemptions |
| China RoHS | |
| Environment friendly use period (EFUP) | EFUP-E |
| | No hazardous substances above the limits |
| EU REACH SVHC | |
| REACH candidate substance (CAS No.) | No substance above 0.1 wt% |

Phoenix Contact 2025 © - all rights reserved
<https://www.phoenixcontact.com>

Phoenix Contact USA
586 Fulling Mill Road
Middletown, PA 17057, United States
(+717) 944-1300
info@phoenixcon.com