

Specifications

Eaton 14101RQD03

Eaton Comet 18mm tubular photoelectric sensor, Polarized Retroreflective, Right Angle, Output ON, Dual key micro, 300 mA AC/DC at 20-264 Vac/15-30 Vdc, 4 pin, AC: L1 switched, DC: NPN open collector, 20-264 Vac 50/60 Hz, 15-30 Vdc (NPN)



General specifications

PRODUCT NAME	Eaton Comet 18mm tubular photoelectric sensor
CATALOG NUMBER	14101RQD03
UPC	782113846675
PRODUCT LENGTH/DEPTH	3 in
PRODUCT HEIGHT	0.71 in
PRODUCT WIDTH	0.47 in
PRODUCT WEIGHT	0.7 lb
WARRANTY	3 year
CERTIFICATIONS	UL Recognized cUL Recognized



Powering Business Worldwide

Product specifications

CONTACT RATING	300 mA AC/DC at 20-264 Vac/15-30 Vdc
ENCLOSURE MATERIAL	Polyurethane foam (RIM)
CONNECTION	Dual key micro
CONTACT CONFIGURATION	AC: L1 switched DC: NPN open collector
SENSOR TYPE	Polarized retroreflective
INPUT VOLTAGE	20-264 Vac at 50/60 Hz, 15-30 Vdc (NPN)
LED INDICATOR	Output ON
NUMBER OF PINS	4
PROTECTION	Latching short circuit
MAXIMUM AC CURRENT	300 mA
MAXIMUM DC CURRENT	300 mA
OPERATING TEMPERATURE - MAX	158 °F
OPERATING TEMPERATURE - MIN	-40 °F
ENVIRONMENTAL RATING	NEMA 1, NEMA 3, NEMA 4, NEMA 4X, NEMA 6, NEMA 12, NEMA 13, IP69K

Resources

[Product Range Catalog Sensors – products, basic information, applications](#)

CATALOGS

[Sensing Solutions, Photoelectric Sensor, Volume 8, Tab 5](#)

SPECIFICATIONS AND DATASHEETS

[Eaton Specification Sheet - 14101RQD03](#)

PROJECT NAME:

PROJECT NUMBER:

PREPARED BY:

DATE:



Eaton Corporation plc

Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

Follow us on social media to get the latest product and support information.



© 2025 Eaton. All Rights Reserved.