

Specifications



Photo is representative

Eaton 11155AA07

Eaton OEM Prism 18mm tubular photoelectric sensor, Photoelectric, 0.71 diameter, Forward Viewing, Sensor distance: 20 Ft., Lens: polycarbonate cable jacket: PVC body: structural polyurethane foam enclosure, 10-30 Vdc input

General specifications

PRODUCT NAME	Eaton OEM Prism 18mm tubular photoelectric sensor
CATALOG NUMBER	11155AA07
UPC	782113056623
PRODUCT LENGTH/DEPTH	0.47 in
PRODUCT HEIGHT	2.35 in
PRODUCT WIDTH	0.71 in
PRODUCT WEIGHT	0.1313 lb
WARRANTY	3 year
COMPLIANCES	CE Marked
CERTIFICATIONS	cUL Recognized UL Recognized
CATALOG NOTES	Synchronous design requires source and detector to be wired to each other



Powering Business Worldwide

Product specifications

CABLE TYPE	Polyvinyl Chloride (PVC)
ENCLOSURE MATERIAL	Cable jacket: PVC Lens: polycarbonate Body: structural polyurethane foam
OPERATING MODE	Thru-beam
SENSOR TYPE	Through beam
SWITCH TYPE	Photoelectric
INPUT VOLTAGE	10-30 Vdc
LED INDICATOR	Power on: red
CORD LENGTH	8 in
OPERATING TEMPERATURE - MAX	131 °F
OPERATING TEMPERATURE - MIN	-13 °F
ENVIRONMENTAL RATING	NEMA 1, NEMA 3, NEMA 4, NEMA 4X, NEMA 6, NEMA 6P, NEMA 12, NEMA 13

Resources

CATALOGS	Sensing Solutions, Photoelectric Sensor, Volume 8, Tab 5
SPECIFICATIONS AND DATASHEETS	Eaton Specification Sheet - 11155AA07

PROJECT NAME:

PROJECT NUMBER:

PREPARED BY:

DATE:



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

Follow us on social media to get the latest product and support information.



© 2025 Eaton. All Rights Reserved.