

Specifications

Eaton 13106R6513



Photo is representative

Eaton Comet 18mm tubular photoelectric sensor, Right Angle, Sensor dist 8 in, 300 mA max AC L1 switched/DC NPN open coll, 300 mA AC/DC at 20-264Vac/15-30Vdc, 6.6 Ft.(2m) Cable, 20-264 Vac/15-30 Vdc input, Diffuse Reflective, 6.6 Ft.(2m)

General specifications

PRODUCT NAME	Eaton Comet 18mm tubular photoelectric sensor
CATALOG NUMBER	13106R6513
UPC	782113823478
PRODUCT LENGTH/DEPTH	0.47 in
PRODUCT HEIGHT	2.55 in
PRODUCT WIDTH	0.71 in
PRODUCT WEIGHT	0.2875 lb
WARRANTY	3 year
COMPLIANCES	CE Marked
CERTIFICATIONS	cUL Recognized UL Recognized



Powering Business Worldwide

Product specifications

CONTACT RATING	300 mA AC/DC at 20-264Vac/15-30Vdc
CABLE TYPE	Polyvinyl Chloride (PVC)
ENCLOSURE MATERIAL	Body: structural polyurethane foam Lens: polycarbonate Cable jacket: PVC
OPERATING MODE	Diffuse reflective
CONNECTION	6.6 ft (2 m) cable
CONTACT CONFIGURATION	DC: NPN open collector AC: L1 switched
SENSOR TYPE	Diffuse reflective
SWITCH TYPE	Photoelectric
INPUT VOLTAGE	20-264 Vac, 15-30 Vdc
LED INDICATOR	Output status: red
PROTECTION	Latching short circuit
CORD LENGTH	79.2 ft
MAXIMUM AC CURRENT	300 mA
MAXIMUM DC CURRENT	300 mA
OPERATING TEMPERATURE - MAX	158 °F
OPERATING TEMPERATURE - MIN	-40 °F
ENVIRONMENTAL RATING	NEMA 1, NEMA 3, NEMA 4, NEMA 4X, NEMA 6, NEMA 6P, NEMA 12, NEMA 13, IP68, IP69K

Resources

CATALOGS	Product Range Catalog Sensors – products, basic information, applications Sensing Solutions, Photoelectric Sensor, Volume 8, Tab 5
SPECIFICATIONS AND DATASHEETS	Eaton Specification Sheet - 13106R6513

PROJECT NAME:

PROJECT NUMBER:

PREPARED BY:

DATE:



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

Follow us on social media to get the latest product and support information.



© 2025 Eaton. All Rights Reserved.