

Specifications



Eaton 1450E-6547

Eaton Photoelectric Sensor, Retroreflective, Forward Viewing, Output (green), power (yellow), alignment (red), M12, 250 mA at 10-40 Vdc, 4 pin, NPN/PNP open collector outputs, 10-40 Vdc

General specifications

PRODUCT NAME	Eaton Enhanced 50 photoelectric sensor
CATALOG NUMBER	1450E-6547
UPC	782116111053
PRODUCT LENGTH/DEPTH	4.01 in
PRODUCT HEIGHT	1.81 in
PRODUCT WIDTH	1.91 in
PRODUCT WEIGHT	0.41 lb
WARRANTY	3 year
COMPLIANCES	CE Marked
CERTIFICATIONS	CSA Certified



Powering Business Worldwide

Product specifications

CONTACT RATING	250 mA at 10-40 Vdc
ENCLOSURE MATERIAL	Fiberglass reinforced plastic
CONNECTION	M12
CONTACT CONFIGURATION	NPN/PNP open collector
SENSOR TYPE	Retroreflective
INPUT VOLTAGE	10-40 Vdc
LED INDICATOR	Output: green Alignment: red Power: yellow
NUMBER OF PINS	4
PROTECTION	Output short circuit, overcircuit and reverse polarity
MAXIMUM DC CURRENT	250 mA
OPERATING TEMPERATURE - MAX	131 °F
OPERATING TEMPERATURE - MIN	-13 °F
ENVIRONMENTAL RATING	IP67, IP69K

Resources

CATALOGS	Sensing Solutions, Photoelectric Sensor, Volume 8, Tab 5
SPECIFICATIONS AND DATASHEETS	Eaton Specification Sheet - 1450E-6547

PROJECT NAME:

PROJECT NUMBER:

PREPARED BY:

DATE:



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

Follow us on social media to get the latest product and support information.



© 2025 Eaton. All Rights Reserved.