

Specifications

Eaton 13104AF1217



Photo is representative

Eaton Comet 18mm tubular photoelectric sensor, Forward Viewing, Sensor dist 2 in, 100 mA PNP, 250 mA NPN max DC, NPN/PNP Open coll, 100 mA PNP, 250 mA NPN at 10-30 Vdc, 12 Ft(3.7m) Cable, 10-30 Vdc input, Background Suppression

General specifications

PRODUCT NAME	Eaton Comet 18mm tubular photoelectric sensor
CATALOG NUMBER	13104AF1217
UPC	782113930725
PRODUCT LENGTH/DEPTH	0.47 in
PRODUCT HEIGHT	2.6 in
PRODUCT WIDTH	0.71 in
PRODUCT WEIGHT	0.2875 lb
WARRANTY	3 year
COMPLIANCES	Contact Manufacturer



Powering Business Worldwide

Product specifications

CONTACT RATING	100 mA PNP, 250 mA NPN at 10-30 Vdc
CABLE TYPE	Polyvinyl Chloride (PVC)
ENCLOSURE MATERIAL	Lens: polycarbonate Body: structural polyurethane foam Cable jacket: PVC
OPERATING MODE	Background suppression
CONNECTION	12 ft (3.7 m) cable
CONTACT CONFIGURATION	NPN and PNP open collector
SENSOR TYPE	Back ground suppression
SWITCH TYPE	Photoelectric
INPUT VOLTAGE	10-30 Vdc
LED INDICATOR	Output status: red
PROTECTION	Auto reset short circuit
CORD LENGTH	144 ft
MAXIMUM DC CURRENT	100 mA PNP, 250 mA NPN
OPERATING TEMPERATURE - MAX	158 °F
OPERATING TEMPERATURE - MIN	-40 °F
ENVIRONMENTAL RATING	NEMA 1, NEMA 3, NEMA 4, NEMA 4X, NEMA 6, NEMA 6P, NEMA 12, NEMA 13, IP68, IP69K

Resources

CATALOGS	Product Range Catalog Sensors – products, basic information, applications
SPECIFICATIONS AND DATASHEETS	Eaton Specification Sheet - 13104AF1217

PROJECT NAME:

PROJECT NUMBER:

PREPARED BY:

DATE:



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

Follow us on social media to get the latest product and support information.



© 2025 Eaton. All Rights Reserved.