

Specifications

Eaton 13101AS3342



Photo is representative

Eaton Comet 18mm tubular photoelectric sensor, Back Ground Suppression, Forward Viewing, Background suppression, Output ON, 12 ft cable, 6.6 ft, 100 mA PNP, 250 mA NPN at 10-30 Vdc, PVC, NPN and PNP open collector, 10-30 Vdc

General specifications

PRODUCT NAME	Eaton Comet 18mm tubular photoelectric sensor
CATALOG NUMBER	13101AS3342
UPC	786685473475
PRODUCT LENGTH/DEPTH	2.6 in
PRODUCT HEIGHT	0.71 in
PRODUCT WIDTH	0.47 in
PRODUCT WEIGHT	0.58 lb
WARRANTY	3 year
CERTIFICATIONS	UL Listed cUL Listed CE

Product specifications

CONTACT RATING	100 mA PNP, 250 mA NPN at 10-30 Vdc
CABLE TYPE	Polyvinyl Chloride (PVC)
ENCLOSURE MATERIAL	Polyurethane foam (RIM)
OPERATING MODE	Background suppression
CONNECTION	12 ft cable
CONTACT CONFIGURATION	NPN and PNP open collector
SENSOR TYPE	Back ground suppression
INPUT VOLTAGE	10-30 Vdc
LED INDICATOR	Output ON
PROTECTION	Auto reset short circuit
CORD LENGTH	79.2 ft
MAXIMUM DC CURRENT	100 mA PNP, 250 mA NPN
OPERATING TEMPERATURE - MAX	158 °F
OPERATING TEMPERATURE - MIN	-40 °F
ENVIRONMENTAL RATING	NEMA 1, NEMA 3, NEMA 4, NEMA 4X, NEMA 6, NEMA 12, NEMA 13, IP69K

Resources

CATALOGS	Product Range Catalog Sensors – products, basic information, applications
	Sensing Solutions, Photoelectric Sensor, Volume 8, Tab 5
SPECIFICATIONS AND DATASHEETS	Eaton Specification Sheet - 13101AS3342

PROJECT NAME:

PROJECT NUMBER:

PREPARED BY:

DATE:



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

Follow us on social media to get the latest product and support information.



© 2025 Eaton. All Rights Reserved.