

Specifications



Photo is representative

Eaton 12155AD07

Eaton OEM Prism 18mm tubular photoelectric sensor, Forward Viewing, Sensor distance: 20 Ft., Iso SS Relay, 80 mA at 132 Vac/110 mA at 132Vdc, 4 Pin M12 Connector, 10-30 Vdc input, Current Limited for loads > 32V AC/DC, Thru-beam

General specifications

PRODUCT NAME	Eaton OEM Prism 18mm tubular photoelectric sensor
CATALOG NUMBER	12155AD07
UPC	782113056692
PRODUCT LENGTH/DEPTH	0.47 in
PRODUCT HEIGHT	2.35 in
PRODUCT WIDTH	0.71 in
PRODUCT WEIGHT	0.1313 lb
WARRANTY	3 year
COMPLIANCES	CE Marked
CERTIFICATIONS	UL Recognized cUL Recognized
CATALOG NOTES	Synchronous design requires source and detector to be wired to each other



Powering Business Worldwide

Product specifications

CONTACT RATING	80 mA at 132 Vac / 110 mA at 132Vdc
CABLE TYPE	Polyvinyl Chloride (PVC)
ENCLOSURE MATERIAL	Cable jacket: PVC Body: structural polyurethane foam Lens: polycarbonate
OPERATING MODE	Thru-beam
CONNECTION	4-pin M12 connector
CONTACT CONFIGURATION	Isolated solid state relay
SENSOR TYPE	Through beam
SWITCH TYPE	Photoelectric
INPUT VOLTAGE	10-30 Vdc
LED INDICATOR	Output status: red
PROTECTION	Current limited for loads less than 32 Vac/dc
CORD LENGTH	8 in
MAXIMUM AC CURRENT	80 mA
MAXIMUM DC CURRENT	110 mA
OPERATING TEMPERATURE - MAX	131 °F
OPERATING TEMPERATURE - MIN	-13 °F
ENVIRONMENTAL RATING	NEMA 1, NEMA 3, NEMA 4, NEMA 4X, NEMA 6, NEMA 6P, NEMA 12, NEMA 13

Resources

CATALOGS	Sensing Solutions, Photoelectric Sensor, Volume 8, Tab 5
SPECIFICATIONS AND DATASHEETS	Eaton Specification Sheet - 12155AD07

PROJECT NAME:

PROJECT NUMBER:

PREPARED BY:

DATE:



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

Follow us on social media to get the latest product and support information.



© 2025 Eaton. All Rights Reserved.