

# Specifications



Photo is representative



## Eaton 170E8882

Fuse-link, high speed, 160 A, DC 4000 V, size 2, 75 x 86 x 414 mm, aR, IEC, with indicator

### General specifications

<b>PRODUCT NAME</b>	Eaton Bussmann series high speed traction fuse
<b>CATALOG NUMBER</b>	170E8882
<b>UPC</b>	051712534345
<b>EAN</b>	5996516001974
<b>PRODUCT LENGTH/DEPTH</b>	414 mm
<b>PRODUCT HEIGHT</b>	86 mm
<b>PRODUCT WIDTH</b>	75 mm
<b>PRODUCT WEIGHT</b>	2.8 kg
<b>COMPLIANCES</b>	EAC
<b>CERTIFICATIONS</b>	IEC
<b>GLOBAL CATALOG</b>	170E8882



Powering Business Worldwide

## Product specifications

<b>AMPERAGE RATING</b>	160 A
<b>ACCESSORIES</b>	170H3036 Type K indicator
<b>BREAKING CAPACITY</b>	60 kA
<b>VOLTAGE TYPE</b>	DC
<b>UTILIZATION CATEGORY</b>	aR (accompanied semiconductor protection)
<b>FUSE INDICATOR</b>	Top fuse status indicator
<b>FUSE SIZE</b>	2
<b>CLASS</b>	Class aR
<b>WATT LOSSES</b>	182 W
<b>FUSE SHAPE</b>	Square body, offset bolted tags
<b>MOUNTING DIMENSION</b>	M8
<b>CENTER-TO-CENTER DISTANCE OF CONNECTIONS</b>	393 mm
<b>CURRENT TYPE</b>	DC
<b>RATED VOLTAGE DC</b>	4000 V
<b>COLOR</b>	None
<b>INTERRUPT RATING</b>	60 kAIC
<b>CONSTRUCTION SIZE</b>	2
<b>PACKAGING TYPE</b>	Standard
<b>VOLTAGE RATING</b>	4000 V
<b>TYPE</b>	Fuse
<b>APPLICATION</b>	traction
<b>FITTED WITH:</b>	Double slot tags
<b>FUSE SYSTEM (ACCORDING TO IEC 60269)</b>	Other

**PROJECT NAME:**

**PROJECT NUMBER:**

**PREPARED BY:**

**DATE:**

## Resources

<b>CATALOGS</b>	<a href="#">Traction fuse-links</a>
<b>MCAD MODEL</b>	<a href="#">eaton-traction-fuses-mcad-3d-models-170x0424.stp</a>



**Eaton Corporation plc**  
Eaton House  
30 Pembroke Road  
Dublin 4, Ireland  
Eaton.com

Follow us on social media to get the latest product and support information.



© 2025 Eaton. All Rights Reserved.