

Specifications



Eaton 170L9222

Fuse-link, high speed, 700 A, AC 2000 V, Size 3, 74 x 90 x 143 mm, aR, IEC, single indicator

General specifications

PRODUCT NAME	Eaton Bussmann series high speed square body fuse
CATALOG NUMBER	170L9222
UPC	051712805964
EAN	5996516008928
PRODUCT LENGTH/DEPTH	168 mm
PRODUCT HEIGHT	76 mm
PRODUCT WIDTH	95 mm
PRODUCT WEIGHT	2168 g
CERTIFICATIONS	IEC 60269-4
GLOBAL CATALOG	170L9222



Powering Business Worldwide

Product specifications

AMPERAGE RATING	700 A
BREAKING CAPACITY	100 kA
FUSE INDICATOR	Centre fuse status indicator
INSULATED METAL GRIPPING LUGS (IMGL)	No
UTILIZATION CATEGORY	aR (accompanied semiconductor protection)
VOLTAGE TYPE	AC
FUSE SIZE	3
RATED VOLTAGE AC	2000 V
CENTER-TO-CENTER DISTANCE OF CONNECTIONS	143 mm
CURRENT TYPE	AC
MOUNTING DIMENSION	M12
CLASS	Class aR
WATT LOSSES	200 W
FUSE SHAPE	Square body, flush end contacts
COLOR	None
CONSTRUCTION SIZE	3
PACKAGING TYPE	Standard
VOLTAGE RATING	2000 V
TYPE	Fuse
APPLICATION	semiconductor protection
FUSE TYPE	Flush end
FUSE SYSTEM (ACCORDING TO IEC 60269)	IEC 60269-4 flush end connections type A

PROJECT NAME:

PROJECT NUMBER:

PREPARED BY:

DATE:

Resources

CATALOGS	eaton-bussmann-series-iec-high-speed-fuses-catalogue-ca135001en-en-gb.pdf
MANUALS AND USER GUIDES	High speed fuses application guide
MCAD MODEL	eaton-hs-square-body-fuses-mcad-3d-models-u0223.stp
PRODUCT NOTIFICATIONS	eaton-bussmann-series-170m-fuses-product-change-notice-pcn-bur-00193-en-us.pdf eaton-bussmann-series-ukca-marking-high-speed-fuses-pcn-bur-00167-en-gb.pdf



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

Follow us on social media to get the latest product and support information.

