

# Specifications



## Eaton 25KBR20

Expulsion fuse-link, medium voltage, 20 A, AC 25 kV, 660 mm, ANSI, K fast, style BR termination

### General specifications

<b>PRODUCT NAME</b>	Eaton Bussmann series medium voltage expulsion fuse
<b>CATALOG NUMBER</b>	25KBR20
<b>MODEL CODE</b>	25KV 20A REMOVABLE B/H EXPULSION LINK
<b>UPC</b>	051712296380
<b>EAN</b>	5027590470476
<b>PRODUCT LENGTH/DEPTH</b>	225 mm
<b>PRODUCT HEIGHT</b>	76 mm
<b>PRODUCT WIDTH</b>	106 mm
<b>PRODUCT WEIGHT</b>	42.6 g
<b>COMPLIANCES</b>	ANSI C37.42
<b>GLOBAL CATALOG</b>	25KBR20



Powering Business Worldwide

## Product specifications

<b>AMPERAGE RATING</b>	20 A
<b>CURRENT CHARACTERISTIC TYPE</b>	Type K - Complies with ANSI C 37-42 requirements for fast acting K Characteristics
<b>RATED FREQUENCY - MAX</b>	60 Hz
<b>RATED FREQUENCY - MIN</b>	50 Hz
<b>RELEASE CHARACTERISTIC</b>	K
<b>STANDARD</b>	ANSI
<b>TYPE OF TERMINATION</b>	Removable buttonhead
<b>VOLTAGE TYPE</b>	AC
<b>COLOR</b>	Yellow
<b>INTERRUPT RATING</b>	8 kAIC
<b>CONSTRUCTION SIZE</b>	660 mm
<b>VOLTAGE RATING</b>	25 kV
<b>TYPE</b>	Medium Voltage Expulsion Fuse Link
<b>APPLICATION</b>	Primary side transformer protection, feeder protection, capacitor bank protection

## Resources

**PROJECT NAME:**

**PROJECT NUMBER:**

**PREPARED BY:**

**DATE:**



**Eaton Corporation plc**  
Eaton House  
30 Pembroke Road  
Dublin 4, Ireland  
Eaton.com

Follow us on social media to get the latest product and support information.



© 2025 Eaton. All Rights Reserved.