

Product specifications

AMPERAGE RATING	315 A
BREAKING CAPACITY	100 kA
UTILIZATION CATEGORY	gR (general purpose semiconductor protection)
FUSE INDICATOR	Top fuse status indicator
FUSE SIZE	2
CLASS	Class gR
WATT LOSSES	57 W
PRE ARC (I2T)	28000
MOUNTING DIMENSION	M10
CENTER-TO-CENTER DISTANCE OF CONNECTIONS	129 mm
CURRENT TYPE	DC
RATED VOLTAGE DC	750 V
COLOR	None
INTERRUPT RATING	100 kAIC
CONSTRUCTION SIZE	2
PACKAGING TYPE	Standard
VOLTAGE RATING	750 V
TYPE	Fuse
FUSE SYSTEM (ACCORDING TO IEC 60269)	Other

PROJECT NAME:

PROJECT NUMBER:

PREPARED BY:

DATE:

Resources

CATALOGS	Traction fuse-links
DECLARATIONS OF CONFORMITY	eaton-high-speed-square-body-fuse-declaration-of-conformity-uk251153en.pdf eaton-high-speed-square-body-fuse-declaration-of-conformity-eu250670en.pdf
MCAD MODEL	eaton-traction-fuses-mcad-3d-models-u0515.stp



Eaton Corporation plc

Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

Follow us on social media to get the latest product and support information.

