


## 12.5 mm Modular High Torque Panel Potentiometer



### FEATURES

- Keep the setting under high mechanical constraints (vibrations, shocks, ...)
- High torque (8 Ncm) with smooth feeling during all potentiometer life
- Torque stability under high environmental constraints
- 12.5 mm square single turn panel control with 6.35 mm shaft diameters
- Custom designs upon request
- Compact, versatile, modular, and robust
- Tests according to CECC 41000 or IEC 60393-1
- Material categorization: for definitions of compliance please see [www.vishay.com/doc?99912](http://www.vishay.com/doc?99912)


**RoHS**  
COMPLIANT

### LINKS TO ADDITIONAL RESOURCES





3D Models


Capabilities and  
Custom Options


### QUICK REFERENCE DATA

|                         |                 |
|-------------------------|-----------------|
| Multiple module         | Up to 7 modules |
| Switch module           | Yes             |
| Detent module           | n/a             |
| Special electrical laws | A: linear       |
| Sealing level           | IP 64           |
| Lifespan                | 50K cycles      |

### CONFIGURATION EXAMPLE - Dimensions in millimeters (inches) $\pm 0.5$ mm ( $\pm 0.02$ " )

**EXAMPLE: P11H1F0GHFW10102KA**

**Shaft view at middle travel**

**CONFIGURATION EXAMPLE** - Dimensions in millimeters (inches)  $\pm 0.5$  mm ( $\pm 0.02$ " )

**EXAMPLE: P11H1F0GHFY00102KA**

**CUSTOM CAPABILITIES**

P11H model can be fully customized:




- Custom shafts
- Switch option
- Connector and wire
- Special leads
- Special taper
- One to 7 modules
- ...

When special shafts are required (special shaft lengths, diameter etc.) a drawing is required.

Hardware supplied in separate bags.



## GENERAL SPECIFICATIONS

| ELECTRICAL (initial)                                               |                                                                                                                                                                                                                              |
|--------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Resistive element                                                  | Cermet element                                                                                                                                                                                                               |
| Electrical travel                                                  | $270^\circ \pm 10^\circ$                                                                                                                                                                                                     |
| Resistance range <sup>(1)</sup>                                    | 1 k $\Omega$ , 4.7 k $\Omega$ , 10 k $\Omega$ , 47 k $\Omega$ , 100 k $\Omega$ , 100 $\Omega$ , 220 $\Omega$ , 50 $\Omega$ , 2.2 k $\Omega$ , 22 k $\Omega$ , 50 k $\Omega$ , 220 k $\Omega$ , 500 k $\Omega$ , 1 M $\Omega$ |
| Tolerance                                                          | 5 % (on request), $\pm 10$ %, $\pm 20$ %                                                                                                                                                                                     |
| Taper standard law: A (linear)<br>(other custom laws upon request) |                                                                                                                                            |
| Circuit diagram                                                    |                                                                                                                                           |
| Power rating at 70 °C                                              | <p>1 W for single module or 0.5 W per module</p>                                                                                         |
| Temperature coefficient (typical)                                  | $\pm 150$ ppm                                                                                                                                                                                                                |
| Limiting element voltage                                           | 350 V                                                                                                                                                                                                                        |
| End resistance (typical)                                           | 2 $\Omega$                                                                                                                                                                                                                   |
| Contact resistance variation (typical)                             | 2 % or 3 $\Omega$                                                                                                                                                                                                            |
| Independent linearity (typical)                                    | $\pm 5$ %                                                                                                                                                                                                                    |
| Insulation resistance                                              | $10^6$ M $\Omega$ min.                                                                                                                                                                                                       |
| Dielectric strength                                                | 1500 V <sub>RMS</sub> min.                                                                                                                                                                                                   |
| Mechanical endurance                                               | 50 000 cycles                                                                                                                                                                                                                |

## Note

<sup>(1)</sup> Consult Vishay Sfernice for other ohmic values



| MECHANICAL (initial)       |                                                |
|----------------------------|------------------------------------------------|
| Mechanical travel          | 300° ± 5°                                      |
| Operating torque (typical) | 8 Ncm ± 3 Ncm (7.08 oz.-inch to 15.6 oz.-inch) |
| End stop torque            | 80 Ncm max. (6.8 lb-inch max.)                 |
| Tightening torque          | 250 Ncm max. (21 lb-inch max.)                 |
| Weight                     | 7 g to 9 g per module (0.25 oz. to 0.32 oz.)   |

| ENVIRONMENTAL               |                   |
|-----------------------------|-------------------|
| Operating temperature range | -55 °C to +125 °C |
| Climatic category           | 55 / 125 / 56     |
| Sealing                     | IP64              |

| MARKING                                                                                                                                           |
|---------------------------------------------------------------------------------------------------------------------------------------------------|
| Potentiometer module Vishay logo, SAP code of ohmic value and tolerance in %, variation law, manufacturing date (four digits), "3" for the lead 3 |

| PACKAGING |
|-----------|
| • Box     |

| PERFORMANCES            |                                                              |                                                                        |                                   |
|-------------------------|--------------------------------------------------------------|------------------------------------------------------------------------|-----------------------------------|
| TESTS                   | CONDITIONS                                                   | TYPICAL VALUE AND DRIFTS                                               |                                   |
| Electrical endurance    | 1000 h at rated power<br>90'/30' at ambient temp. 70 °C      | $\Delta R_T/R_T$                                                       | ± 2 %                             |
|                         |                                                              | Contact resistance variation                                           | ± 4 %                             |
| Change of temperature   | 5 cycles, -55 °C to +125 °C, 30' per cycle                   | $\Delta R_T/R_T$<br>Operating torque                                   | ± 0.2 %<br>> 2 Ncm (2.8 oz.-inch) |
|                         | Severe stress: 90 cycles, -40 °C to +80 °C,<br>4 h per cycle | $\Delta$ Operating torque / torque (%)                                 | < 35 %                            |
| Damp heat, steady state | +40 °C, 93 % relative humidity, 56 days                      | $\Delta R_T/R_T$                                                       | ± 2 %                             |
|                         |                                                              | Insulation resistance<br>$\Delta$ Operating torque / torque (%)        | > 1000 MΩ<br>< 20 %               |
| Mechanical endurance    | 50 000 cycles                                                | $\Delta R_T/R_T$                                                       | ± 5 %                             |
|                         |                                                              | Contact resistance variation<br>$\Delta$ Operating torque / torque (%) | ± 5 %<br>> 5 Ncm                  |
| Shock                   | 50 g, 11 ms<br>3 shocks - 3 directions                       | $\Delta R_T/R_T$                                                       | ± 0.2 %                           |
|                         |                                                              | $\Delta R_{1-2}/R_{1-2}$<br>$\Delta$ Operating torque / torque (%)     | ± 0.5 %<br>< 13 %                 |
| Vibration               | 10 Hz to 55 Hz<br>0.75 mm or 10 g, 6 h                       | $\Delta R_T/R_T$                                                       | ± 0.2 %                           |
|                         |                                                              | $\Delta V_{1-2}/V_{1-3}$<br>$\Delta$ Operating torque / torque (%)     | ± 0.5 %<br>< 11 %                 |

**Note**

- Nothing stated herein shall be construed as a guarantee of quality or durability

| ORDERING INFORMATION (part number) |                                 |   |         |                                                                  |   |                                    |             |                                                                                         |   |                                                                                                                                                                                                                                 |   |   |                                                           |   |                           |   |   |
|------------------------------------|---------------------------------|---|---------|------------------------------------------------------------------|---|------------------------------------|-------------|-----------------------------------------------------------------------------------------|---|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---|---|-----------------------------------------------------------|---|---------------------------|---|---|
| P                                  | 1                               | 1 | H       | 1                                                                | F | 0                                  | G           | H                                                                                       | F | W                                                                                                                                                                                                                               | 1 | 0 | 1                                                         | 0 | 3                         | K | A |
| MODEL                              | NUMBER OF MODULES               |   | BUSHING | LOCATION PEG                                                     |   | SHAFT                              | SHAFT STYLE | LEADS                                                                                   |   | RESISTANCE CODE                                                                                                                                                                                                                 |   |   | TOLERANCE                                                 |   | TAPER OR SPECIAL          |   |   |
| P11H                               | 1<br>2<br>3<br>4<br>5<br>6<br>7 |   | F       | A, B, C, D =<br>see "Location Pegs" table<br><br>0 = without peg |   | GH<br><br>AP =<br>particular shaft | F           | W10 = vertical mounting,<br>PCB pin<br>Y00 = solder lugs<br><br>Other styles on request |   | 102 = 1 kΩ<br>472 = 4.7 kΩ<br>502 = 5 kΩ<br>103 = 10 kΩ<br>473 = 47 kΩ<br>104 = 100 kΩ<br>101 = 100 Ω<br>221 = 220 Ω<br>501 = 500 Ω<br>222 = 2.2 kΩ<br>223 = 22 kΩ<br>503 = 50 kΩ<br>224 = 220 kΩ<br>504 = 500 kΩ<br>105 = 1 MΩ |   |   | M = ± 20 %<br>K = ± 10 %<br><u>On request:</u><br>J = 5 % |   | A<br><br>Other on request |   |   |
| OR SPECIAL CODE                    |                                 |   |         |                                                                  |   |                                    |             |                                                                                         |   |                                                                                                                                                                                                                                 |   |   |                                                           |   |                           |   |   |

### SPECIAL CODES GIVEN BY VISHAY


Options available:

- Custom shaft
- Specific linearity, interlinearity, taper
- Multiple assemblies with various modules
- Wires, connectors
- Switch modules
- PCB adding
- Custom design on request

### STANDARD RESISTANCE ELEMENT DATA

| STANDARD RESISTANCE VALUES | MAX. POWER AT 70 °C | MAX. WORKING VOLTAGE | MAX. WIPER CURRENT |
|----------------------------|---------------------|----------------------|--------------------|
| Ω                          | W                   | V                    | mA                 |
| 1K                         | 1                   | 31.6                 | 31.6               |
| 4.7K                       | 1                   | 69                   | 14.5               |
| 10K                        | 1                   | 100                  | 10                 |
| 47K                        | 1                   | 21.7                 | 46.1               |
| 100K                       | 1                   | 31.6                 | 31.6               |
| 100                        | 1                   | 10                   | 100                |
| 220                        | 1                   | 14.8                 | 67.4               |
| 470                        | 1                   | 21.7                 | 46.1               |
| 500                        | 1                   | 22.4                 | 44.7               |
| 1K                         | 1                   | 31.6                 | 31.6               |
| 2.2K                       | 1                   | 46.9                 | 21.3               |
| 4.7K                       | 1                   | 69                   | 14.5               |
| 5K                         | 1                   | 70.7                 | 14.1               |
| 10K                        | 1                   | 100                  | 10.0               |
| 22K                        | 1                   | 148                  | 6.74               |
| 47K                        | 1                   | 217                  | 4.61               |
| 50K                        | 1                   | 224                  | 4.47               |
| 100K                       | 1                   | 316                  | 3.16               |
| 220K                       | 0.56                | 350                  | 1.59               |
| 470K                       | 0.26                | 350                  | 0.75               |
| 500K                       | 0.25                | 350                  | 0.70               |
| 1M                         | 0.12                | 350                  | 0.35               |


### PANEL CUT OUT (± 0.5 mm)



**LOCATING PEGS (anti-rotation lug)**






The locating peg is provided by a plate mounted on the bushing and positioned by the module sides. Four set positions are available, clock face orientation: 12, 3, 6, 9.

All P11 bushings have a double flat. When panel mounting holes have been punched accordingly, an anti-rotation lug is not necessary.




| CODE | VERSION | BUSHING | EFFECTIVE HIGH PEG |
|------|---------|---------|--------------------|
| A    | Ø d mm  | 2       | 0.7                |
|      | L mm    | 6.2     |                    |
| B    | Ø d mm  | 2       | 0.7                |
|      | L mm    | 7.75    |                    |
| C    | Ø d mm  | 3.5     | 1.1                |
|      | L mm    | 13.5    |                    |

Locating pegs are supplied in separate bags with nuts and washers.

**LEADS CONFIGURATION EXAMPLES (on request) - Dimensions in millimeters (inches)**
**SOLDER LUGS Y**

**PCB PIN OUT**

**HORIZONTAL MOUNTING**
**FRONT AND REAR SUPPORT PLATES**

**FRONT SUPPORT PLATE**

**VERTICAL MOUNTING**

**Note**

- Standard version: Y00 W10. Other styles on request

**P11 OPTION: ROTARY SWITCH MODULES**


- Rotary switches
- Current up to 2 A
- Actuation CW or CCW position
- Sealing IP 60

The position of each switch module is free. Leads finish: Gold plated  
RS and RSI rotary switches are housed in a standard P11 module size 12.7 mm x 12.7 mm x 5.08 mm (0.5" x 0.5" x 0.2"). They have the same terminal styles as the assembled electrical modules. An assembly can comprise one or more switch modules. Switch actuation is described as seen from the shaft end.

D: means actuation in maximum CCW position

F: means actuation in maximum CW position

The switch actuation travel is 25° with a total mechanical travel of 300° ± 5° and electrical travel of electrical modules is 238° ± 10°.

**RSI SINGLE POLE SWITCH, NORMALLY OPEN**

In full CCW position, the contact between 1 and 3 is open. It is made at the beginning of the travel in CW direction.

**RSF SINGLE POLE SWITCH, NORMALLY OPEN**

In full CW position, the contact between 1 and 3 is open. It is made at the beginning of the travel in CCW direction.

**RSID SINGLE POLE CHANGEOVER**

In full CCW position, the contact is made between 3 and 2, and open between 3 and 1. Switch actuation (CW direction) reverses these positions.

**RSIF SINGLE POLE CHANGEOVER**

In full CW position, the contact is made between 1 and 2, and open between 1 and 3. Switch actuation (CCW direction) reverses these positions.

**SWITCH SPECIFICATIONS**


|                                        |                      |                                |
|----------------------------------------|----------------------|--------------------------------|
| Switching power maximum                |                      | 62.5 VA v<br>15 VA =           |
| Switching current maximum              |                      | 0.25 A 250 V v<br>0.5 A 30 V = |
| Maximum current through element        |                      | 2 A                            |
| Contact resistance                     |                      | 100 mΩ                         |
| Dielectric strength                    | Terminal to terminal | 1000 V <sub>RMS</sub>          |
|                                        | Terminal to bushing  | 2000 V <sub>RMS</sub>          |
| Maximum voltage operation              |                      | 250 V v<br>30 V =              |
| Insulation resistance between contacts |                      | 10 <sup>6</sup> MΩ             |
| Life at P <sub>max.</sub>              |                      | 10 000 actuations              |
| Minimal travel                         |                      | 25°                            |
| Operating temperature                  |                      | -40 °C to +85 °C               |

**RSI SPST:** single pole, open switch in CCW position - 2 pins

**RSF SPST:** single pole, open switch in CW position - 2 pins

**RSID SPDT:** single pole, changeover switch in CCW position - 3 pins

**RSIF SPDT:** single pole, changeover switch in CW position - 3 pins

**ELECTRICAL DIAGRAM**

**Note**

(1) Common

**ACCESSORIES**

Additional Accessories (to order separately)

[www.vishay.com/doc?51051](http://www.vishay.com/doc?51051)

Control knobs

[www.vishay.com/doc?51101](http://www.vishay.com/doc?51101)

**RELATED DOCUMENTS**
**APPLICATION NOTES**

Potentiometers and Trimmers

[www.vishay.com/doc?51001](http://www.vishay.com/doc?51001)

Guidelines for Vishay Sfernice Resistive and Inductive Components

[www.vishay.com/doc?52029](http://www.vishay.com/doc?52029)

Capabilities and Custom Options

[www.vishay.com/doc?48463](http://www.vishay.com/doc?48463)



## Disclaimer

ALL PRODUCT, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE TO IMPROVE RELIABILITY, FUNCTION OR DESIGN OR OTHERWISE.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained in any datasheet or in any other disclosure relating to any product.

Vishay makes no warranty, representation or guarantee regarding the suitability of the products for any particular purpose or the continuing production of any product. To the maximum extent permitted by applicable law, Vishay disclaims (i) any and all liability arising out of the application or use of any product, (ii) any and all liability, including without limitation special, consequential or incidental damages, and (iii) any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.

Statements regarding the suitability of products for certain types of applications are based on Vishay's knowledge of typical requirements that are often placed on Vishay products in generic applications. Such statements are not binding statements about the suitability of products for a particular application. It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application. Parameters provided in datasheets and / or specifications may vary in different applications and performance may vary over time. All operating parameters, including typical parameters, must be validated for each customer application by the customer's technical experts. Product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein.

Hyperlinks included in this datasheet may direct users to third-party websites. These links are provided as a convenience and for informational purposes only. Inclusion of these hyperlinks does not constitute an endorsement or an approval by Vishay of any of the products, services or opinions of the corporation, organization or individual associated with the third-party website. Vishay disclaims any and all liability and bears no responsibility for the accuracy, legality or content of the third-party website or for that of subsequent links.

Vishay products are not designed for use in life-saving or life-sustaining applications or any application in which the failure of the Vishay product could result in personal injury or death unless specifically qualified in writing by Vishay. Customers using or selling Vishay products not expressly indicated for use in such applications do so at their own risk. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay. Product names and markings noted herein may be trademarks of their respective owners.