



General Specification
 Current Rating: 1.5A DC /Contact, 20mA DC for LED signals
 Voltage Rating: 125V AC /Contact, 2.0 volts DC for LED signals
 Operating Environment
 Standard Temperature: -20°C~+70°C
 Industrial Temperature: -40°C~+85°C
 Humidity: 20~70%
 Contact Resistance: $\leq 30m\Omega$
 Insulation Resistance: $\geq 500M\Omega$
 Dielectric Strength: 500V AC / (50HZ) /Min
 Mating And Unmating Force: 3~20N
 Durability: 750 Cycles Min

Material Specification
 Housing: Thermo plastic, UL94V-0.
 Contact: Alloy Copper
 Shield: Alloy Copper

Please refer to the customer drawing when customer has specified

网络插座外形图

绘图: 梁飞 日期: 2022.4.18

审核: 李伟 日期:

审核: 日期:

变更单号 绘制 日期 核准: 日期:

序号	名称	材料	数量	镀层/颜色	备注
2	插针	PHOSPHOR BRONZE	16	RJ	
1	塑座	PBT	1	YELLOW	

温州瑞川电子有限公司
 WEN ZHOU RUI CHUAN ELECTRONIC CO., LTD.

品名: RCH-X56-21-12-Y (全塑) 一体
 料号: X562112Y-8000001DPY26 (RC026223)
 型号: RJ45 图号:

公差: ± 0.45
 $>10\sim 30$ ± 0.35
 ~ 10 ± 0.25
 角度: $\pm 5^\circ$
 版本: 1 of 1 单位:mm 比例: 1:1 纸张: A4

变更单号 绘制 日期 核准: 日期: