



General Specification
 Current Rating: 1.5A DC /Contact, 20mA DC for LED signals
 Voltage Rating: 125V AC /Contact, 2.0 volts DC for LED signals
 Operating Environment
 Standard Temperature: -20°C~+70°C
 Industrial Temperature: -40°C~+85°C
 Humidity: 20~70%
 Contact Resistance: ≤30mΩ
 Insulation Resistance: ≥500MΩ
 Dielectric Strength: 500V AC / (50HZ) /Min
 Mating And Umating Force: 3~20N
 Durability: 750 Cycles Min

Material Specification
 Housing :Thermo-plastic, UL94V-0.
 Contact :Alloy Copper
 Shield :Alloy Copper
 Please refer to the customer drawing when customer has specified

4	长后盖	PA46	1	BLACK	
3	短后盖	PA46	1	BLACK	
2	插针	PHOSPHOR BRONZE	16	"FU"	
1	塑座	PA46	1	BLACK	
序号	名称	材料	数量	镀层/颜色	备注

网络插座外形图



绘图: 魏飞 日期: 2022.4.8
 审核: 张德 日期:
 核准: 李华 日期:

一般公差
 90~ ±0.25
 10~30 ±0.20
 ~10 ±0.15
 角度: ±2°
 页面: 1 of 1
 品名: RCH-59-01-21 (全塑无灯)
 料号: 590121-80000010AB36 (RC02700)
 型号: RJ45 图号:
 版本: 单位: mm 比例: 1:1 纸张: A4

禁止在图面上随意涂改

A/0 新出版发行
 变更履历