



General Specification
 Current Rating: 1.5A DC /Contact, 20mA DC for LED signals
 Voltage Rating: 125V AC /Contact, 2.0 volts DC for LED signals
 Operating Environment
 Standard Temperature: -20°C~+70°C
 Industrial Temperature: -40°C~+85°C
 Humidity: 20~70%
 Contact Resistance: ≤30mΩ
 Insulation Resistance: ≥500MΩ
 Dielectric Strength: 500V AC/(50HZ)/Min
 Mating And Unmating Force: 3~20N
 Durability: 750 Cycles Min

Material Specification
 Housing: Thermoplastic, UL94V-0
 Contact: Alloy Copper
 Shield: Alloy Copper

Please refer to the customer drawing when customer has specified

网络插座外形图

绘图:	梁飞	日期:	2022.4.11
审核:	陈伟	日期:	
核准:	李华	日期:	

序号	名称	材料	数量	镀层/颜色	备注
3	后盖	PA46	1	BLACK	
2	插针	PHOSPHOR BRONZE	8	10"	
1	塑座	PA46	1	BLACK	

温州瑞川电子有限公司
 WEN ZHOU RUI CHUAN ELECTRONIC CO., LTD.

品名: RCH-56-04(全塑10P8C)
 料号: 5604-80000011AB26 (RC01253)
 型号: RJ45
 图号:
 单位:mm 比例: 1:1 纸套: A4

一般公差
 30~ ±0.25
 10~30 ±0.20
 ~10 ±0.15
 角度: ±2°
 页面: 1 of 1

图号	变更单号	绘制	日期	审核	日期
版本	变更履历	该图面	温州瑞川电子	有限	公司
A/0	新出版发行				
1	2	3			

内部使用, 不得私自复印