

# NYLON-INSULATED SPADE TERMINALS

**MAXIMUM ELECTRIC CURRENT:**

A.W.G.	22	20	18	16	14
AMP.	9	12	17	18	30


**MAXIMUM ELECTRICAL RATING: 105°C 600 VOLTS MAX.**

**INSULATION MATERIAL: NYLON**

**INSULATION COLOR:**

22-16 A.W.G.: RED ■ 16-14 A.W.G.: BLUE ■

**TERMINAL MATERIAL: COPPER**



WIRE RANGE A.W.G. mm <sup>2</sup>	ITEM NO.		STUD SIZE		DIMENSION <small>inch mm</small>							CRIMPING TOOL	Q'TY BOX	
	BRAZED SEAM	BUTTED SEAM	d2		W	F	L	E	D	d1	T			
22-16 A.W.G.	SNYB1-3.2	SNY1-3.2 *	#4	.126 3.2	.224 5.7	.256 6.5	.866 22.0	.433 11.0	.157 4.0	.067 1.7	.030 0.75	IZUMI MODEL 34 WITH DIE INDEX COLOR:RED  OR K.S. MODEL KST2000A <b>HRI-126J</b> WITH DIE INDEX COLOR:RED	1000	
	SNYBS1-3.7	SNYS1-3.7 *	#6	.146 3.7									1000	
	SNYBL1-3.7	SNYL1-3.7 *	#6	.146 3.7	.252 6.4								1000	
	SNYBLL1-3.7	SNYLL1-3.7 *	#6	.146 3.7	.283 7.2								1000	
	SNYBS1-4	SNYS1-4 *	#8	.169 4.3	.252 6.4								1000	
	SNYBM1-4	SNYM1-4 *	#8	.169 4.3	.283 7.2								1000	
	SNYBL1-4	SNYL1-4 *	#8	.169 4.3	.319 8.1								1000	
	SNYBS1-5	SNYS1-5 *	#10	.209 5.3									1000	
	0.5-1.5 mm <sup>2</sup>	SNYBL1-5	SNYL1-5 *	#10	.209 5.3								.374 9.5	1000
		SNYBS1-6	SNYS1-6 *	1/4	.252 6.4									1000
SNYBL1-6		SNYL1-6 *	1/4	.252 6.4	.472 12.0	.433 11.0	1.102 28.0	1000						
16-14 A.W.G.		SNYB2-3.2	SNY2-3.2 *	#4	.126 3.2	.224 5.7	.256 6.5	.866 22.0	.433 11.0	.177 4.5	.091 2.3	.031 0.8	IZUMI MODEL 34 WITH DIE INDEX COLOR:BLUE  OR K.S. MODEL KST2000A <b>HRI-126J</b> WITH DIE INDEX COLOR:BLUE	1000
	SNYBS2-3.7	SNYS2-3.7 *	#6	.146 3.7	1000									
	SNYBL2-3.7	SNYL2-3.7 *	#6	.146 3.7	.236 6.0	1000								
	SNYBLL2-3.7	SNYLL2-3.7 *	#6	.146 3.7	.283 7.2	1000								
	SNYBS2-4	SNYS2-4 *	#8	.169 4.3	.252 6.4	1000								
	SNYBM2-4	SNYM2-4 *	#8	.169 4.3	.283 7.2	1000								
	SNYBL2-4	SNYL2-4 *	#8	.169 4.3	.311 7.9	1000								
	SNYBS2-5	SNYS2-5 *	#10	.209 5.3		1000								
	1.5-2.5 mm <sup>2</sup>	SNYBL2-5	SNYL2-5 *	#10	.209 5.3	.366 9.3								1000
		SNYBS2-6	SNYS2-6 *	1/4	.252 6.4									1000
SNYBL2-6		SNYL2-6 *	1/4	.252 6.4	.472 12.0	.433 11.0	1.102 28.0	1000						

UL cUL ALL LISTED  
\*: ADDITIONAL CERTIFIED