


1.Features

The SDxxC Series is designed for applications requiring transient overvoltage protection capability. They are intended for use in voltage and ESD sensitive equipment such as computers, printers, business machines, communication systems, medical equipment and other applications. These devices are ideal for situations where board space is at a premium.

2.Features

- IEC61000-4-4 (EFT) 40A (5/50ns)
- 350 Watts Peak Pulse Power per ($t_p=8/20\mu s$)
- Protects one I/O line (bidirectional)
- Low clamping voltage
- Working voltages :
3V,5V,8V,12V,15V,18V,20V,24V,36V
- Low leakage current
- IEC61000-4-2 (ESD) $\pm 30kV$ (air)
 $\pm 30kV$ (contact)

3.Pinning information



SOD-323

4.Absolute Maximum Ratings $T_A= 25^\circ C$

Parameter	Symbol	Maximum	Units
ESD per IEC 61000-4-2 (Air)	V_{ESD}	± 30	kV
ESD per IEC 61000-4-2(Contact)		± 30	kV
Peak Pulse Power (8/20us)	P_{PP}	350	W
Junction Temperature	T_{OPT}	-55 to 150	$^\circ C$
Storage Temperature	T_{STG}	-55 to 150	$^\circ C$
Lead Soldering Temperature	T_L	260(10sec.)	$^\circ C$



5. Electrical Characteristics (T_{amb}=25°C)

PART NUMBER	DEVICE MARKING	V _{RWM} (V)	V _B (V)	I _T (mA)	V _{c@1A} (V)	V _c (V)		I _R (μA)	C _T (pF)
		(max.)	(min.)		(max.)	(max.)	(@A)	(max.)	(max.)
UMW SD03C	2A	3.3	4.0	1	7.5	16.0	20	40	450
UMW SD05C	2B	5.0	6.0	1	9.8	18.0	17	10	200
UMW SD08C	2C	8.0	8.5	1	13.4	24.0	15	2	120
UMW SD12C	2D	12.0	13.3	1	19.0	32.0	11	1	75
UMW SD15C	2J	15.0	16.7	1	24.0	38.0	10	1	68
UMW SD18C	2K	18.0	20.0	1	29.0	45.0	9	1	57
UMW SD20C	2L	20.0	22.3	1	35.0	50.0	8	1	52
UMW SD24C	2H	24.0	26.7	1	43.0	52.0	7	1	50
UMW SD36C	2N	36.0	40.0	1	60.0	75.0	4.5	1	35




6. Typical characteristic

<p>Figure 1: 8/20µs Waveform per IEC61000-4-5</p>	<p>Figure 2: Contact Discharge Current Waveform per IEC 61000-4-2</p>
<p>Figure 3: Voltage vs Capacitance</p>	<p>Figure 4: Voltage vs Capacitance</p>
<p>Figure 5: Clamping Voltage vs Peak Pulse Current</p>	<p>Figure 6: Clamping Voltage vs Peak Pulse Current</p>



7.SOD-323 Package Outline Dimensions




DIMENSIONS (mm are the original dimensions)

Symbol	A	b_p	C	D	E	H_E	A_1	p
Min	0.90	0.25	0.10	1.60	1.15	2.30	0.01	0.20
Max	1.20	0.40	0.15	1.80	1.35	2.80	0.10	0.50



8. Ordering information



Order Code	Marking	Package	Base QTY	Delivery Mode
UMW SD03C	2A	SOD-323	3000	Tape and reel
UMW SD05C	2B	SOD-323	3000	Tape and reel
UMW SD08C	2C	SOD-323	3000	Tape and reel
UMW SD12C	2D	SOD-323	3000	Tape and reel
UMW SD15C	2J	SOD-323	3000	Tape and reel
UMW SD18C	2K	SOD-323	3000	Tape and reel
UMW SD20C	2L	SOD-323	3000	Tape and reel
UMW SD24C	2H	SOD-323	3000	Tape and reel
UMW SD36C	2N	SOD-323	3000	Tape and reel



9.Disclaimer

UMW reserves the right to make changes to all products, specifications. Customers should obtain the latest version of product documentation and verify the completeness and currency of the information before placing an order.

When applying our products, please do not exceed the maximum rated values, as this may affect the reliability of the entire system. Under certain conditions, any semiconductor product may experience faults or failures. Buyers are responsible for adhering to safety standards and implementing safety measures during system design, prototyping, and manufacturing when using our products to prevent potential failure risks that could lead to personal injury or property damage.

Unless explicitly stated in writing, UMW products are not intended for use in medical, life-saving, or life-sustaining applications, nor for any other applications where product failure could result in personal injury or death. If customers use or sell the product for such applications without explicit authorization, they assume all associated risks.

When reselling, applying, or exporting, please comply with export control laws and regulations of China, the United States, the United Kingdom, the European Union, and other relevant countries, regions, and international organizations.

This document and any actions by UMW do not grant any intellectual property rights, whether express or implied, by estoppel or otherwise. The product names and marks mentioned herein may be trademarks of their respective owners.