


PCB board installation size  
PCB板安装尺寸



The circuit principle diagram  
电路原理图

Technical requirement  
技术要求

1. Rated voltage: DC30 100mA  
1. 额定电压: DC30 100mA
2. Insulation resistance: ≥ 100M Ω  
2. 绝缘电阻: ≥100MΩ
3. Contact resistance: ≤ 500m Ω  
3. 接触电阻: ≤500mΩ
4. Operating force: 50g ± 10g  
4. 操作力: 50g±10g
5. Service life: 50000 times  
5. 寿命: 50000次
6. Working temperature: -10 °C~+60 °C  
6. 工作温度: -10°C~ +60°C

5	Spring 弹簧	Phosphorous copper 磷铜	1	Ag plating 镀银
4	Terminal 端子脚	Brass	1	Ag plating 镀银
3	Pedestal 基座	PPA	1	Black 黑色
2	Plastic cover 塑盖	PA46	1	Black 黑色
1	Button 按钮	PA46	4	Black 黑色
NO 序号	Part name 部件名	Material 材料	QTY 数量	Remark 备注

A4				
A3				
A2				
A1				
REV	DATE	REVISION	DESCRIPTION	ISSUE



COMMON TOLERANCE	
X.XX	± 0.10
X.X	± 0.15
X	± 0.25
ANGULAR	—

UNIT	MM	PROJECTED		PRODUCT NAME:
DRAWN BY	FUYUAN	CHECKED BY	COCO	MODEL NO: TP72611
DATE	2019	APPROVAL B	ALEN	Https: www.rocpcu.tw

# ROCPCU TECHNOLOGY CO.,LTD

Copies are issued in strict confidence and shall not be reproduced or copied, or used as the basic of manufacture or sale of apparatus without permission