


NOTES:

1. Rating: 16VDC 50mA
1. 额定值: 16VDC 50mA
2. Dielectric Strength: 250V AC
2. 耐电压: 250V AC
3. Contact Resistance: ≤200mΩ Max
3. 接触电阻: ≤200mΩ
4. Insulation Resistance: ≥50MΩ
4. 绝缘电阻: ≥50MΩ
5. Operating Force: 30±10gf
5. 操作力: 30±10gf
6. Life: 20,000 times
6. 寿命: 20,000 次
7. operation temperature: -20°C~70°C
7. 工作温度: -20°C~70°C



5	Solder foot 焊锡脚	Brass	2	Ag plating 镀银
4	Pedestal 基座	PA66	1	Black 黑色
3	Shrapnel 弹片	Phosphorous copper	1	Ag plating 镀银
2	Cover 盖子	POM	1	Black 黑色
1	Press handle 按柄	POM	1	Black 黑色
NO 序号	Part name 部件名	Material 材料	QTY 数量	Remark 备注

A4				
A3				
A2				
A1				
REV	DATE	REVISION	DESCRIPTION	ISSUE



COMMON TOLERANCE	
X.XX	± 0.10
X.X	± 0.15
X	± 0.25
ANGULAR	—

UNIT	MM	PROJECTED	PRODUCT NAME:
DRAWN BY	FUYUAN	CHECKED BY	COCO
DATE	2019	APPROVAL	B
MODEL NO: TP72531		Https: www.rocpcu.tw	
ROCPCU TECHNOLOGY CO.,LTD			
Copies are issued in strict confidence and shall not be reproduced or copied, or used as the basic of manufacture or sale of apparatus without permission			