

SLIDE SWITCH

碩方精密電子開關

 www.Sofng.com

Operation:DIP/臥式 小型 6PIN 二挡位 滑动开关 [柄长可定制]



LTEM NO.:MS-201V-□ (Series)

(L9.10mm×W3.5mm×H3.50mm SLIDE-SWITCH)

表面插装 DIP

側向操作 LATERAL

精密部品 NICETY


可靠 STABILIZE

適合環保 RoHS



Technical parameter

PROJECT		LEVEL	A[better product]	B[average product]
Electrical Properties	Contact Rating		0.3A, 30V DC	
	Initial Contact Resistance		50mΩ max.	
	Insulation Resistance		100MΩ min.500V DC Skey/PD: 100MΩ min.300V DC	
Durable Performance	Withstand Voltage		300V AC for 1 minute	250 V AC for 1 minut
	There No Load		15,000 Cycles	10,000 Cycles
	Rated Load		12,000 Cycles	8,500 Cycles
	Storage temp.		-25℃~+75℃(Operating Temp:)	
	Operating Force		2. 6N. (1N. =100gram-force) ±0. 5N	
	Heat Rrsistance		IR Reflow:255℃, 5sec. Manual:350℃, 3sec.	

CIRCUIT DIAGRAM



Unit:mm



P.C.B LAYOUT

