



- 1. Rating: DC 12V 50mA**  
**1. 额定值: DC 12V 50mA**  
**2. Contact Resistance: 100mΩ MAX**  
**2. 接触电阻: 最大100mΩ**  
**3. Insulation resistance: ≥ 100M Ω**  
**3. 绝缘电阻: ≥100MΩ**  
**4. Stroke: 0.35 ± 0.10mm**  
**4. 行程: 0.35±0.10mm**  
**5. Service life: 100000 times**  
**5. 使用寿命: 100000 次**  
**6. Operating force: 260 ± 50gf**  
**6. 操作力: 260±50gf**  
**7. Operating temperature: - 20 °C ~ + 70 °C**  
**7. 使用温度: -20°C ~ + 70°C**

NO 序号	Part name 部件名	Material 材料	QTY 数量	Remark 备注
5	Terminal 端子	Brass 黄铜	4	Ag plating 镀银
4	Base 底座	PA6T	1	Black 黑色
3	Contact 弹片	SUS	1	Ag plating 镀银
2	Stem 按钮	PA6T	1	Red 红色
1	Cover 盖板	Brass 黄铜	1	Sn plating 镀锡

A4					<b>COMMON TOLERANCE</b> X.XX ± 0.10 X.X ± 0.15 X ± 0.25 <b>ANGULAR</b> —	UNIT	MM	PROJECTED		PRODUCT NAME:	
A3						DRAWN BY	FUYUAN	CHECKED BY	COCO	MODEL NO:	TP11012670
A2						DATE	2019	APPROVAL B	ALEN	Https:	www.rocpu.tw
A1						<b>ROCPCU TECHNOLOGY CO.,LTD</b>					
REV	DATE	REVISION	DESCRIPTION			ISSUE	<small>Copies are issued in strict confidence and shall not be reproduced or copied, or used as the basic of manufacture or sale of apparatus without permission</small>				